



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Intel(R) Corporation

Intel(R) D975XBX motherboard( 2.93 GHz, Intel(R) Core(TM) 2 Extreme processor X6800)

SPECfp2000 = 2836

SPECfp\_base2000 = 2836

SPEC license #: 13 Tested by: Intel Corporation Test date: Jul-2006 Hardware Avail: Jul-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	37.8	4238	37.8	4238
171.swim	3100	116	2675	116	2672
172.mgrid	1800	98.7	1823	98.7	1824
173.applu	2100	99.3	2116	99.3	2116
177.mesa	1400	50.7	2763	50.7	2763
178.galgel	2900	41.8	6931	41.8	6931
179.art	2600	25.3	10259	25.3	10259
183.quake	1300	37.5	3462	37.7	3452
187.facerec	1900	65.3	2909	65.4	2905
188.amp	2200	105	2098	104	2112
189.lucas	2000	75.8	2639	74.9	2670
191.fma3d	2100	102	2053	102	2053
200.sixtrack	1100	93.7	1174	95.0	1158
301.apsi	2600	138	1890	138	1890

### Hardware

CPU: Intel(R) Core(TM) 2 Extreme processor X6800( 2.93 GHz, 1066 MHz bus)  
CPU MHz: 2933  
FPU: Integrated  
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 32KBI + 32KBD per core  
Secondary Cache: 4MB(I+D) shared, per chip  
L3 Cache: None  
Other Cache: None  
Memory: 1 GB (2 512MB Micron MT16HTF6464AY-667B3 DDR2 667 CL5-5-5 DIMMs)  
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)  
Other Hardware: ATI Radeon X1900 XTX PCI express graphics card

### Software

Operating System: Windows XP Professional SP2  
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications  
Build 20060323Z Package ID: W\_FC\_P\_9.1.020  
Microsoft Visual Studio 2005(for libraries)  
SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -QxP -Oa -Qrcd -Qipo +FDO shlW32M.lib
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO
188.amp: -fast -Oa +FDO shlW32M.lib
189.lucas: -fast -Qprefetch- +FDO
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Intel(R) Corporation**

Intel(R) D975XBX motherboard( 2.93 GHz, Intel(R) Core(TM) 2 Extreme processor X6800)

SPECfp2000 = 2836

SPECfp\_base2000 = 2836

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 03/2006

<http://www.intel.com/products/motherboard/D975XBX/index.htm>

The system bus runs at 1066 MHz