



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon 5140 processor, 2.33 GHz

SPECfp_rate2000 = 73.6

SPECfp_rate_base2000 = 73.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

250 200 150 100 50					Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
					168.wupwise	4	73.2	101	4	73.2	101
					171.swim	4	273	52.6	4	273	52.6
					172.mgrid	4	175	47.7	4	175	47.7
					173.applu	4	190	51.2	4	190	51.2
					177.mesa	4	59.9	109	4	59.9	109
					178.galgel	4	70.2	192	4	70.2	192
					179.art	4	58.7	205	4	58.7	205
					183.equake	4	119	50.5	4	119	50.5
					187.facerec	4	94.9	92.9	4	94.9	92.9
					188.ampmp	4	143	71.6	4	143	71.6
					189.lucas	4	176	52.9	4	176	52.9
					191.fma3d	4	171	56.8	4	171	56.8
					200.sixtrack	4	125	40.7	4	125	40.7
					301.apsi	4	204	59.1	4	204	59.1

Hardware

CPU: Intel Xeon 5140 processor (2.33 GHz, 4MB SLC, 1333 MHz system bus)
 CPU MHz: 2333
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4096KB(I+D) on chip, per chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8x1024 MB DDRII-RAM PC2-5300F (CAS 5-5-5)
 Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)
 Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
 Kernel 2.6.5-7.244-smp on an x86_64
 Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
 Build 20060120 (for 64-bit applications)
 File System: ext2
 System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
 PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
 178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon 5140 processor, 2.33 GHz

SPECfp_rate2000 = 73.6

SPECfp_rate_base2000 = 73.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

This result was measured on the PRIMERGY TX300 S3. The PRIMERGY TX300 S3 and the PRIMERGY RX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>