



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB3 (3.00GHz, Intel Xeon 5160 processor)

SPECfp2000 = 2618

SPECfp_base2000 = 2620

SPEC license #01176 Tested by: Supermicro Test date: May-2006 Hardware Avail: May-2006 Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	43.2	3702	43.2	3701
171.swim	3100	124	2499	124	2499
172.mgrid	1800	102	1766	102	1766
173.applu	2100	103	2032	103	2032
177.mesa	1400	51.2	2737	51.2	2737
178.galgel	2900	40.9	7095	40.9	7097
179.art	2600	25.1	10367	25.1	10367
183.earthquake	1300	44.8	2903	44.9	2893
187.facerec	1900	75.6	2512	75.8	2508
188.ammmp	2200	108	2041	107	2054
189.lucas	2000	101	1989	101	1990
191.fma3d	2100	109	1920	109	1920
200.sixtrack	1100	92.2	1193	93.5	1176
301.apsi	2600	164	1586	164	1585

Hardware

CPU: Intel Xeon 5160 processor (3.00 GHz, 4MB L2 shared, 1333 MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 32KBI + 32KBD on chip per core
Secondary Cache: 4MB(I+D) on chip (per chip)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 2.0GB 667MHz FBDIMM ECC CL5
Disk Subsystem: 1X 30GB Fujitsu MHS2030AT SATA HDD
Other Hardware: N/A

Software

Operating System: Windows server 2003 Enterprise Edition 32-bits W/ SP1
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_FC_P_9.1.020
Microsoft Visual Studio 2005 (for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for 177.mesa: -fast +FDO shlw32M.lib
Base tuning for 179.art: -fast +FDO shlw32M.lib
Base tuning for 183.earthquake: -fast +FDO shlw32M.lib
Base tuning for 188.ammmp: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.earthquake: -QxP -Oa -Qrcd -Qipo +FDO shlw32M.lib
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Supermicro

Motherboard X7DB3 (3.00GHz, Intel Xeon 5160 processor)

SPECfp2000 = 2618

SPECfp_base2000 = 2620

SPEC license #01176 | Tested by: Supermicro | Test date: May-2006 | Hardware Avail: May-2006 | Software Avail: Mar-2006

Notes/Tuning Information (Continued)

```
187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO
188.amp: -fast -Oa +FDO shlw32M.lib
189.lucas: -fast -Qprefetch- +FDO
191.fma3d: basepeak=yes
200.sixtrack: -Qipo -QxP +FDO
301.apsi: -fast +FDO
```

Tested systems can be used with SC825TQ-R700LPV case,
To ensure system stability, a 550W (minimum) ATX power supply
[4-pin (+12V), 8-pin (+12V) and 24-pin are required]

Product description located as of X7DB3:

<http://www.supermicro.com/products/motherboard/Xeon1333/5000P/X7DB3.cfm>

The system bus runs at 1333 MHz