



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3550 (2.0 GHz Xeon 5130, 4MB L2 Cache)

SPECfp2000 = --

SPECfp_base2000 = 2079

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	54.8	2917			
171.swim	3100	125	2475			
172.mgrid	1800	138	1307			
173.applu	2100	123	1706			
177.mesa	1400	70.5	1985			
178.galgel	2900	59.6	4867			
179.art	2600	37.4	6957			
183.quake	1300	51.5	2525			
187.facerec	1900	86.9	2185			
188.amp	2200	149	1472			
189.lucas	2000	91.5	2187			
191.fma3d	2100	139	1515			
200.sixtrack	1100	137	802			
301.apsi	2600	215	1208			

Hardware

CPU: Intel Xeon processor 5130 (2.0 GHz, 1333 MHz bus)
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1, 2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
Secondary Cache: 4096KB(I+D) on chip (per chip)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1024 MB ECC PC2-5300F
Disk Subsystem: 73GB SAS 15K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
Build 20060323Z
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
```