



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision M90 (Intel T7600,
2.33 GHz)

SPECint_rate2006 = 23.8

SPECint_rate_base2006 = 23.0

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Dec-2006

Hardware Availability: Sep-2006

Software Availability: Nov-2006



SPECint_rate_base2006 = 23.0

SPECint_rate2006 = 23.8

Hardware

CPU Name: Intel Core 2 Duo T7600
 CPU Characteristics: 667 MHz System Bus
 CPU MHz: 2333
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 2 GB (2x1 GB 667 MHz CL5 DDR2 SDRAM)
 Disk Subsystem: 1 x 80 GB SATA 7200 RPM
 Other Hardware: None

Software

Operating System: Windows XP Professional SP2
 Compiler: Intel C++ Compiler 9.1 for IA32 (20061103Z)
 Microsoft Visual Studio 2005
 MicroQuill SmartHeap Library 8.0
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: None



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision M90 (Intel T7600,
2.33 GHz)

SPECint_rate2006 = 23.8

SPECint_rate_base2006 = 23.0

CPU2006 license: 55

Test date: Dec-2006

Test sponsor: Dell Inc.

Hardware Availability: Sep-2006

Tested by: Dell Inc.

Software Availability: Nov-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	613	31.9	611	32.0	613	31.9	2	558	35.0	558	35.0	559	34.9
401.bzip2	2	944	20.4	958	20.2	952	20.3	2	944	20.4	958	20.2	952	20.3
403.gcc	2	1254	12.8	1250	12.9	1279	12.6	2	1225	13.1	1218	13.2	1249	12.9
429.mcf	2	673	27.1	702	26.0	702	26.0	2	688	26.5	687	26.5	673	27.1
445.gobmk	2	718	29.2	714	29.4	714	29.4	2	638	32.9	638	32.9	640	32.8
456.hammer	2	962	19.4	962	19.4	962	19.4	2	962	19.4	962	19.4	962	19.4
458.sjeng	2	869	27.8	865	28.0	865	28.0	2	789	30.7	793	30.5	797	30.4
462.libquantum	2	2703	15.3	2746	15.1	2700	15.4	2	2725	15.2	2636	15.7	2731	15.2
464.h264ref	2	933	47.4	933	47.4	933	47.5	2	912	48.5	913	48.5	914	48.4
471.omnetpp	2	752	16.6	726	17.2	752	16.6	2	713	17.5	701	17.8	714	17.5
473.astar	2	745	18.8	746	18.8	750	18.7	2	750	18.7	750	18.7	755	18.6
483.xalancbmk	2	494	27.9	491	28.1	493	28.0	2	489	28.2	492	28.1	497	27.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

32-bit binaries were built on Windows XP Professional x64 Edition

Base Compiler Invocation

C benchmarks:
icl -QC99

C++ benchmarks:
icl

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32

464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword

Base Optimization Flags

C benchmarks:
-fast /F512000000 shlw32M.lib

-link /FORCE:MULTIPLE

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision M90 (Intel T7600,
2.33 GHz)

SPECint_rate2006 = 23.8

SPECint_rate_base2006 = 23.0

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Dec-2006

Hardware Availability: Sep-2006

Software Availability: Nov-2006

Base Optimization Flags (Continued)

C++ benchmarks:

```
-fast -Qcxx_features /F512000000 shlw32M.lib  
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qc99
```

C++ benchmarks:

```
icl
```

Peak Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32
```

```
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
```

```
483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast  
/F512000000 shlw32M.lib -link /FORCE:MULTIPLE
```

```
401.bzip2: basepeak = yes
```

```
403.gcc: Same as 400.perlbench
```

```
429.mcf: ONESTEP -fast /F512000000 shlw32M.lib  
-link /FORCE:MULTIPLE
```

```
445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000  
shlw32M.lib -link /FORCE:MULTIPLE
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision M90 (Intel T7600,
2.33 GHz)

SPECint_rate2006 = 23.8

SPECint_rate_base2006 = 23.0

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Dec-2006

Hardware Availability: Sep-2006

Software Availability: Nov-2006

Peak Optimization Flags (Continued)

456.hmmer: basepeak = yes

458.sjeng: Same as 400.perlbench

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:

471.omnetpp: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qcxx_features /F512000000 shlw32M.lib
-link /FORCE:MULTIPLE

473.astar: Same as 471.omnetpp

483.xalancbmk: ONESTEP -fast -Qcxx_features /F512000000 shlw32M.lib
-link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.20090715.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/dell.cpu2006.ic91.flags.20090715.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 10:56:40 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 9 January 2007.