SPEC® CINT2006 Result

IBM Corporation

IBM System x3250 (Intel Xeon X3220)

$SPECint^{®}\_rate2006 =$ Not Run

$SPECint\_rate\_base2006 =$ 44.1

Benchmark	Copies	Result
400.perlbench	4	69.2
401.bzip2	4	43.3
403.gcc	4	21.7
429.mcf	4	45.5
445.gobmk	4	61.5
456.hmmer	4	40.4
458.sjeng	4	58.5
462.libquantum	4	22.7
464.h264ref	4	99.4
471.omnetpp	4	27.8
473.astar	4	34.7
483.xalancbmk	4	58.4

SPECint_rate_base2006 = 44.1

Hardware

CPU Name:	Intel Xeon X3220
CPU Characteristics:	1066MHz system bus
CPU MHz:	2400
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	8 GB (4 x 2GB PC2-5300 ECC)
Disk Subsystem:	1 x 73 GB SAS, 10000 RPM
Other Hardware:	None

Software

Operating System:	Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler:	Intel C++ Compiler for IA32 version 9.1 Build no 20060816 Microsoft Visual Studio .Net 2003 (for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	Not Applicable
Other Software:	Smart Heap Library, Version 8

SPEC CINT2006 Result
Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3250 (Intel Xeon X3220)

SPECint_rate2006 =   Not Run

SPECint_rate_base2006 = 44.1

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Jan-2007
Hardware Availability: Feb-2007
Software Availability: Aug-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	567	68.9	**565**	**69.2**	564	69.3							
401.bzip2	4	895	43.1	890	43.4	**892**	**43.3**							
403.gcc	4	1492	21.6	1481	21.7	**1487**	**21.7**							
429.mcf	4	809	45.1	**801**	**45.5**	800	45.6							
445.gobmk	4	**682**	**61.5**	683	61.4	682	61.6							
456.hmmer	4	922	40.5	**923**	**40.4**	923	40.4							
458.sjeng	4	827	58.5	827	58.5	**827**	**58.5**							
462.libquantum	4	3696	22.4	3651	22.7	**3655**	**22.7**							
464.h264ref	4	891	99.3	**890**	**99.4**	890	99.5							
471.omnetpp	4	905	27.6	**898**	**27.8**	897	27.9							
473.astar	4	812	34.6	**809**	**34.7**	809	34.7							
483.xalancbmk	4	473	58.3	473	58.4	**473**	**58.4**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Base Compiler Invocation

C benchmarks:
```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:
```
icl -Qvc7.1
```

Base Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
```

Base Optimization Flags

C benchmarks:
```
-fast /F512000000 shlw32m.lib          -link /FORCE:MULTIPLE
```

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlw32m.lib
          -link /FORCE:MULTIPLE
```

SPEC CINT2006 Result
Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 =   Not Run

IBM System x3250 (Intel Xeon X3220)

SPECint_rate_base2006 = 44.1

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.xml`

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:18:26 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 February 2007.