



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = Not Run

IBM System x3200 (Intel Xeon X3220)

SPECint_rate_base2006 = 43.4

CPU2006 license: 11


Test date: Jan-2007

Test sponsor: IBM Corporation

Hardware Availability: Feb-2007

Tested by: IBM Corporation

Software Availability: Aug-2006



Hardware

CPU Name: Intel Xeon X3220
 CPU Characteristics: 1066MHz system bus
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (4 x 2GB PC2-5300 ECC)
 Disk Subsystem: 1 x 80 GB SATA, 7200 RPM
 Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
 Compiler: Intel C++ Compiler for IA32 version 9.1 Build no 20060816
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: Not Applicable
 Other Software: Smart Heap Library, Version 8



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = Not Run

IBM System x3200 (Intel Xeon X3220)

SPECint_rate_base2006 = 43.4

CPU2006 license: 11

Test date: Jan-2007

Test sponsor: IBM Corporation

Hardware Availability: Feb-2007

Tested by: IBM Corporation

Software Availability: Aug-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	567	68.9	566	69.1	566	69.0							
401.bzip2	4	904	42.7	906	42.6	901	42.8							
403.gcc	4	1537	21.0	1519	21.2	1546	20.8							
429.mcf	4	837	43.6	827	44.1	827	44.1							
445.gobmk	4	684	61.3	684	61.4	683	61.4							
456.hmmer	4	923	40.4	923	40.4	923	40.4							
458.sjeng	4	831	58.2	831	58.2	831	58.2							
462.libquantum	4	3826	21.7	3780	21.9	3789	21.9							
464.h264ref	4	891	99.3	891	99.3	892	99.2							
471.omnetpp	4	934	26.8	927	27.0	928	26.9							
473.astar	4	825	34.1	820	34.3	822	34.2							
483.xalancbmk	4	484	57.1	483	57.2	483	57.2							

Results appear in the order in which they were run. **Bold underlined** text indicates a median measurement.

Base Compiler Invocation

C benchmarks:

icl -Qvc7.1 -Qc99

C++ benchmarks:

icl -Qvc7.1

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32

464.h264ref: -DSPEC_CPU_NO_INNTYPES -DWIN32

Base Optimization Flags

C benchmarks:

-fast /F512000000 shlw32m.lib

-link /FORCE:MULTIPLE

C++ benchmarks:

```
-fast -Qcxx_features /F512000000 shlw32m.lib  
        -link /FORCE:MULTIPLE
```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = Not Run

IBM System x3200 (Intel Xeon X3220)

SPECint_rate_base2006 = 43.4

CPU2006 license: 11

Test date: Jan-2007

Test sponsor: IBM Corporation

Hardware Availability: Feb-2007

Tested by: IBM Corporation

Software Availability: Aug-2006

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 10:15:14 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 February 2007.