



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = Not Run

IBM BladeCenter HS21 XM (Intel Xeon 5130)

SPECint_rate_base2006 = 41.0

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jan-2007

Hardware Availability: Feb-2007

Software Availability: Aug-2006



Hardware

CPU Name: Intel Xeon 5130
CPU Characteristics: 1333MHz system bus
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip
L3 Cache: None
Other Cache: None
Memory: 16 GB (8 x 2GB DDR2-5300F ECC)
Disk Subsystem: 1 x 74 GB SAS, 1000 RPM
Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler: Intel C++ Compiler for IA32 version 9.1 Build no 20060816
Auto Parallel: No
File System: NTFS
System State: Default
Base Pointers: 32-bit
Peak Pointers: Not Applicable
Other Software: Smart Heap Library, Version 8



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = Not Run

IBM BladeCenter HS21 XM (Intel Xeon 5130)

SPECint_rate_base2006 = 41.0

CPU2006 license: 11

Test date: Jan-2007

Test sponsor: IBM Corporation

Hardware Availability: Feb-2007

Tested by: IBM Corporation

Software Availability: Aug-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	686	57.0	685	57.0	685	57.0							
401.bzip2	4	1130	34.2	1128	34.2	1126	34.3							
403.gcc	4	1354	23.8	1360	23.7	1355	23.8							
429.mcf	4	834	43.7	836	43.6	835	43.7							
445.gobmk	4	808	51.9	806	52.0	808	52.0							
456.hmmer	4	1106	33.7	1106	33.7	1106	33.7							
458.sjeng	4	986	49.1	986	49.1	986	49.1							
462.libquantum	4	2881	28.8	2880	28.8	2877	28.8							
464.h264ref	4	1077	82.2	1077	82.2	1077	82.2							
471.omnetpp	4	804	31.1	804	31.1	804	31.1							
473.astar	4	845	33.2	846	33.2	846	33.2							
483.xalancbmk	4	524	52.6	525	52.6	524	52.6							

Results appear in the order in which they were run. **Bold underlined** text indicates a median measurement.

Base Compiler Invocation

C benchmarks:

icl -Qvc7.1 -Qc99

C++ benchmarks:

icl -Qvc7.1

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32

464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Base Optimization Flags

C benchmarks:

-fast /F512000000 shlw32m.lib

-link /FORCE:MULTIPLE

C++ benchmarks:

```
-fast -Qcxx_features /F512000000 shlw32m.lib  
        -link /FORCE:MULTIPLE
```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint_rate2006 = Not Run

IBM BladeCenter HS21 XM (Intel Xeon 5130)

SPECint_rate_base2006 = 41.0

CPU2006 license: 11

Test date: Jan-2007

Test sponsor: IBM Corporation

Hardware Availability: Feb-2007

Tested by: IBM Corporation

Software Availability: Aug-2006

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 10:41:43 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 March 2007.