



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECint®\_rate2006 = 34.5

ProLiant ML370 G5  
(1.86 GHz, Intel Xeon processor E5320)

SPECint\_rate\_base2006 = 33.3

CPU2006 license: 3


Test date: Feb-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Nov-2006

Tested by: Hewlett-Packard Company

Software Availability: Nov-2006



### Hardware

CPU Name: Intel Xeon E5320  
 CPU Characteristics: 1.86 GHz, 2x4 MB L2 shared, 1066 MHz system bus  
 CPU MHz: 1860  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8x2 GB PC2-5300F CL5)  
 Disk Subsystem: 1x72 GB 10 K SAS  
 Other Hardware: None

### Software

Operating System: Windows Server 2003 Enterprise x64 Edition  
 Compiler: Intel C++ Compiler for 32-bit applications, Version 9.1, Build 20061103Z  
 Package ID: W\_CC\_C\_9.1.033  
 Microsoft Visual Studio .NET 2003 (v7.1.3088, for libraries)  
 Auto Parallel: No  
 File System: NTFS  
 System State: Default  
 Base Pointers: 32-bit  
 Peak Pointers: 32-bit  
 Other Software: MicroQuill SmartHeap Library 8.0



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECint\_rate2006 = 34.5

ProLiant ML370 G5  
(1.86 GHz, Intel Xeon processor E5320)

SPECint\_rate\_base2006 = 33.3

CPU2006 license: 3  
Test sponsor: Hewlett-Packard Company  
Tested by: Hewlett-Packard Company

Test date: Feb-2007  
Hardware Availability: Nov-2006  
Software Availability: Nov-2006

## Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	747	52.3	746	52.4	<b>747</b>	<b>52.3</b>	4	684	57.1	684	57.2	<b>684</b>	<b>57.2</b>
401.bzip2	4	1270	30.4	1264	30.5	<b>1268</b>	<b>30.5</b>	4	1237	31.2	<b>1238</b>	<b>31.2</b>	1241	31.1
403.gcc	4	1810	17.8	<b>1804</b>	<b>17.9</b>	1797	17.9	4	1787	18.0	<b>1787</b>	<b>18.0</b>	1777	18.1
429.mcf	4	1130	32.3	<b>1131</b>	<b>32.3</b>	1133	32.2	4	1130	32.3	<b>1131</b>	<b>32.3</b>	1133	32.2
445.gobmk	4	882	47.6	881	47.6	<b>881</b>	<b>47.6</b>	4	783	53.6	<b>785</b>	<b>53.5</b>	787	53.3
456.hammer	4	1198	31.2	1198	31.2	<b>1198</b>	<b>31.2</b>	4	<b>1166</b>	<b>32.0</b>	1166	32.0	1166	32.0
458.sjeng	4	1067	45.4	1066	45.4	<b>1066</b>	<b>45.4</b>	4	<b>980</b>	<b>49.4</b>	981	49.4	980	49.4
462.libquantum	4	5374	15.4	5380	15.4	<b>5378</b>	<b>15.4</b>	4	5376	15.4	<b>5376</b>	<b>15.4</b>	5373	15.4
464.h264ref	4	1165	76.0	1164	76.1	<b>1164</b>	<b>76.0</b>	4	1141	77.6	<b>1140</b>	<b>77.6</b>	1140	77.6
471.omnetpp	4	1096	22.8	<b>1097</b>	<b>22.8</b>	1098	22.8	4	<b>1068</b>	<b>23.4</b>	1068	23.4	1068	23.4
473.astar	4	<b>1053</b>	<b>26.7</b>	1054	26.7	1053	26.7	4	<b>1056</b>	<b>26.6</b>	1056	26.6	1057	26.6
483.xalancbmk	4	<b>651</b>	<b>42.4</b>	650	42.4	653	42.3	4	636	43.4	<b>636</b>	<b>43.4</b>	635	43.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Platform Notes

Power Regulator set to Static High Performance Mode in BIOS.  
Adjacent Sector Prefetch disabled in BIOS.

## Base Compiler Invocation

C benchmarks:  
icl -Qvc7.1 -Qc99  
C++ benchmarks:  
icl -Qvc7.1

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32  
464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

## Base Optimization Flags

C benchmarks:  
-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECint\_rate2006 = 34.5**

ProLiant ML370 G5  
(1.86 GHz, Intel Xeon processor E5320)

**SPECint\_rate\_base2006 = 33.3**

**CPU2006 license:** 3

**Test date:** Feb-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Nov-2006

**Tested by:** Hewlett-Packard Company

**Software Availability:** Nov-2006

## Base Optimization Flags (Continued)

C++ benchmarks:

```
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE
```

## Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

## Peak Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

## Peak Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
```

## Peak Optimization Flags

C benchmarks:

```
400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000
shlw32m.lib -link /FORCE:MULTIPLE
```

```
401.bzip2: Same as 400.perlbench
```

```
403.gcc: Same as 400.perlbench
```

```
429.mcf: basepeak = yes
```

```
445.gobmk: Same as 400.perlbench
```

```
456.hmmmer: Same as 400.perlbench
```

```
458.sjeng: Same as 400.perlbench
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECint\_rate2006 = 34.5**

ProLiant ML370 G5  
(1.86 GHz, Intel Xeon processor E5320)

**SPECint\_rate\_base2006 = 33.3**

**CPU2006 license:** 3

**Test date:** Feb-2007

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Nov-2006

**Tested by:** Hewlett-Packard Company

**Software Availability:** Nov-2006

## Peak Optimization Flags (Continued)

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:

-Qprof\_gen(pass 1) -Qprof\_use(pass 2) -fast -Qcxx\_features  
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 10:48:10 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 20 March 2007.