



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ965GF motherboard (Intel Core 2 Quad Q6700)

SPECint®2006 = 19.7

SPECint_base2006 = 17.6

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2007

Hardware Availability: Jul-2007

Software Availability: Aug-2006



Hardware

CPU Name: Intel Core 2 Quad Q6700
 CPU Characteristics: 2.67 GHz, 1066 MHz bus
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 2 GB (2 1GB Micron MT16HTF12864AY-80ED4 DDR2 800, CL5)
 Disk Subsystem: Seagate ST3320620AS 320GB Barracuda 7200.10 NCQ SATA II
 Other Hardware: None

Software

Operating System: Windows Vista32 Ultimate
 Compiler: Intel C++ Compiler for IA32 version 10.0
 Build 20070426 Package ID: W_CC_P_10.0.025
 Microsoft Visual Studio .Net 2003 (for libraries)
 Auto Parallel: No
 File System: NTFS
 System State: Default
 Base Pointers: 32-bit
 Peak Pointers: 32-bit
 Other Software: SmartHeap Library Version 8.0 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ965GF motherboard (Intel Core 2 Quad Q6700)

SPECint2006 = 19.7

SPECint_base2006 = 17.6

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2007

Hardware Availability: Jul-2007

Software Availability: Aug-2006

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	513	19.0	513	19.0	513	19.1	446	21.9	446	21.9	445	22.0
401.bzip2	682	14.1	682	14.1	684	14.1	658	14.7	659	14.6	662	14.6
403.gcc	695	11.6	703	11.4	697	11.5	442	18.2	442	18.2	443	18.2
429.mcf	367	24.9	367	24.9	367	24.9	367	24.9	367	24.9	367	24.9
445.gobmk	596	17.6	596	17.6	596	17.6	536	19.6	536	19.6	536	19.6
456.hammer	667	14.0	668	14.0	667	14.0	660	14.1	659	14.2	659	14.2
458.sjeng	768	15.8	768	15.8	768	15.8	685	17.7	684	17.7	685	17.7
462.libquantum	831	24.9	832	24.9	832	24.9	648	32.0	648	32.0	649	31.9
464.h264ref	813	27.2	814	27.2	815	27.2	766	28.9	766	28.9	768	28.8
471.omnetpp	408	15.3	408	15.3	408	15.3	373	16.7	372	16.8	373	16.7
473.astar	523	13.4	523	13.4	523	13.4	487	14.4	487	14.4	487	14.4
483.xalancbmk	323	21.4	323	21.3	324	21.3	320	21.6	320	21.6	320	21.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
 Product description located as of 7/2007:
<http://www.intel.com/products/motherboard/DQ965GF/index.htm>
 The system bus runs at 1066 MHz
 System was configured with integrated graphics card
 Binaries were built on Windows XP Professional SP2 with 4GB of RAM and /3GB boot switch

Base Compiler Invocation

C benchmarks:
 icl -Qvc7.1 -Qc99

C++ benchmarks:
 icl -Qvc7.1

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32
 464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ965GF motherboard (Intel Core 2 Quad Q6700)

SPECint2006 =

19.7

SPECint_base2006 =

17.6

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2007

Hardware Availability: Jul-2007

Software Availability: Aug-2006

Base Optimization Flags

C benchmarks:

-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:

-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:

icl -Qvc7.1 -Qc99

C++ benchmarks:

icl -Qvc7.1

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Peak Optimization Flags

C benchmarks:

400.perlbenc: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qprefetch /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

401.bzip2: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000
shlw32m.lib -link /FORCE:MULTIPLE

403.gcc: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000
-link /FORCE:MULTIPLE

429.mcf: basepeak = yes

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DQ965GF motherboard (Intel Core 2 Quad Q6700)

SPECint2006 = 19.7

SPECint_base2006 = 17.6

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2007

Hardware Availability: Jul-2007

Software Availability: Aug-2006

Peak Optimization Flags (Continued)

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2 -Qipo
-Qprec_div- -Qansi-alias /F512000000
-link /FORCE:MULTIPLE

456.hmmer: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2
-Qansi-alias /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

458.sjeng: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll4
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

462.libquantum: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll4
-Ob0 -Qprefetch -Qopt-streaming-stores:always /F512000000
shlw32m.lib -link /FORCE:MULTIPLE

464.h264ref: Same as 456.hmmer

C++ benchmarks:

-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.42.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.42.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:54:28 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 August 2007.