



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B240
(Intel Xeon E3113, 3.00 GHz)

SPECint®2006 = 24.4

SPECint_base2006 = 20.8

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Oct-2008

Hardware Availability: Jun-2008

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon E3113
 CPU Characteristics: 1333 MHz system bus
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 6 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 8 GB (4x2 GB) FB-DIMM PC2-5300F ECC CL5
 Disk Subsystem: 1x73 GB SAS, 15000 RPM
 Other Hardware: None

Software

Operating System: SUSE LINUX Enterprise Server 10 (x86_64) SP1
 Kernel 2.6.16.46-0.12-smp
 Compiler: Intel C++ Compiler 10.1 for Linux
 Build 20070913 Package ID: l_cc_p_10.1.008
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Binutils 2.17.50.0.15
 SmartHeap library V8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B240
(Intel Xeon E3113, 3.00 GHz)

SPECint2006 = 24.4

SPECint_base2006 = 20.8

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Oct-2008
Hardware Availability: Jun-2008
Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	501	19.5	<u>497</u>	<u>19.6</u>	497	19.7	397	24.6	<u>397</u>	<u>24.6</u>	399	24.5
401.bzip2	<u>584</u>	<u>16.5</u>	584	16.5	593	16.3	539	17.9	<u>539</u>	<u>17.9</u>	538	17.9
403.gcc	412	19.5	<u>412</u>	<u>19.5</u>	411	19.6	382	21.1	381	21.1	<u>381</u>	<u>21.1</u>
429.mcf	367	24.8	<u>367</u>	<u>24.9</u>	366	24.9	<u>342</u>	<u>26.7</u>	342	26.7	342	26.6
445.gobmk	541	19.4	540	19.4	<u>540</u>	<u>19.4</u>	482	21.8	<u>482</u>	<u>21.8</u>	483	21.7
456.hammer	593	15.7	<u>593</u>	<u>15.7</u>	593	15.7	341	27.4	<u>341</u>	<u>27.4</u>	342	27.3
458.sjeng	660	18.3	<u>661</u>	<u>18.3</u>	662	18.3	590	20.5	591	20.5	<u>591</u>	<u>20.5</u>
462.libquantum	609	34.0	<u>606</u>	<u>34.2</u>	605	34.3	<u>386</u>	<u>53.6</u>	385	53.8	386	53.6
464.h264ref	701	31.6	<u>699</u>	<u>31.6</u>	699	31.7	666	33.2	670	33.0	<u>670</u>	<u>33.0</u>
471.omnetpp	364	17.2	359	17.4	<u>359</u>	<u>17.4</u>	<u>329</u>	<u>19.0</u>	330	18.9	329	19.0
473.astar	<u>455</u>	<u>15.4</u>	455	15.4	457	15.4	411	17.1	<u>411</u>	<u>17.1</u>	412	17.1
483.xalancbmk	<u>269</u>	<u>25.7</u>	268	25.7	269	25.6	<u>269</u>	<u>25.7</u>	268	25.7	269	25.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to null
```

Platform Notes

BIOS Settings:
Hardware Prefetcher = Enabled
Adjacent Cache Line Prefetch = Enabled

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B240
(Intel Xeon E3113, 3.00 GHz)

SPECint2006 = 24.4

SPECint_base2006 = 20.8

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Oct-2008
Hardware Availability: Jun-2008
Software Availability: Nov-2007

Base Portability Flags (Continued)

462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -vec-guard-write -parallel -par-runtime-control

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/cpu2006/lib -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B240
(Intel Xeon E3113, 3.00 GHz)

SPECint2006 = 24.4

SPECint_base2006 = 20.8

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Oct-2008
Hardware Availability: Jun-2008
Software Availability: Nov-2007

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmcr: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive
-auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs -L/spec/cpu2006/lib -lsmarheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs -L/spec/cpu2006/lib -lsmarheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale B240
(Intel Xeon E3113, 3.00 GHz)

SPECint2006 = 24.4

SPECint_base2006 = 20.8

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Oct-2008
Hardware Availability: Jun-2008
Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/EM64T_Intel101_int_flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/EM64T_Intel101_int_flags.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 20:19:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 11 November 2008.