



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECint®2006 = 29.7

Asus P5E3 Premium (Intel Core 2 Extreme QX9770)

SPECint_base2006 = 27.0

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2008

Hardware Availability: Apr-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Core 2 Extreme QX9770
CPU Characteristics:
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
CPU(s) orderable: 1 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache: None
Other Cache: None
Memory: 4 GB (4 x 1GB Corsair CM3X1024-1333C9DHX DDR3-1333 CL9)
Disk Subsystem: 80 GB Intel X-25M SATA Solid-State Drive
Other Hardware: None

Software

Operating System: Windows Vista Ultimate w/ SP1 (64-bit)
Compiler: Intel C++ Compiler Professional 11.0 for IA32 Build 20080930 Package ID: w_cproc_p_11.0.054 Microsoft Visual Studio 2008 (for libraries)
Auto Parallel: Yes
File System: NTFS
System State: Default
Base Pointers: 32-bit
Peak Pointers: 32-bit
Other Software: None SmartHeap Library Version 8.1 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.
(Test Sponsor: Intel Corporation)

SPECint2006 = 29.7

Asus P5E3 Premium (Intel Core 2 Extreme QX9770)

SPECint_base2006 = 27.0

CPU2006 license: 13

Test date: Oct-2008

Test sponsor: Intel Corporation

Hardware Availability: Apr-2008

Tested by: Intel Corporation

Software Availability: Nov-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
400.perlbench	465	21.0	467	20.9	465	21.0	338	28.9	338	28.9	338	28.9
401.bzip2	531	18.2	536	18.0	533	18.1	527	18.3	528	18.3	529	18.3
403.gcc	374	21.5	374	21.5	375	21.5	322	25.0	327	24.7	318	25.3
429.mcf	252	36.2	252	36.2	252	36.2	252	36.2	252	36.2	252	36.1
445.gobmk	487	21.5	487	21.5	487	21.5	446	23.5	446	23.5	446	23.5
456.hmmer	515	18.1	515	18.1	515	18.1	422	22.1	422	22.1	422	22.1
458.sjeng	547	22.1	547	22.1	547	22.1	521	23.2	521	23.2	521	23.2
462.libquantum	111	186	111	188	112	186	111	186	111	188	112	186
464.h264ref	627	35.3	627	35.3	627	35.3	585	37.8	585	37.8	585	37.8
471.omnetpp	307	20.3	307	20.3	307	20.3	266	23.5	266	23.5	266	23.5
473.astar	406	17.3	406	17.3	406	17.3	358	19.6	358	19.6	358	19.6
483.xalancbmk	272	25.4	272	25.4	272	25.4	272	25.4	272	25.4	272	25.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

The system bus runs at 1600 MHz

System was configured with nVidia GTX 280 discrete graphics card

Binaries were built on Windows Vista Ultimate (32-bit)

OMP_NUM_THREADS set to number of logical processors as seen by the OS

KMP_AFFINITY set to physical,0

Base Compiler Invocation

C benchmarks:

icl -Qvc9 -Qc99

C++ benchmarks:

icl -Qvc9

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32

464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECint2006 = 29.7

Asus P5E3 Premium (Intel Core 2 Extreme QX9770)

SPECint_base2006 = 27.0

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2008

Hardware Availability: Apr-2008

Software Availability: Nov-2008

Base Optimization Flags

C benchmarks:

```
-QxSSE4.1 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel  
-Qpar-runtime-control -Qvec-guard-write /F512000000
```

C++ benchmarks:

```
-QxSSE4.1 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features  
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qc99
```

C++ benchmarks:

```
icl -Qvc9
```

Peak Portability Flags

```
403.gcc: -DSPEC_CPU_WIN32
```

```
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
```

```
483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -QxSSE4.1(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE
```

```
401.bzip2: -QxSSE4.1(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias  
/F512000000
```

```
403.gcc: -QxSSE4.1(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- /F512000000
```

Continued on next page



SPEC CINT2006 Result Copyright © 2006-2014 Standard Performance Evaluation Corporation

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc. (Test Sponsor: Intel Corporation)	SPECint2006 = 29.7 SPECint_base2006 = 27.0
Asus P5E3 Premium (Intel Core 2 Extreme QX9770)	
CPU2006 license: 13	Test date: Oct-2008
Test sponsor: Intel Corporation	Hardware Availability: Apr-2008
Tested by: Intel Corporation	Software Availability: Nov-2008

Peak Optimization Flags (Continued)

```
429.mcf: -QxSSE4.1 -Qipo -O3 -Qprec-div- -Qopt-prefetch  
/F512000000
```

```
445.gobmk: -QxSSE4.1(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O2 -Qprec-div- -Qansi-alias /F51200000
```

456.hmmr: -QxSSE4.1 -Qipo -O3 -Qprec-div- -Qunroll12 -Qansi-alias
/F512000000

458.sjeng: -QxSSE4 .1(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 /F51200000

462.libquantum: basepeak = yes

464.h264ref: -QxSSE4 .1(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Oipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias /F512000000

C++ benchmarks:

```
471.omnetpp: -QxSSE4.1(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
           -Qipo -O3 -Qprec-div- -Qansi-alias
           -Qopt-ra-region-strategy=block /F512000000 shlw32m.lib
           -link /FORCE:MULTIPLE
```

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca= alloca

The flags files that were used to format this result can be browsed at [here](#).

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.20090713.html>
<http://www.spec.org/cpu2006/flags/Intel-Win32-Platform.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.20090713.xml>
<http://www.spec.org/cpu2006/flags/Intel-Win32-Platform.xml>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

SPECint2006 = 29.7

Asus P5E3 Premium (Intel Core 2 Extreme QX9770)

SPECint_base2006 = 27.0

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Oct-2008

Hardware Availability: Apr-2008

Software Availability: Nov-2008

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 20:15:23 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 11 November 2008.