



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp®2006 = 22.2**

Dell Precision R5400 (Intel Xeon E5450, 3.00 GHz)

**SPECfp\_base2006 = 21.5**

CPU2006 license: 55


Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Dec-2008

Hardware Availability: Oct-2008

Software Availability: Nov-2008



## Hardware

CPU Name: Intel Xeon E5450  
 CPU Characteristics: 1333 MHz Bus Speed  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

## Software

Operating System: Windows Vista Business SP1 (64-bit)  
 Compiler: Intel C++ Compiler for Intel 64, Version 11.0  
 Build 20080930 Package ID: w\_cproc\_p\_11.0.061  
 Intel Visual Fortran Compiler for Intel 64,  
 Version 11.0  
 Build 20080930 Package ID: w\_cprof\_p\_11.0.061  
 Microsoft Visual Studio 2008 SP1  
 Auto Parallel: Yes  
 File System: NTFS

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp2006 = 22.2**

Dell Precision R5400 (Intel Xeon E5450, 3.00 GHz)

**SPECfp\_base2006 = 21.5**

CPU2006 license: 55

Test date: Dec-2008

Test sponsor: Dell Inc.

Hardware Availability: Oct-2008

Tested by: Dell Inc.

Software Availability: Nov-2008

L3 Cache:	None	System State:	Default
Other Cache:	None	Base Pointers:	32/64-bit
Memory:	16 GB (4x4 GB DDR2-667 FB-DIMM, CL5)	Peak Pointers:	32/64-bit
Disk Subsystem:	1 x 320 GB SATA 7200 RPM	Other Software:	MicroQuill SmartHeap Library 8.1 for x64
Other Hardware:	None		

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	437	31.1	<b>423</b>	<b>32.1</b>	423	32.1	<b>423</b>	<b>32.1</b>	424	32.1	421	32.3
416.gamess	998	19.6	1000	19.6	<b>998</b>	<b>19.6</b>	894	21.9	893	21.9	<b>893</b>	<b>21.9</b>
433.milc	890	10.3	<b>890</b>	<b>10.3</b>	889	10.3	<b>890</b>	<b>10.3</b>	<b>890</b>	<b>10.3</b>	889	10.3
434.zeusmp	437	20.8	438	20.8	<b>438</b>	<b>20.8</b>	437	20.8	438	20.8	<b>438</b>	<b>20.8</b>
435.gromacs	353	20.2	<b>353</b>	<b>20.2</b>	353	20.2	350	20.4	351	20.4	<b>350</b>	<b>20.4</b>
436.cactusADM	163	73.4	<b>165</b>	<b>72.4</b>	165	72.3	163	73.4	<b>165</b>	<b>72.4</b>	165	72.3
437.leslie3d	<b>540</b>	<b>17.4</b>	542	17.3	539	17.4	<b>540</b>	<b>17.4</b>	542	17.3	539	17.4
444.namd	493	16.3	<b>493</b>	<b>16.3</b>	492	16.3	494	16.2	494	16.2	<b>494</b>	<b>16.2</b>
447.dealII	517	22.1	516	22.2	<b>516</b>	<b>22.2</b>	<b>494</b>	<b>23.1</b>	494	23.1	494	23.2
450.soplex	637	13.1	<b>639</b>	<b>13.1</b>	639	13.1	<b>635</b>	<b>13.1</b>	634	13.1	636	13.1
453.povray	223	23.9	223	23.9	<b>223</b>	<b>23.9</b>	181	29.3	181	29.4	<b>181</b>	<b>29.4</b>
454.calculix	386	21.4	<b>386</b>	<b>21.4</b>	385	21.4	<b>366</b>	<b>22.6</b>	366	22.6	366	22.6
459.GemsFDTD	<b>531</b>	<b>20.0</b>	531	20.0	532	20.0	<b>534</b>	<b>19.9</b>	532	20.0	<b>535</b>	19.8
465.tonto	505	19.5	<b>504</b>	<b>19.5</b>	504	19.5	<b>443</b>	22.2	<b>444</b>	<b>22.2</b>	444	22.2
470.lbm	554	24.8	547	25.1	<b>552</b>	<b>24.9</b>	554	24.8	547	25.1	<b>552</b>	<b>24.9</b>
481.wrf	539	20.7	<b>540</b>	<b>20.7</b>	540	20.7	<b>540</b>	20.7	538	20.8	<b>538</b>	<b>20.8</b>
482.sphinx3	706	27.6	712	27.4	<b>706</b>	<b>27.6</b>	<b>702</b>	<b>27.8</b>	<b>702</b>	<b>27.8</b>	704	27.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

Binaries were built on Windows Vista Ultimate (64-bit)

BIOS Settings

Adjacent Cache Line Prefetch set to ON

## Base Compiler Invocation

C benchmarks:

  icl -Qvc9 -Qstd=c99

C++ benchmarks:

  icl -Qvc9

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

<b>Dell Inc.</b>	<b>SPECfp2006 =</b>	<b>22.2</b>
Dell Precision R5400 (Intel Xeon E5450, 3.00 GHz)	<b>SPECfp_base2006 =</b>	<b>21.5</b>
<b>CPU2006 license:</b> 55	<b>Test date:</b>	Dec-2008
<b>Test sponsor:</b> Dell Inc.	<b>Hardware Availability:</b>	Oct-2008
<b>Tested by:</b> Dell Inc.	<b>Software Availability:</b>	Nov-2008

## Base Compiler Invocation (Continued)

## Fortran benchmarks: ifort

Benchmarks using both Fortran and C:  
icl -Ovc9 -Ostd=c99 ifort

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_P64 /assume:underscore
416.gamess: -DSPEC_CPU_P64
    433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -Qlowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
    444.namd: -DSPEC_CPU_P64 /TP
    447.dealIII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -Qlowercase
459.GemsFDTD: -DSPEC_CPU_P64
    465.tonto: -DSPEC_CPU_P64
    470.lbm: -DSPEC_CPU_P64
        481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64
```

## Base Optimization Flags

C benchmarks:

```
-QxSSE4.1 -Qauto-ilp32 -Qipo -O3 -Qprec-div- -Qparallel  
-Oopt-prefetch /F512000000
```

## C++ benchmarks:

```
-QxSSE4.1 -Qauto-ilp32 -Qipo -O3 -Qprec-div- -Qparallel  
-Qopt-prefetch -Qcxx_features /F512000000 shlw64m.lib  
    -link /FORCE:MULTIPLE
```

## Fortran benchmarks:

```
-QxSSE4.1 -Qauto-ilp32 -Qipo -O3 -Qprec-div- -Qparallel  
-Qopt-prefetch /F1000000000
```

Benchmarks using both Fortran and C:

```
-QxSSE4.1 -Qauto-ilp32 -Qipo -O3 -Qprec-div- -Qparallel  
-Qopt-prefetch /F10000000000
```



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp2006 = 22.2**

Dell Precision R5400 (Intel Xeon E5450, 3.00 GHz)

**SPECfp\_base2006 = 21.5**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Dec-2008

**Hardware Availability:** Oct-2008

**Software Availability:** Nov-2008

## Peak Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc9
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc9 -Qstd=c99 ifort
```

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
433.milc: basepeak = yes
```

```
470.lbm: basepeak = yes
```

```
482.sphinx3: -QxSSE4.1 -Qauto-ilp32 -Qipo -O3 -Qprec-div- -Qunroll2
/F512000000
```

C++ benchmarks:

```
444.namd: -Qprof_gen(pass 1) -QxSSE4.1(pass 2) -Qauto-ilp32(pass 2)
-Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Oa /F512000000
shlw64m.lib -link /FORCE:MULTIPLE
```

```
447.dealII: -Qprof_gen(pass 1) -QxSSE4.1(pass 2) -Qauto-ilp32(pass 2)
-Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2
-Qopt-prefetch -Qansi-alias -Qscalar-rep- /F512000000
shlw64m.lib -link /FORCE:MULTIPLE
```

```
450.soplex: -Qprof_gen(pass 1) -QxSSE4.1 -Qauto-ilp32
-Qprof_use(pass 2) -Qipo -O3 -Qprec-div- /F512000000
shlw64m.lib -link /FORCE:MULTIPLE
```

```
453.povray: -Qprof_gen(pass 1) -QxSSE4.1(pass 2) -Qauto-ilp32(pass 2)
-Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4
-Qansi-alias /F512000000 shlw64m.lib
-link /FORCE:MULTIPLE
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

**SPECfp2006 = 22.2**

Dell Precision R5400 (Intel Xeon E5450, 3.00 GHz)

**SPECfp\_base2006 = 21.5**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Dec-2008

**Hardware Availability:** Oct-2008

**Software Availability:** Nov-2008

## Peak Optimization Flags (Continued)

Fortran benchmarks:

410.bwaves: -QxSSE4.1 -Qauto-ilp32 -Qipo -O3 -Qprec-div-  
-Qopt-prefetch -Qparallel /F1000000000

416.gamess: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qauto-ilp32(pass 2)  
-Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2 -Ob0  
-Qansi-alias -Qscalar-rep- /F1000000000

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qauto-ilp32(pass 2)  
-Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2 -Ob0  
-Qopt-prefetch -Qparallel /F1000000000

465.tonto: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qauto-ilp32(pass 2)  
-Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 -Qauto  
/F1000000000

Benchmarks using both Fortran and C:

435.gromacs: -Qprof\_gen(pass 1) -QxSSE4.1(pass 2) -Qauto-ilp32(pass 2)  
-Qprof\_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch  
/F1000000000

436.cactusADM: basepeak = yes

454.calculix: -QxSSE4.1 -Qauto-ilp32 -Qipo -O3 -Qprec-div- /F1000000000

481.wrf: -QxSSE4.1 -Qauto-ilp32 -Qipo -O3 -Qprec-div-  
-Qopt-prefetch -Qparallel /F1000000000

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/dell.ic11.0.windows.flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/dell.ic11.0.windows.flags.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

Dell Precision R5400 (Intel Xeon E5450, 3.00 GHz)

**SPECfp2006 = 22.2**

**SPECfp\_base2006 = 21.5**

**CPU2006 license:** 55

**Test sponsor:** Dell Inc.

**Tested by:** Dell Inc.

**Test date:** Dec-2008

**Hardware Availability:** Oct-2008

**Software Availability:** Nov-2008

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 22:55:24 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 January 2009.