



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DH67BLB3 Motherboard (Intel Core i5-2500S)

SPECint®2006 = 43.8

SPECint_base2006 = 41.8

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2011

Hardware Availability: Mar-2011

Software Availability: Apr-2011



Hardware

CPU Name: Intel Core i5-2500S
 CPU Characteristics: Intel Turbo Boost Technology up to 3.7 GHz
 CPU MHz: 2700
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 6 MB I+D on chip per chip
 Other Cache: None
 Memory: 4 GB (2 x 2 GB 2Rx8 PC3-10600U-9)
 Disk Subsystem: Seagate 1 TB SATA, 7200 RPM
 Other Hardware: None

Software

Operating System: Windows 7 Ultimate (64-bit)
 Compiler: Intel C++ Compiler XE for IA32 and Intel 64 Version 12.0.3.176 Build 20110309
 Microsoft Visual Studio 2008 Professional SP1 (for libraries)
 Auto Parallel: Yes
 File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DH67BLB3 Motherboard (Intel Core i5-2500S)

SPECint2006 = 43.8

CPU2006 license: 13

Test date: Jul-2011

Test sponsor: Intel Corporation

Hardware Availability: Mar-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

SPECint_base2006 = 41.8

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	334	29.3	333	29.3	333	29.4	264	37.0	264	37.0	264	37.0
401.bzip2	401	24.1	407	23.7	396	24.4	382	25.2	398	24.2	385	25.1
403.gcc	285	28.2	285	28.2	285	28.2	268	30.1	268	30.1	268	30.1
429.mcf	179	50.9	179	50.9	179	51.0	180	50.8	180	50.8	180	50.8
445.gobmk	387	27.1	387	27.1	387	27.1	373	28.1	373	28.1	374	28.1
456.hammer	172	54.2	174	53.7	174	53.7	172	54.3	172	54.4	173	53.8
458.sjeng	420	28.8	420	28.8	420	28.8	420	28.8	420	28.8	420	28.8
462.libquantum	42.4	489	42.5	488	42.4	489	42.4	489	42.5	488	42.4	489
464.h264ref	370	59.8	370	59.8	370	59.8	337	65.7	336	65.8	337	65.8
471.omnetpp	251	25.0	251	24.9	251	24.9	230	27.2	230	27.1	231	27.1
473.astar	252	27.8	252	27.8	253	27.8	252	27.8	252	27.8	253	27.8
483.xalancbmk	211	32.7	211	32.7	211	32.7	211	32.7	211	32.7	211	32.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply
OMP_NUM_THREADS set to number of processors cores
KMP_AFFINITY set to granularity=fine,scatter

Base Compiler Invocation

C benchmarks:

icl -Qvc9 -Qstd=c99

C++ benchmarks:

icl -Qvc9

Base Portability Flags

```
400.perlbench: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64_X64
                  -DSPEC_CPU_NO_NEED_VA_COPY
401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64
429.mcf: -DSPEC_CPU_P64
445.gobmk: -DSPEC_CPU_P64
456.hammer: -DSPEC_CPU_P64
458.sjeng: -DSPEC_CPU_P64
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Intel DH67BLB3 Motherboard (Intel Core i5-2500S)

SPECint2006 = 43.8

SPECint_base2006 = 41.8

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jul-2011

Hardware Availability: Mar-2011

Software Availability: Apr-2011

Base Portability Flags (Continued)

```
462.libquantum: -DSPEC_CPU_P64  
464.h264ref: -DSPEC_CPU_P64 -DWIN32 -DSPEC_CPU_NO_INTTYPES  
471.omnetpp: -DSPEC_CPU_P64 -DSPEC_CPU_WIN64  
473.astar: -DSPEC_CPU_P64  
483.xalancbmk: -DSPEC_CPU_P64 -Qoption,cpp,--no_wchar_t_keyword
```

Base Optimization Flags

C benchmarks:

```
-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qauto-ilp32  
/F512000000
```

C++ benchmarks:

```
-QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features  
-Qauto-ilp32 /F512000000 shlw64M.lib -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc9
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qansi-alias -Qopt-prefetch -Qauto-ilp32  
/F512000000 shlw64M.lib -link /FORCE:MULTIPLE
```

Continued on next page



SPEC CINT2006 Result Copyright 2006 SPEC Inc. All rights reserved. Evaluation Committee

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation Intel DH67BLB3 Motherboard (Intel Core i5-2500S)	SPECint2006 = 43.8 SPECint_base2006 = 41.8
CPU2006 license: 13 Test sponsor: Intel Corporation Tested by: Intel Corporation	Test date: Jul-2011 Hardware Availability: Mar-2011 Software Availability: Apr-2011

Peak Optimization Flags (Continued)

```
401.bzip2: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qopt-prefetch -Qansi-alias -Qauto-ilp32  
/F512000000
```

403.gcc: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec_div_ -Qauto_ilp32 /F512000000

```
429.mcf: -QxAVX -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32  
/F512000000
```

```
445.gobmk: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo  
-O2 -Qprec-div- -Qansi-alias -Qauto-ilp32 /F512000000
```

456.hmmer: -QxAVX -Qipo -O3 -Qprec-div- -Qunroll12 -Qansi-alias
-Qauto-ilp32 /F512000000

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo
-O3 -Qprec-div- -Qunroll2 -Qansi-alias -Qauto-ilp32
/F512000000

C++ benchmarks:

```
471.omnetpp: -QxAVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo  
-O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F512000000  
shlw64M.lib -link /FORCE:MULTIPLE
```

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=__alloca

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.20110808.html>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint2006 = 43.8

Intel DH67BLB3 Motherboard (Intel Core i5-2500S)

SPECint_base2006 = 41.8

CPU2006 license: 13

Test date: Jul-2011

Test sponsor: Intel Corporation

Hardware Availability: Mar-2011

Tested by: Intel Corporation

Software Availability: Apr-2011

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12-winx64-revB.20110808.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 23:43:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 2 August 2011.