



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp®2006 = 38.1

Intel DH61WW motherboard (Intel Pentium G630)

SPECfp_base2006 = 37.4

CPU2006 license: 13


Test date: Dec-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2011

Tested by: Intel Corporation

Software Availability: Sep-2011



Hardware

CPU Name: Intel Pentium G630
 CPU Characteristics:
 CPU MHz: 2700
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Microsoft Windows 7 Ultimate
 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 12.1.0.229 of Intel C++ Studio XE for Windows;
 Fortran: Version 12.1.0.229 of Intel Fortran Studio XE for Windows;
 Libraries: Version 15.00.30729.01 of Microsoft Visual Studio 2008 Professional SP1
 Auto Parallel: Yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = **38.1**

Intel DH61WW motherboard (Intel Pentium G630)

SPECfp_base2006 = **37.4**

CPU2006 license: 13

Test date: Dec-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2011

Tested by: Intel Corporation

Software Availability: Sep-2011

L3 Cache: 3 MB I+D on chip per chip
 Other Cache: None
 Memory: 4 GB (2 x 2 GB 2Rx8 PC3-10600U-9, running at 1066 MHz and CL7)
 Disk Subsystem: 1 TB Seagate SATA, 7200 RPM
 Other Hardware: None

File System: NTFS
 System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: SmartHeap Library Version 9.01 from <http://www.microquill.com/>

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	180	75.5	179	75.8	<u>179</u>	<u>75.8</u>	180	75.5	179	75.8	<u>179</u>	<u>75.8</u>
416.gamess	<u>764</u>	<u>25.6</u>	764	25.6	764	25.6	716	27.4	716	27.3	<u>716</u>	<u>27.4</u>
433.milc	195	47.1	195	47.1	<u>195</u>	<u>47.1</u>	195	47.1	195	47.1	<u>195</u>	<u>47.1</u>
434.zeusmp	178	51.2	178	51.1	<u>178</u>	<u>51.1</u>	178	51.2	178	51.1	<u>178</u>	<u>51.1</u>
435.gromacs	301	23.7	302	23.7	<u>301</u>	<u>23.7</u>	301	23.7	302	23.7	<u>301</u>	<u>23.7</u>
436.cactusADM	235	50.8	236	50.7	<u>236</u>	<u>50.7</u>	235	50.8	236	50.7	<u>236</u>	<u>50.7</u>
437.leslie3d	221	42.6	<u>221</u>	<u>42.5</u>	221	42.5	221	42.6	<u>221</u>	<u>42.5</u>	221	42.5
444.namd	<u>444</u>	<u>18.1</u>	444	18.1	444	18.1	436	18.4	<u>436</u>	<u>18.4</u>	436	18.4
447.dealII	321	35.7	321	35.6	<u>321</u>	<u>35.7</u>	321	35.7	321	35.6	<u>321</u>	<u>35.7</u>
450.soplex	<u>311</u>	<u>26.8</u>	311	26.8	311	26.8	<u>311</u>	<u>26.8</u>	311	26.8	311	26.8
453.povray	162	32.8	163	32.7	<u>162</u>	<u>32.8</u>	132	40.5	132	40.4	<u>132</u>	<u>40.5</u>
454.calculix	<u>269</u>	<u>30.7</u>	269	30.7	269	30.7	<u>269</u>	<u>30.7</u>	269	30.7	269	30.7
459.GemsFDTD	287	37.0	<u>287</u>	<u>37.0</u>	287	37.0	287	37.0	<u>287</u>	<u>37.0</u>	287	37.0
465.tonto	<u>400</u>	<u>24.6</u>	400	24.6	401	24.6	379	25.9	<u>379</u>	<u>25.9</u>	379	25.9
470.lbm	158	86.7	<u>158</u>	<u>86.7</u>	158	86.7	158	86.7	<u>158</u>	<u>86.7</u>	158	86.7
481.wrf	<u>228</u>	<u>49.0</u>	228	49.1	228	49.0	<u>228</u>	<u>49.0</u>	228	49.1	228	49.0
482.sphinx3	<u>581</u>	<u>33.5</u>	580	33.6	582	33.5	<u>581</u>	<u>33.5</u>	580	33.6	582	33.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

ipsxe-comp-vars batch file invoked with intel64

Platform Notes

Sysinfo program C:\SPEC12.1\Docs\sysinfo
 \$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c
 running on CltE06995A30CB5 Thu Dec 29 08:34:29 2011

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Trying 'systeminfo'

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 38.1

Intel DH61WW motherboard (Intel Pentium G630)

SPECfp_base2006 = 37.4

CPU2006 license: 13

Test date: Dec-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2011

Tested by: Intel Corporation

Software Availability: Sep-2011

Platform Notes (Continued)

OS Name : Microsoft Windows 7 Ultimate
 OS Version : 6.1.7601 Service Pack 1 Build 7601
 System Manufacturer: INTEL_
 System Model : DH61WW__
 Processor(s) : 1 Processor(s) Installed.
 [01]: Intel64 Family 6 Model 42 Stepping 7 GenuineIntel ~2700 Mhz
 BIOS Version : Intel Corp. BEH6110H.86A.0016.2011.0118.1128, 1/18/2011
 Total Physical Memory: 4,004 MB

```
Trying 'wmic cpu get /value'
DeviceID : CPU0
L2CacheSize : 512
L3CacheSize : 3072
MaxClockSpeed : 2700
Name : Intel(R) Pentium(R) CPU G630 @ 2.70GHz
NumberOfCores : 2
NumberOfLogicalProcessors: 2
```

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case, PC Power and Cooling 1200W power supply

General Notes

OMP_NUM_THREADS set to number of processors cores
 KMP_AFFINITY set to granularity=fine,scatter
 Binaries compiled on a system with 1x Intel Core i7-860 CPU
 + 8GB memory using Windows 7 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:
 icl -Qvc9 -Qstd=c99

C++ benchmarks:
 icl -Qvc9

Fortran benchmarks:
 ifort

Benchmarks using both Fortran and C:
 icl -Qvc9 -Qstd=c99 ifort



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 38.1

Intel DH61WW motherboard (Intel Pentium G630)

SPECfp_base2006 = 37.4

CPU2006 license: 13

Test date: Dec-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2011

Tested by: Intel Corporation

Software Availability: Sep-2011

Base Portability Flags

```

410.bwaves: -DSPEC_CPU_P64 -names:lowercase
416.gamess: -DSPEC_CPU_P64
433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 -names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER -names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64

```

Base Optimization Flags

C benchmarks:

```

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qauto-ilp32 /F1000000000

```

C++ benchmarks:

```

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qcxx-features -Qauto-ilp32 /F1000000000 shlw64M.lib
-link /FORCE:MULTIPLE

```

Fortran benchmarks:

```

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch /F1000000000

```

Benchmarks using both Fortran and C:

```

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qparallel -Qansi-alias
-Qopt-prefetch -Qauto-ilp32 /F1000000000

```

Peak Compiler Invocation

C benchmarks:

```

icl -Qvc9 -Qstd=c99

```

C++ benchmarks:

```

icl -Qvc9

```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 38.1

Intel DH61WW motherboard (Intel Pentium G630)

SPECfp_base2006 = 37.4

CPU2006 license: 13

Test date: Dec-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2011

Tested by: Intel Corporation

Software Availability: Sep-2011

Peak Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qstd=c99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000
sh1W64M.lib -link /FORCE:MULTIPLE

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias -Qauto-ilp32
/F1000000000 sh1W64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias
-Qscalar-rep- /F1000000000

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 38.1

Intel DH61WW motherboard (Intel Pentium G630)

SPECfp_base2006 = 37.4

CPU2006 license: 13

Test date: Dec-2011

Test sponsor: Intel Corporation

Hardware Availability: Sep-2011

Tested by: Intel Corporation

Software Availability: Sep-2011

Peak Optimization Flags (Continued)

459.GemsFDTD: basepeak = yes

465.tonto: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto -Qinline-calloc
/F1000000000

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-windows.20120117.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 02:08:55 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 17 January 2012.