



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp[®]2006 = 54.6

Acer AT310 F2 (Xeon E3-1220)

SPECfp_base2006 = 53.4

CPU2006 license: 97


Test sponsor: Acer Incorporation

Tested by: Acer Incorporation

Test date: Dec-2011

Hardware Availability: Jan-2012

Software Availability: Dec-2011



Hardware

CPU Name: Intel Xeon E3-1220
 CPU Characteristics: Intel Turbo Boost Technology up to 3.40 GHz
 CPU MHz: 3100
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.1
 Kernel 2.6.32-131.0.15.el6.x86_64-default
 Compiler: C/C++: Version 12.1.0.225 of Intel C++ Studio XE for Linux;
 Fortran: Version 12.1.0.225 of Intel Fortran Studio XE for Linux
 Auto Parallel: Yes
 File System: ext3
 System State: Run level 3 (multi-user)

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp2006 = 54.6

Acer AT310 F2 (Xeon E3-1220)

SPECfp_base2006 = 53.4

CPU2006 license: 97

Test date: Dec-2011

Test sponsor: Acer Incorporation

Hardware Availability: Jan-2012

Tested by: Acer Incorporation

Software Availability: Dec-2011

L3 Cache: 8 MB I+D on chip per chip
Other Cache: None
Memory: 8 GB (2 x 4 GB 2Rx8 PC3-10600E-9,ECC)
Disk Subsystem: 1 x 250 GB SATA, 7200 RPM
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: Microquill SmartHeap V9.01

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>142</u>	<u>95.8</u>	142	95.6	142	95.8	142	95.8	<u>142</u>	<u>95.8</u>	142	95.5
416.gamess	591	33.1	<u>594</u>	<u>32.9</u>	598	32.8	547	35.8	<u>547</u>	<u>35.8</u>	546	35.8
433.milc	139	66.1	139	66.1	<u>139</u>	<u>66.1</u>	137	66.9	137	67.0	<u>137</u>	<u>67.0</u>
434.zeusmp	134	67.9	<u>134</u>	<u>67.9</u>	134	68.0	134	67.9	<u>134</u>	<u>67.9</u>	134	68.0
435.gromacs	246	29.1	244	29.3	<u>245</u>	<u>29.1</u>	246	29.1	244	29.3	<u>245</u>	<u>29.1</u>
436.cactusADM	108	111	<u>107</u>	<u>111</u>	106	112	108	111	<u>107</u>	<u>111</u>	106	112
437.leslie3d	150	62.5	<u>151</u>	<u>62.2</u>	152	61.9	150	62.5	<u>151</u>	<u>62.2</u>	152	61.9
444.namd	346	23.2	<u>346</u>	<u>23.2</u>	346	23.2	340	23.6	<u>340</u>	<u>23.6</u>	340	23.6
447.dealII	217	52.6	<u>216</u>	<u>52.9</u>	216	53.0	217	52.6	<u>216</u>	<u>52.9</u>	216	53.0
450.soplex	209	40.0	<u>208</u>	<u>40.0</u>	208	40.1	209	40.0	<u>208</u>	<u>40.0</u>	208	40.1
453.povray	124	42.8	123	43.4	<u>124</u>	<u>42.9</u>	103	51.7	<u>103</u>	<u>51.4</u>	104	51.1
454.calculix	198	41.7	<u>197</u>	<u>41.8</u>	197	41.8	<u>192</u>	<u>43.0</u>	192	43.0	193	42.8
459.GemsFDTD	228	46.5	<u>228</u>	<u>46.5</u>	229	46.4	229	46.4	228	46.4	<u>229</u>	<u>46.4</u>
465.tonto	244	40.3	250	39.4	<u>245</u>	<u>40.1</u>	<u>226</u>	<u>43.6</u>	225	43.8	227	43.4
470.lbm	<u>136</u>	<u>101</u>	136	101	136	101	<u>136</u>	<u>101</u>	136	101	136	101
481.wrf	150	74.4	150	74.3	<u>150</u>	<u>74.3</u>	150	74.4	150	74.3	<u>150</u>	<u>74.3</u>
482.sphinx3	<u>291</u>	<u>67.1</u>	290	67.3	292	66.8	303	64.3	304	64.1	<u>304</u>	<u>64.2</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Large pages were disabled for this run.

General Notes

Binaries compiled on RHEL5.5

Base Compiler Invocation

C benchmarks:
icc -m64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp2006 = 54.6

Acer AT310 F2 (Xeon E3-1220)

SPECfp_base2006 = 53.4

CPU2006 license: 97

Test date: Dec-2011

Test sponsor: Acer Incorporation

Hardware Availability: Jan-2012

Tested by: Acer Incorporation

Software Availability: Dec-2011

Base Compiler Invocation (Continued)

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias

C++ benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp2006 = 54.6

Acer AT310 F2 (Xeon E3-1220)

SPECfp_base2006 = 53.4

CPU2006 license: 97

Test date: Dec-2011

Test sponsor: Acer Incorporation

Hardware Availability: Jan-2012

Tested by: Acer Incorporation

Software Availability: Dec-2011

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32
-ansi-alias

470.lbm: basepeak = yes

482.sphinx3: -xAVX -ipo -O3 -no-prec-div -unroll2 -ansi-alias
-parallel

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xAVX -ipo -O3 -no-prec-div -opt-prefetch -parallel
-static

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated
(Test Sponsor: Acer Incorporation)

SPECfp2006 = 54.6

Acer AT310 F2 (Xeon E3-1220)

SPECfp_base2006 = 53.4

CPU2006 license: 97

Test sponsor: Acer Incorporation

Tested by: Acer Incorporation

Test date: Dec-2011

Hardware Availability: Jan-2012

Software Availability: Dec-2011

Peak Optimization Flags (Continued)

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc
-opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Thu Jul 24 01:58:49 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 21 February 2012.