



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

IBM Flex System x222  
(Intel Xeon E5-2418L, 2.00 GHz)

**SPECfp®\_rate2006 = 214**

**SPECfp\_rate\_base2006 = 209**

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2013

Hardware Availability: Sep-2013

Software Availability: Oct-2012



**SPECfp\_rate\_base2006 = 209**

**SPECfp\_rate2006 = 214**

### Hardware

CPU Name: Intel Xeon E5-2418L  
CPU Characteristics: Intel Turbo Boost Technology up to 2.10 GHz  
CPU MHz: 2000  
FPU: Integrated  
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip, 2 threads/core  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server release 6.2 (Santiago)  
Compiler: 2.6.32-220.el6.x86\_64  
C/C++: Version 13.0.0.133 of Intel C++ Studio XE for Linux;  
Fortran: Version 13.0.0.133 of Intel Fortran Studio XE for Linux  
Auto Parallel: No  
File System: ext4  
Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

IBM Flex System x222  
(Intel Xeon E5-2418L, 2.00 GHz)

**SPECfp\_rate2006 = 214**

**SPECfp\_rate\_base2006 = 209**

CPU2006 license: 11

Test date: Jul-2013

Test sponsor: IBM Corporation

Hardware Availability: Sep-2013

Tested by: IBM Corporation

Software Availability: Oct-2012

L3 Cache: 10 MB I+D on chip per chip  
Other Cache: None  
Memory: 96 GB (12 x 8 GB 2Rx4 PC3-12800R-11, ECC, running at 1333 MHz)  
Disk Subsystem: 1 x 100 GB SATA, SSD  
Other Hardware: None

System State: Run level 3 (multi-user)  
Base Pointers: 32/64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	<b>955</b>	<b>228</b>	956	228	955	228	16	<b>955</b>	<b>228</b>	956	228	955	228	955	228
416.gamess	16	1919	163	<b>1909</b>	<b>164</b>	1906	164	16	1776	176	<b>1778</b>	<b>176</b>	1852	169		
433.milc	16	592	248	593	248	<b>593</b>	<b>248</b>	16	591	249	<b>591</b>	<b>249</b>	591	248		
434.zeusmp	16	659	221	<b>658</b>	<b>221</b>	658	221	16	659	221	<b>658</b>	<b>221</b>	658	221		
435.gromacs	16	<b>606</b>	<b>188</b>	609	188	601	190	16	590	193	<b>591</b>	<b>193</b>	600	190		
436.cactusADM	16	<b>758</b>	<b>252</b>	767	249	756	253	16	<b>758</b>	<b>252</b>	767	249	756	253		
437.leslie3d	16	916	164	<b>915</b>	<b>164</b>	914	165	8	416	181	418	180	<b>416</b>	<b>181</b>		
444.namd	16	929	138	929	138	<b>929</b>	<b>138</b>	16	914	140	918	140	<b>918</b>	<b>140</b>		
447.dealII	16	602	304	<b>603</b>	<b>303</b>	607	301	16	602	304	<b>603</b>	<b>303</b>	607	301		
450.soplex	16	824	162	831	161	<b>826</b>	<b>162</b>	16	824	162	831	161	<b>826</b>	<b>162</b>		
453.povray	16	364	234	360	236	<b>363</b>	<b>234</b>	16	<b>311</b>	<b>274</b>	310	275	313	272		
454.calculix	16	602	219	592	223	<b>593</b>	<b>223</b>	16	602	219	592	223	<b>593</b>	<b>223</b>		
459.GemsFDTD	16	1122	151	<b>1121</b>	<b>151</b>	1118	152	16	1122	151	<b>1121</b>	<b>151</b>	1118	152		
465.tonto	16	769	205	756	208	<b>758</b>	<b>208</b>	16	712	221	725	217	<b>714</b>	<b>221</b>		
470.lbm	16	829	265	<b>827</b>	<b>266</b>	827	266	16	829	265	<b>827</b>	<b>266</b>	827	266		
481.wrf	16	645	277	669	267	<b>656</b>	<b>273</b>	16	636	281	640	279	<b>637</b>	<b>280</b>		
482.sphinx3	16	1473	212	<b>1474</b>	<b>212</b>	1474	212	16	1473	212	<b>1474</b>	<b>212</b>	1474	212		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

Operating Mode set to Maximum Performance in BIOS  
Sysinfo program /cpu2006.1.2/config/sysinfo.rev6818  
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\\$ e86d102572650a6e4d596a3cee98f191  
Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

IBM Flex System x222  
(Intel Xeon E5-2418L, 2.00 GHz)

**SPECfp\_rate2006 = 214**

**SPECfp\_rate\_base2006 = 209**

**CPU2006 license:** 11

**Test date:** Jul-2013

**Test sponsor:** IBM Corporation

**Hardware Availability:** Sep-2013

**Tested by:** IBM Corporation

**Software Availability:** Oct-2012

## Platform Notes (Continued)

running on Cara-speccpu1 Sat Jul 13 06:51:53 2013

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
    model name : Intel(R) Xeon(R) CPU E5-2418L 0 @ 2.00GHz
        2 "physical id"s (chips)
        16 "processors"
    cores, siblings (Caution: counting these is hw and system dependent. The
    following excerpts from /proc/cpuinfo might not be reliable. Use with
    caution.)
        cpu cores : 4
        siblings   : 8
        physical 0: cores 0 1 2 3
        physical 1: cores 0 1 2 3
    cache size : 10240 KB
```

```
From /proc/meminfo
MemTotal:      99038608 kB
HugePages_Total:       0
Hugepagesize:     2048 kB
```

```
/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.2 (Santiago)
```

```
From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

```
uname -a:
Linux Cara-speccpu1 2.6.32-220.el6.x86_64 #1 SMP Wed Nov 9 08:03:13 EST 2011
x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Jul 12 14:41
```

```
SPEC is set to: /cpu2006.1.2
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/mapper/vg_caraspeccpu1-lv_root
                    ext4   82G   8.0G   70G  11%  /
```

```
Additional information from dmidecode:
BIOS IBM -[CCE123MUS-1.00]- 04/18/2013
Memory:
 12x Samsung M393B1K70DH0-CK0 8 GB 1333 MHz 2 rank
```

(End of data from sysinfo program)

Memory speed from dmidecode lists the downclocked speed of the run.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

IBM Flex System x222  
(Intel Xeon E5-2418L, 2.00 GHz)

**SPECfp\_rate2006 = 214**

**SPECfp\_rate\_base2006 = 209**

**CPU2006 license:** 11

**Test sponsor:** IBM Corporation

**Tested by:** IBM Corporation

**Test date:** Jul-2013

**Hardware Availability:** Sep-2013

**Software Availability:** Oct-2012

## General Notes

Environment variables set by runspec before the start of the run:

LD\_LIBRARY\_PATH = "/cpu2006.1.2/lib32:/cpu2006.1.2/lib64:/cpu2006.1.2/sh"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RHEL5.5

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

Filesystem page cache cleared with:

echo 1> /proc/sys/vm/drop\_caches

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM Flex System x222  
(Intel Xeon E5-2418L, 2.00 GHz)

**SPECfp\_rate2006 = 214**

**SPECfp\_rate\_base2006 = 209**

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2013

Hardware Availability: Sep-2013

Software Availability: Oct-2012

## Base Optimization Flags

C benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32  
-ansi-alias -opt-mem-layout-trans=3
```

C++ benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32  
-ansi-alias -opt-mem-layout-trans=3
```

Fortran benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch
```

Benchmarks using both Fortran and C:

```
-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32  
-ansi-alias -opt-mem-layout-trans=3
```

## Peak Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

```
433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)  
-prof-use(pass 2) -static -auto-ilp32
```

```
470.lbm: basepeak = yes
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM Flex System x222  
(Intel Xeon E5-2418L, 2.00 GHz)

**SPECfp\_rate2006 = 214**

**SPECfp\_rate\_base2006 = 209**

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jul-2013

Hardware Availability: Sep-2013

Software Availability: Oct-2012

## Peak Optimization Flags (Continued)

482.sphinx3: basepeak = yes

C++ benchmarks:

```
444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
           -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
           -prof-use(pass 2) -fno-alias -auto-ilp32
```

447.dealII: basepeak = yes

450.soplex: basepeak = yes

```
453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
            -prof-use(pass 2) -unroll14 -ansi-alias
```

Fortran benchmarks:

410.bwaves: basepeak = yes

```
416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
             -no-prec-div(pass 2) -prof-use(pass 2) -unroll2
             -inline-level=0 -scalar-rep- -static
```

434.zeusmp: basepeak = yes

437.leslie3d: -xAVX -ipo -O3 -no-prec-div -static -opt-prefetch

459.GemsFDTD: basepeak = yes

```
465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
            -no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -auto
            -inline-calloc -opt-malloc-options=3
```

Benchmarks using both Fortran and C:

```
435.gromacs: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
              -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
              -prof-use(pass 2) -opt-prefetch -static -auto-ilp32
```

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: -xAVX -ipo -O3 -no-prec-div -static -auto-ilp32

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic13-official-linux64.html>  
<http://www.spec.org/cpu2006/flags/IBM-Platform-Flags-V1.2-SNB-C.html>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM Flex System x222  
(Intel Xeon E5-2418L, 2.00 GHz)

**SPECfp\_rate2006 = 214**

**SPECfp\_rate\_base2006 = 209**

**CPU2006 license:** 11

**Test sponsor:** IBM Corporation

**Tested by:** IBM Corporation

**Test date:** Jul-2013

**Hardware Availability:** Sep-2013

**Software Availability:** Oct-2012

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic13-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/IBM-Platform-Flags-V1.2-SNB-C.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 17:38:55 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 19 November 2013.