



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

SuperServer 6027AX-TRF  
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

**SPECfp®2006 =**

**SPECfp\_base2006 = NC**

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.**

### Hardware

CPU Name: Intel Xeon E5-2697 v2  
CPU Characteristics: Intel Turbo Boost Technology up to 3.50 GHz  
CPU MHz: 2700  
FPU: Integrated  
CPU(s) enabled: 24 cores, 2 chips, 12 cores/chip  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 256 KB I+D on chip per core  
L3 Cache: 30 MB I+D on chip per chip  
Other Cache: None  
Memory: 128 GB (16 x 8 GB 2Rx4 L3-14900R-13, ECC)  
Disk Subsystem: 1 x 300 GB ATA II, 10000 RPM  
Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 6.4, Kernel 2.6.32-358.el6.x86\_64  
Compiler:  
C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;  
Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux  
Auto Parallel: Yes  
File System: ext4  
System State: Run level 3 (multi-user)  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

SuperServer 6027AX-TRF  
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

**SPECfp2006 =**

**SPECfp\_base2006 = NC**

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.**

**Results Table**

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	NC	NC										
416.gamess	NC	NC										
433.milc	NC	NC										
434.zeusmp	NC	NC										
435.gromacs	NC	NC										
436.cactusADM	NC	NC										
437.leslie3d	NC	NC										
444.namd	NC	NC										
447.dealII	NC	NC										
450.soplex	NC	NC										
453.povray	NC	NC										
454.calculix	NC	NC										
459.GemsFDTD	NC	NC										
465.tonto	NC	NC										
470.lbm	NC	NC										
481.wrf	NC	NC										
482.sphinx3	NC	NC										

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

SuperServer 6027AX-TRF  
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

**SPECfp2006 =**

**SPECfp\_base2006 =** NC

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.**

### General Notes

Environment variables set by runspec before the start of the run:

LD\_LIBRARY\_PATH = "/usr/cpu2006/libs/32:/usr/cpu2006/libs/64:/usr/cpu2006/sh"

OMP\_NUM\_THREADS = "23"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled

echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

### Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

### Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64

416.gamess: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

SuperServer 6027AX-TRF  
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

**SPECfp2006 =**

**SPECfp\_base2006 = NC**

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.**

## Base Portability Flags (Continued)

433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

C++ benchmarks:

-xAVX -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:

-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

SuperServer 6027AX-TRF  
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

**SPECfp2006 =**

**SPECfp\_base2006 = NC**

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.**

## Peak Compiler Invocation

C benchmarks:

  icc -m64

C++ benchmarks:

  icpc -m64

Fortran benchmarks:

  ifort -m64

Benchmarks using both Fortran and C:

  icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

423.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
  -no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32  
  -ansi-alias

470.lbm: basepeak = yes

482.sphinx3: -xAVX -ipo -O3 -no-prec-div -unroll12 -ansi-alias  
  -parallel

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Supermicro**

SuperServer 6027AX-TRF  
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

**SPECfp2006 =**

**SPECfp\_base2006 = NC**

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.**

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias  
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll14 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -unroll12  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)  
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc  
-opt-malloc-options=3 -auto -unroll14

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

SuperServer 6027AX-TRF  
(X9DAX-iF, Intel Xeon E5-2697 v2, 2.70 GHz)

CPU2006 license: 001176

Test sponsor: Supermicro

Tested by: Supermicro

SPECfp2006 =

SPECfp\_base2006 = NC

Test date: Oct-2013

Hardware Availability: Sep-2013

Software Availability: Sep-2013

**SPEC has determined that this result is not in compliance with the SPEC CPU2006 run and reporting rules. Specifically, SPEC was notified that an attempt to reproduce the published result did not come within SPEC's requirements for run-to-run variation. Upon re-review, it was determined that the system configuration does not meet SPEC's requirements for documented and supported systems, and does not meet SPEC's requirements for general availability.**

## Peak Optimization Flags (Continued)

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-fc -div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at  
<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>  
<http://www.spec.org/cpu2006/flags/Supermicro-Platform-Settings-V1.2-revB.20130719.html>

You can also download the XML flags sources by saving the following links:  
<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>  
<http://www.spec.org/cpu2006/flags/Supermicro-Platform-Settings-V1.2-revB.20130719.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Wed Oct 1 12:23:42 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 25 February 2014.