



# SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECint®2006 = 70.9

ASUS Q170M-C motherboard (Intel Core i7-6700)

SPECint\_base2006 = 68.9

CPU2006 license: 13


Test date: Feb-2016

Test sponsor: Intel Corporation

Hardware Availability: Aug-2015

Tested by: Intel Corporation

Software Availability: Aug-2015



## Hardware

CPU Name: Intel Core i7-6700  
 CPU Characteristics: Intel Turbo Boost Technology up to 4.00 GHz  
 CPU MHz: 3400  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 8 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 8 GB (2 x 4 GB 2Rx4 PC4-2133P-U)  
 Disk Subsystem: 1 TB Seagate Barracuda HDD, 7200 RPM  
 Other Hardware: None

## Software

Operating System: Microsoft Windows 7 Professional 6.1.7601 Service Pack 1 Build 7601  
 Compiler: C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows;  
 Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013  
 Auto Parallel: Yes  
 File System: NTFS  
 System State: Default  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: SmartHeap Library Version 11.0 from <http://www.microquill.com/>



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECint2006 = 70.9

ASUS Q170M-C motherboard (Intel Core i7-6700)

SPECint\_base2006 = 68.9

CPU2006 license: 13  
Test sponsor: Intel Corporation  
Tested by: Intel Corporation

Test date: Feb-2016  
Hardware Availability: Aug-2015  
Software Availability: Aug-2015

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	<b>208</b>	<b>47.1</b>	207	47.2	208	47.1	172	56.8	<b>172</b>	<b>56.8</b>	172	56.7
401.bzip2	318	30.3	<b>317</b>	<b>30.5</b>	317	30.5	310	31.1	310	31.2	<b>310</b>	<b>31.2</b>
403.gcc	193	41.8	<b>193</b>	<b>41.8</b>	193	41.8	184	43.7	<b>184</b>	<b>43.7</b>	184	43.7
429.mcf	109	83.5	<b>109</b>	<b>83.4</b>	109	83.4	109	83.5	<b>109</b>	<b>83.4</b>	109	83.4
445.gobmk	302	34.7	302	34.7	<b>302</b>	<b>34.7</b>	<b>292</b>	<b>35.9</b>	292	35.9	292	35.9
456.hmmer	<b>89.0</b>	<b>105</b>	89.1	105	88.9	105	<b>89.0</b>	<b>105</b>	89.1	105	88.9	105
458.sjeng	<b>320</b>	<b>37.8</b>	320	37.8	320	37.8	<b>320</b>	<b>37.8</b>	320	37.8	320	37.8
462.libquantum	10.3	2010	<b>10.3</b>	<b>2010</b>	10.3	2010	10.3	2010	<b>10.3</b>	<b>2010</b>	10.3	2010
464.h264ref	260	85.0	260	85.2	<b>260</b>	<b>85.1</b>	260	85.0	260	85.2	<b>260</b>	<b>85.1</b>
471.omnetpp	185	33.7	186	33.6	<b>186</b>	<b>33.7</b>	174	35.8	174	35.9	<b>174</b>	<b>35.9</b>
473.astar	177	39.7	<b>177</b>	<b>39.7</b>	177	39.7	177	39.7	<b>177</b>	<b>39.7</b>	177	39.7
483.xalancbmk	95.7	72.1	95.3	72.4	<b>95.6</b>	<b>72.2</b>	95.7	72.1	95.3	72.4	<b>95.6</b>	<b>72.2</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

To compile these binaries, the Intel Compiler 16.0 was set up to generate 64-bit binaries with the command:  
"psxevars.bat intel64" (shortcut provided in the Intel(r) Parallel Studio XE 2016 program folder)

## Platform Notes

Sysinfo program C:\SPEC16.0\Docs\sysinfo  
\$Rev: 6775 \$ \$Date:: 2011-08-16 #\$ \8787f7622badcf24e01c368b1db4377c  
running on CltF832E48856E2 Fri Feb 26 21:43:21 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:  
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name       : Microsoft Windows 7 Professional
OS Version    : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: System manufacturer
System Model   : System Product Name
Processor(s)  : 1 Processor(s) Installed.
               [01]: Intel64 Family 6 Model 94 Stepping 3 GenuineIntel ~3401 Mhz
BIOS Version  : American Megatrends Inc. 0704, 1/12/2016
Total Physical Memory: 8,069 MB
```

```
Trying 'wmic cpu get /value'
DeviceID      : CPU0
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECint2006 = 70.9

ASUS Q170M-C motherboard (Intel Core i7-6700)

SPECint\_base2006 = 68.9

CPU2006 license: 13  
Test sponsor: Intel Corporation  
Tested by: Intel Corporation

Test date: Feb-2016  
Hardware Availability: Aug-2015  
Software Availability: Aug-2015

## Platform Notes (Continued)

L2CacheSize : 1024  
L3CacheSize : 8192  
MaxClockSpeed : 3401  
Name : Intel(R) Core(TM) i7-6700 CPU @ 3.40GHz  
NumberOfCores : 4  
NumberOfLogicalProcessors: 8

(End of data from sysinfo program)

## Component Notes

Tested systems can be used with Shin-G ATX case,  
PC Power and Cooling 1200W power supply

## General Notes

OMP\_NUM\_THREADS set to number of processors cores  
KMP\_AFFINITY set to granularity=fine,scatter  
Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU  
+ 64GB memory using Windows 8.1 Enterprise 64-bit

## Base Compiler Invocation

C benchmarks:  
icl -Qvc12 -Qstd=c99  
  
C++ benchmarks:  
icl -Qvc12

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WIN64\_X64  
401.bzip2: -DSPEC\_CPU\_P64  
403.gcc: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WIN64  
429.mcf: -DSPEC\_CPU\_P64  
445.gobmk: -DSPEC\_CPU\_P64  
456.hmmer: -DSPEC\_CPU\_P64  
458.sjeng: -DSPEC\_CPU\_P64  
462.libquantum: -DSPEC\_CPU\_P64  
464.h264ref: -DSPEC\_CPU\_P64 -DWIN32  
471.omnetpp: -DSPEC\_CPU\_P64 -DSPEC\_CPU\_WIN64  
473.astar: -DSPEC\_CPU\_P64  
483.xalancbmk: -DSPEC\_CPU\_P64 -Qoption,cpp,--no\_wchar\_t\_keyword -DWIN64



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECint2006 = 70.9

ASUS Q170M-C motherboard (Intel Core i7-6700)

SPECint\_base2006 = 68.9

CPU2006 license: 13  
Test sponsor: Intel Corporation  
Tested by: Intel Corporation

Test date: Feb-2016  
Hardware Availability: Aug-2015  
Software Availability: Aug-2015

## Base Optimization Flags

C benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel  
-Qauto-ilp32 /F64000000

C++ benchmarks:

-QxCORE-AVX2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features  
-Qauto-ilp32 /F64000000 shlw64M.lib -link /FORCE:MULTIPLE

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

C++ benchmarks:

icl -Qvc12

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

400.perlbench: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
-Qauto-ilp32 /F64000000 shlw64M.lib  
/F256000000 -link /FORCE:MULTIPLE

401.bzip2: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias  
-Qauto-ilp32 /F64000000

403.gcc: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qauto-ilp32 /F64000000

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.  
(Test Sponsor: Intel Corporation)

SPECint2006 = 70.9

ASUS Q170M-C motherboard (Intel Core i7-6700)

SPECint\_base2006 = 68.9

CPU2006 license: 13  
Test sponsor: Intel Corporation  
Tested by: Intel Corporation

Test date: Feb-2016  
Hardware Availability: Aug-2015  
Software Availability: Aug-2015

## Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O2 -Qprec-div- -Qansi-alias -Qauto-ilp32  
/F64000000

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -QxCORE-AVX2(pass 2) -Qprof\_gen(pass 1) -Qprof\_use(pass 2)  
-Qipo -O3 -Qprec-div- -Qansi-alias  
-Qopt-ra-region-strategy=block -Qauto-ilp32 /F64000000  
shlW64M.lib -link /FORCE:MULTIPLE

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at  
<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html>

You can also download the XML flags source by saving the following link:  
<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml>



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

**ASUSTeK Computer Inc.**  
(Test Sponsor: Intel Corporation)

**SPECint2006 = 70.9**

**ASUS Q170M-C motherboard (Intel Core i7-6700)**

**SPECint\_base2006 = 68.9**

**CPU2006 license:** 13  
**Test sponsor:** Intel Corporation  
**Tested by:** Intel Corporation

**Test date:** Feb-2016  
**Hardware Availability:** Aug-2015  
**Software Availability:** Aug-2015

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue Jul 12 11:03:02 2016 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 12 July 2016.