



# SPEC® MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix 4700 Bandwidth System (Itanium 2 Processor 9040 1.6GHz/18M)

**SPECmpIM\_peak2007 = Not run**

**SPECmpIM\_base2007 = NC**

MPI2007 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: May-2007

Hardware Availability: Jul-2006

Software Availability: Apr-2007

Ranks
<b>104.milc</b>
<b>107.leslie3d</b>
<b>113.GemsFDTD</b>
<b>115.fds4</b>
<b>121.pop2</b>
<b>122.tachyon</b>
<b>126.lammps</b>
<b>127.wrf2</b>
<b>128.GAPgeomfem</b>
<b>129.tera_tf</b>
<b>130.socorro</b>
<b>132.zeusmp2</b>
<b>137.lu</b>

## Results Table

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
104.milc	128	NC	NC	NC	NC											
107.leslie3d	128	NC	NC	NC	NC											
113.GemsFDTD	128	NC	NC	NC	NC											
115.fds4	128	NC	NC	NC	NC											
121.pop2	128	NC	NC	NC	NC											
122.tachyon	128	NC	NC	NC	NC											
126.lammps	128	NC	NC	NC	NC											
127.wrf2	128	NC	NC	NC	NC											
128.GAPgeomfem	128	NC	NC	NC	NC											

Table continues on next page. Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix 4700 Bandwidth System (Itanium 2 Processor 9040 1.6GHz/18M)

~~SPECmpIM\_peak2007 = Not run~~

~~SPECmpIM\_base2007 = NC~~

**MPI2007 license:** 4

**Test sponsor:** SGI

**Tested by:** SGI

**Test date:** May-2007

**Hardware Availability:** Jul-2006

**Software Availability:** Apr-2007

## Results Table (Continued)

Benchmark	Base								Peak							
	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Ranks	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
129.tera_tf	128	NC	NC	NC	NC											
130.socorro	128	NC	NC	NC	NC											
132.zeusmp2	128	NC	NC	NC	NC											
137.lu	128	NC	NC	NC	NC											

Results appear in the order in which they were run. Bold underlined text indicates median measurement.

### Hardware Summary

Type of System: SMP  
 Compute Node: SMP  
 File Server Node: SMP  
 Total Compute Nodes: 1  
 Total Chips: 64  
 Total Cores: 128  
 Total Threads: 128  
 Total Memory: 512 GB  
 Base Ranks Run: 128  
 Minimum Peak Ranks: --  
 Maximum Peak Ranks: --

### Software Summary

Compiler: Intel C Itanium Compiler for Itanium-based Applications Version 9.1 (Build 20070320)  
 C++ Compiler: Intel C++ Itanium Compiler for Itanium-based Applications Version 9.1 (Build 20070320)  
 Fortran Compiler: Intel Fortran Itanium Compiler for Itanium-based Applications Version 9.1 (Build 20070320)  
 Bas Pointers: 64-bit  
 Peak Pointers: 64-bit  
 MPI Library: SGI Message Passing Toolkit (MPT) Version 1.15  
 Other MPI Info: None  
 Pre-processors: None  
 Other Software: None

### Node Description: SMP

#### Hardware

Number of nodes: 1  
 Uses of the node: compute/file server  
 Vendor: SGI  
 Model: SGI Altix 4700 Bandwidth System (Itanium 2 Processor 9040 1.6GHz/18M)  
 CPU Name: Dual-core Intel Itanium 2 9040  
 CPU(s) orderable: 1-512 cores  
 Chips enabled: 64  
 Cores enabled: 96  
 Cores per chip: 2  
 Threads per core: 1  
 CPI: 3.3MHz FSB  
 CPU MHz: 1600  
 Primary Cache: 16 KB I + 16 KB D on chip per core  
 Secondary Cache: 1 MB I + 256 KB D on chip per core  
 L3 Cache: 9 MB I+D on chip per core  
 Other Cache: None  
 Memory: 512 GB (8\*1GB DDR2-400 DIMMs per 2 core module)  
 Disk Subsystem: 36 x 73 GB FibreChannel (Seagate Cheetah 15k rpm)  
 Other Hardware: None  
 Adapter: None  
 Number of Adapters: 0

#### Software

Adapter: None  
 Adapter Driver: Not applicable  
 Adapter Firmware: Not applicable  
 Operating System: SUSE Linux Enterprise Server 10 + SGI ProPack 5 Service Pack 1  
 Local File System: 36 x 73 GB FibreChannel (Seagate Cheetah 15k rpm)  
 Shared File System: None  
 System State: Multi-user  
 Other Software: None

Continued on next page



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix 4700 Bandwidth System (Itanium 2 Processor 9040 1.6GHz/18M)

**SPECmpIM\_peak2007 = Not run**

**SPECmpIM\_base2007 = NC**

**MPI2007 license:** 4

**Test sponsor:** SGI

**Tested by:** SGI

**Test date:** May-2007

**Hardware Availability:** Jul-2006

**Software Availability:** Apr-2007

## Node Description: SMP

Slot Type: Not applicable  
Data Rate: Not applicable  
Ports Used: 0  
Interconnect Type: None

setenv MPI\_DSM\_DISTRIBUTE 1  
Ensures that each MPI process gets a unique CPU and physical memory on the node with which that CPU is associated. The CPUs are chosen by simply starting at cpu 0 relative CPU 0 and incrementing until all MPI processes have been forked.  
setenv MPI\_REQUEST\_MAX 65536  
Determines the maximum number of nonblocking sends and receives that can simultaneously exist for any single MPI process. MPI generates an error message if this limit (or the default, if not set) is exceeded. Default: 16384  
limit stacksize unlimited  
Removes limits on the maximum size of the automatically-extended stack region for the current process and each process it creates.

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:

12clammps icpc

Fortran benchmarks:  
ifort

12wrf2 benchmarks for Fortran and C:  
icc ifort

## Base Portability Flags

121.pop2: -DSPEC\_MPI\_CASE\_FLAG

127.wrf2: -DSPEC\_MPI\_LINUX -DSPEC\_MPI\_CASE\_FLAG



# SPEC MPIM2007 Result

Copyright 2006-2010 Standard Performance Evaluation Corporation

**SGI**

SGI Altix 4700 Bandwidth System (Itanium 2 Processor 9040 1.6GHz/18M)

**SPECmpIM\_peak2007 = Not Run**

**SPECmpIM\_base2007 = NC**

**MPI2007 license:** 4

**Test sponsor:** SGI

**Tested by:** SGI

**Test date:** May-2007

**Hardware Availability:** Jul-2006

**Software Availability:** Apr-2007

## Base Optimization Flags

C benchmarks:

-O3 -ipo -IPF-fp-relaxed -lmpi

C++ benchmarks:

126.lammps: -O3 -ipo -IPF-fp-relaxed -ansi-alias -lmpi

Fortran benchmarks:

-O3 -ipo -IPF-fp-relaxed -lmpi

Benchmarks using both Fortran and C:

-O3 -ipo -IPF-fp-relaxed -lmpi

The flags file that was used to format this result can be browsed at

<http://www.spec.org/mpi2007/flags/intel-ic91-ipf.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/mpi2007/flags/Intel-ic91-ipf.xml>

SPEC and SPEC MPI are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC MPI2007 v59.

Report generated on Tue Jul 22 13:32:40 2014 by SPEC MPI2007 PS/PDF formatter v1463.

Originally published on 16 July 2007.