

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

IBM: eServer xSeries 342
Red Hat: TUX 2.0

SPECweb99 = 1820

Test Date: Jun-2001
Tester: IBM

Hardware Avail: Jun-2001 OS Avail: Apr-2001 HTTP Software Avail: Apr-2001 Sup. Software Avail: Apr-2001 SPEC license #: 11

Hardware

Vendor: IBM
Model: eServer xSeries 342
Processor: 1.133 GHz Pentium III
Processors: 1 core, 1 chip, 1 core/chip
Primary Cache: 16KBI+16KBD on chip
Secondary Cache: 512KB
Other Cache: none
Memory: 4GB
Disk Subsystem: 6 X 18GB (IBM 19K1638)
Disk Controllers: Onboard Adaptec
Other Hardware: 2 X ALTEON ACESwitch 180 GbE Switch

Software

Operating System: RedHat Linux 7.1
File System: ext2
Other Software: None

HTTP Software

Vendor: Red Hat
HTTP Software: TUX 2.0
API: TUX user API
Server Cache: none
Log Mode: Binary CLF

Test Sponsor

Test Date: Jun-2001
Tested By: IBM
SPEC License: 11

Network

of Controllers: 2
Network Controllers: Alteon ACEnic PCI-SX
of Nets: 2
Type of Nets: Gigabit Ethernet
Network Speed: 1 Gb/s
MSL (sec): 30 (Non RFC1122)
Time-Wait (sec): 60 (Non RFC1122)
MTU: 1500

Clients

of Clients: 10
Model: eServer xSeries 330
Processor: 933Mhz Pentium III
of Processors: 1
Memory: 256MB
Network Controller: Alteon ACEnic PCI-SX
Operating System: Windows 2000 Professional
Compiler: Microsoft Visual C++ 6.0

Notes/Tuning Information

SUT Notes

- 1 disk for OS and logs
- 5 disk software RAID0, using 2MB chunk size, for web pages

Operating System Notes

- Tuning parameters:
- net.ipv4.ip_forward = 1, default 0
 - net.ipv4.conf.all.rp_filter = 1, enables source route verification, default 0
 - net.ipv4.tcp_timestamps = 0, turns TCP timestamp support off, default 1
 - net.ipv4.tcp_max_tw_buckets = 2000000, sets TCP time-wait buckets pool size, default 180000
 - net.core.rmem_max = 10000000, maximum receive socket buffer size, default 65535
 - net.core.rmem_default = 10000000, default receive socket buffer size, default 65535
 - net.core.wmem_max = 10000000, maximum send socket buffer size, default 65535
 - net.core.wmem_default = 10000000, default send socket buffer size, default 65535
 - net.core.optmem_max = 10000000, default 10240
 - net.ipv4.tcp_rmem = 30000000 30000000 30000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
 - net.ipv4.tcp_wmem = 30000000 30000000 30000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072
 - net.ipv4.tcp_mem=30000000 30000000 30000000, maximum TCP buffer space, default 31744 32256 32768
- See config file for kernel build information

HTTP Software Notes

- TUX Configuration
- net.tux.threads = 1, sets number of TUX threads, default 2
 - net.tux.logging = 1, turns on logging, default 0
 - net.tux.mode_allowed = 255, allowed file-permission bits, default 00004
 - net.tux.mode_forbidden = 2, forbidden file-permission bits, default 00000
 - net.tux.mode_cgi = 32841
 - net.tux.cgiroot = /

SPECweb99 Result

© Copyright 1999, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTP Software Notes (Continued)

- net.tux.logfile = /logs/tux
- net.tux.max_keepalive_bw = 0

HTTP API Notes

Tux API from IBM-20010626.tar.gz