



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant ML150 G3 (3.73 GHz, Intel Xeon processor 5080)

SPECfp2000 = **2113**  
SPECfp\_base2000 = **2024**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2006 Hardware Avail: May-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	44.5	3598	44.5	3598	
171.swim	3100	118	2635	112	2778	
172.mgrid	1800	99.6	1808	99.4	1811	
173.applu	2100	115	1819	97.2	2160	
177.mesa	1400	74.2	1886	69.9	2004	
178.galgel	2900	78.4	3697	78.4	3697	
179.art	2600	42.6	6101	42.6	6101	
183.quake	1300	62.3	2087	49.9	2608	
187.facerec	1900	112	1701	99.1	1917	
188.amp	2200	157	1399	157	1399	
189.lucas	2000	116	1719	117	1706	
191.fma3d	2100	122	1723	122	1723	
200.sixtrack	1100	151	729	151	729	
301.apsi	2600	191	1360	195	1336	

### Hardware

CPU: Intel Xeon processor 5080 (3.73 GHz, 2x2 MB L2, 1066 MHz bus)  
CPU MHz: 3730  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (Hyper-Threading Technology disabled)  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 12 K micro-ops I 16 KB D on chip per core  
Secondary Cache: 2 MB I+D on chip per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8 GB (4x2048 MB PC2-5300F)  
Disk Subsystem: 1x36 GB 15 K SAS  
Other Hardware:

### Software

Operating System: RedHat Enterprise Linux 4.0 Advanced Server for AMD64/EM64T, Update 3 Kernel 2.6.9-34.EL  
Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)  
PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
File System: ext2  
System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
  -DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch_ahead=5
          -OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
          -LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
          -OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant ML150 G3 (3.73 GHz, Intel Xeon processor 5080)

SPECfp2000 = 2113  
SPECfp\_base2000 = 2024

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2006 | Hardware Avail: May-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

```
177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art: basepeak=1
183.quake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
            -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t +FDO
188.ammmp: basepeak=1
189.lucas: ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
200.sixtrack: basepeak=1
301.apsi: pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t
```

### BIOS Configuration Notes

Hyper-Threading Technology disabled

### Other Configuration Notes

Single-processor kernel was used