



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp®_rate2006 = 48.4

Servidor Itautec MX221 (Intel Xeon E5335)

SPECfp_rate_base2006 = 48.4

CPU2006 license: 9001


Test date: Feb-2007

Test sponsor: Itautec

Hardware Availability: Feb-2007

Tested by: Itautec

Software Availability: May-2006



SPECfp_rate_base2006 = 48.4

SPECfp_rate2006 = 48.4

Hardware

CPU Name: Intel Xeon E5335
CPU Characteristics: 1333MHz system bus
CPU MHz: 2000
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1-2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler for IA32 version 9.1
Package ID W_CC_C_9.1.025 Build no 20060519Z
Intel Fortran Compiler for IA32 version 9.1
Package ID W_FC_C_9.1.025 Build no 20060519Z
Microsoft Visual Studio .NET 2003 7.1.3088 (for libraries)
Auto Parallel: No
File System: NTFS

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECfp_rate2006 = 48.4

Servidor Itautec MX221 (Intel Xeon E5335)

SPECfp_rate_base2006 = 48.4

CPU2006 license: 9001

Test date: Feb-2007

Test sponsor: Itautec

Hardware Availability: Feb-2007

Tested by: Itautec

Software Availability: May-2006

L3 Cache:	None	System State:	Default
Other Cache:	None	Base Pointers:	32-bit
Memory:	16 GB (8x2GB DDR2-RAM PC2-5300F CAS 5-5-5)	Peak Pointers:	32-bit
Disk Subsystem:	73 GB SCSI, 10000RPM	Other Software:	Microquill SmartHeap Library v.8.0 for SMP
Other Hardware:	None		

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3228	33.7	3220	33.8	3218	33.8	8	3228	33.7	3220	33.8	3218	33.8
416.gamess	8	1647	95.1	1647	95.1	1646	95.2	8	1647	95.1	1647	95.1	1646	95.2
433.milc	8	3771	19.5	3777	19.4	3765	19.5	8	3771	19.5	3777	19.4	3765	19.5
434.zeusmp	8	1211	60.1	1210	60.2	1211	60.1	8	1211	60.1	1210	60.2	1211	60.1
435.gromacs	8	629	90.8	629	90.8	629	90.8	8	629	90.8	629	90.8	629	90.8
436.cactusADM	8	2033	47.0	2007	47.6	2007	47.6	8	2033	47.0	2007	47.6	2007	47.6
437.leslie3d	8	3123	24.1	3124	24.1	3125	24.1	8	3123	24.1	3124	24.1	3125	24.1
444.namd	8	793	80.9	793	80.9	793	80.9	8	793	80.9	793	80.9	793	80.9
447.dealII	8	960	95.3	948	96.5	961	95.3	8	960	95.3	948	96.5	961	95.3
450.soplex	8	2222	30.0	2222	30.0	2221	30.0	8	2222	30.0	2222	30.0	2221	30.0
453.povray	8	375	114	375	114	375	114	8	375	114	375	114	375	114
454.calculix	8	922	71.5	927	71.2	945	69.8	8	922	71.5	927	71.2	945	69.8
459.GemsFDTD	8	3978	21.3	3986	21.3	3983	21.3	8	3978	21.3	3986	21.3	3983	21.3
465.tonto	8	1571	50.1	1552	50.7	1572	50.1	8	1571	50.1	1552	50.7	1572	50.1
470.lbm	8	4318	25.5	4317	25.5	4316	25.5	8	4318	25.5	4317	25.5	4316	25.5
481.wrf	8	1945	46.0	1939	46.1	1943	46.0	8	1945	46.0	1939	46.1	1943	46.0
482.sphinx3	8	3280	47.5	3280	47.5	3274	47.6	8	3280	47.5	3280	47.5	3274	47.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

The Servidor Itautec MX221 and the Servidor Itautec MX201 are electronically equivalent.

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX221 (Intel Xeon E5335)

SPECfp_rate2006 = 48.4

CPU2006 license: 9001

Test sponsor: Itautec

Tested by: Itautec

Test date: Feb-2007

Hardware Availability: Feb-2007

Software Availability: May-2006

Base Compiler Invocation (Continued)

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc7.1 -Qc99 ifort

Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore

444.namd: -TP

447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
-DBOOST_NO_INTRINSIC_WCHAR_T

453.povray: -DSPEC_CPU_WINDOWS_ICL

454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase

481.wrf: -DSPEC_CPU_WINDOWS_ICL

Base Optimization Flags

C benchmarks:

-fast /F950000000 sh1SMPMt.lib -link /FORCE:MULTIPLE

C++ benchmarks:

-fast -Qcxx_features /F950000000 sh1SMPMt.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:

-fast /F950000000 -link /FORCE:MULTIPLE

Benchmarks using both Fortran and C:

-fast /F950000000 -link /FORCE:MULTIPLE

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautech

SPECfp_rate2006 = 48.4

Servidor Itautech MX221 (Intel Xeon E5335)

SPECfp_rate_base2006 = 48.4

CPU2006 license: 9001

Test date: Feb-2007

Test sponsor: Itautech

Hardware Availability: Feb-2007

Tested by: Itautech

Software Availability: May-2006

Peak Optimization Flags (Continued)

444.namd: basepeak = yes

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: basepeak = yes

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: basepeak = yes

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Itautech-ic91-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Itautech-ic91-flags.20090714.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 10:30:03 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 7 March 2007.