



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Bb-6  
(Intel Xeon processor 5110)

SPECfp<sup>®</sup>\_rate2006 = 29.3

SPECfp\_rate\_base2006 = 28.5

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Oct-2007

Hardware Availability: May-2007

Software Availability: Apr-2007



### Hardware

CPU Name: Intel Xeon 5110  
 CPU Characteristics: 1.60 GHz, 4 MB L2, 1066 MHz bus  
 CPU MHz: 1600  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp for x86\_64  
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070320, Package-ID: l\_cc\_c\_9.1.049  
 Intel Fortran Compiler for IA32/EM64T application, Version 9.1 - Build 20070320, Package ID: l\_fc\_c\_9.1.045  
 Auto Parallel: No  
 File System: ext2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Bb-6  
(Intel Xeon processor 5110)

SPECfp\_rate2006 = 29.3

SPECfp\_rate\_base2006 = 28.5

CPU2006 license: 9006  
Test sponsor: NEC Corporation  
Tested by: NEC Corporation

Test date: Oct-2007  
Hardware Availability: May-2007  
Software Availability: Apr-2007

L3 Cache: None  
Other Cache: None  
Memory: 8 GB (4x2 GB PC2-5300F, 2 rank, CL5-5-5, ECC)  
Disk Subsystem: 1x146.5 GB SAS, 10000RPM  
Other Hardware: None

System State: Multiuser, Runlevel 3  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2105	25.8	<u>2107</u>	<u>25.8</u>	2121	25.6	4	2105	25.8	<u>2107</u>	<u>25.8</u>	2121	25.6
416.gamess	4	1790	43.8	1787	43.8	<u>1790</u>	<u>43.8</u>	4	1790	43.8	1787	43.8	<u>1790</u>	<u>43.8</u>
433.milc	4	2122	17.3	2125	17.3	<u>2122</u>	<u>17.3</u>	4	2199	16.7	<u>2198</u>	<u>16.7</u>	2198	16.7
434.zeusmp	4	1222	29.8	<u>1228</u>	<u>29.6</u>	1235	29.5	4	1219	29.9	1228	29.6	<u>1227</u>	<u>29.7</u>
435.gromacs	4	738	38.7	746	38.3	<u>746</u>	<u>38.3</u>	4	716	39.9	715	40.0	<u>715</u>	<u>39.9</u>
436.cactusADM	4	1373	34.8	<u>1366</u>	<u>35.0</u>	1361	35.1	4	1373	34.8	<u>1366</u>	<u>35.0</u>	1361	35.1
437.leslie3d	4	2067	18.2	<u>2063</u>	<u>18.2</u>	2061	18.2	4	2067	18.2	<u>2063</u>	<u>18.2</u>	2061	18.2
444.namd	4	<u>955</u>	<u>33.6</u>	955	33.6	954	33.6	4	<u>955</u>	<u>33.6</u>	955	33.6	954	33.6
447.dealII	4	890	51.4	914	50.1	<u>891</u>	<u>51.3</u>	4	895	51.1	<u>881</u>	<u>51.9</u>	868	52.7
450.soplex	4	<u>1581</u>	<u>21.1</u>	1593	20.9	1579	21.1	4	1481	22.5	1479	22.6	<u>1480</u>	<u>22.5</u>
453.povray	4	<u>487</u>	<u>43.7</u>	490	43.4	485	43.9	4	<u>368</u>	<u>57.9</u>	369	57.7	367	58.0
454.calculix	4	990	33.3	<u>992</u>	<u>33.3</u>	994	33.2	4	967	34.1	<u>968</u>	<u>34.1</u>	968	34.1
459.GemsFDTD	4	2493	17.0	2491	17.0	<u>2491</u>	<u>17.0</u>	4	2493	17.0	2491	17.0	<u>2491</u>	<u>17.0</u>
465.tonto	4	1261	31.2	<u>1263</u>	<u>31.2</u>	1267	31.1	4	1220	32.3	<u>1229</u>	<u>32.0</u>	1239	31.8
470.lbm	4	<u>3843</u>	<u>14.3</u>	3837	14.3	3913	14.0	4	3717	14.8	3712	14.8	<u>3712</u>	<u>14.8</u>
481.wrf	4	<u>1441</u>	<u>31.0</u>	1423	31.4	1441	31.0	4	<u>1441</u>	<u>31.0</u>	1423	31.4	1441	31.0
482.sphinx3	4	2566	30.4	<u>2566</u>	<u>30.4</u>	2570	30.3	4	2498	31.2	2505	31.1	<u>2502</u>	<u>31.2</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
'/usr/bin/taskset' used to bind processes to CPUs

## General Notes

The system bus runs at 1066 MHz  
All binaries were built with 64-bit Intel compiler except:  
433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with  
32-bit Intel compiler by changing the path for include and library files.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/120Bb-6  
(Intel Xeon processor 5110)

**SPECfp\_rate2006 = 29.3**

**SPECfp\_rate\_base2006 = 28.5**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Oct-2007

**Hardware Availability:** May-2007

**Software Availability:** Apr-2007

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/120Bb-6  
(Intel Xeon processor 5110)

**SPECfp\_rate2006 = 29.3**

**SPECfp\_rate\_base2006 = 28.5**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Oct-2007

**Hardware Availability:** May-2007

**Software Availability:** Apr-2007

## Peak Compiler Invocation

C benchmarks:

```
/opt/intel/cc/9.1.049/bin/icc -I/opt/intel/cc/9.1.049/include  
-L/opt/intel/cc/9.1.049/lib
```

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/9.1.049/bin/icpc  
-I/opt/intel/cc/9.1.049/include -L/opt/intel/cc/9.1.049/lib
```

Fortran benchmarks (except as noted below):

ifort

```
434.zeusmp: /opt/intel/fc/9.1.045/bin/ifort  
-I/opt/intel/fc/9.1.045/include -L/opt/intel/fc/9.1.045/lib
```

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof_gen(pass 1) -prof_use(pass 2) -fast
```

```
470.lbm: Same as 433.milc
```

```
482.sphinx3: -fast
```

C++ benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**NEC Corporation**

Express5800/120Bb-6  
(Intel Xeon processor 5110)

**SPECfp\_rate2006 = 29.3**

**SPECfp\_rate\_base2006 = 28.5**

**CPU2006 license:** 9006  
**Test sponsor:** NEC Corporation  
**Tested by:** NEC Corporation

**Test date:** Oct-2007  
**Hardware Availability:** May-2007  
**Software Availability:** Apr-2007

## Peak Optimization Flags (Continued)

444.namd: basepeak = yes

447.dealII: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

450.soplex: Same as 447.dealII

453.povray: Same as 447.dealII

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

### Benchmarks using both Fortran and C:

435.gromacs: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

436.cactusADM: basepeak = yes

454.calculix: Same as 435.gromacs

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-ic91-FP-linux-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-ic91-FP-linux-flags.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 14:32:51 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 27 November 2007.