



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp®_rate2006 = 32.3

Acer Altos R720 (Intel Xeon 5120)

SPECfp_rate_base2006 = 30.3

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007



Hardware

CPU Name: Intel Xeon 5120
CPU Characteristics: 1066MHz system bus
CPU MHz: 1860
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1, 2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

Software

Operating System: SuSE Linux Enterprise Server 10 SP1 EM64T (kernel 2.6.16.46-0.12-smp)
Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070725
Auto Parallel: Yes
File System: ReiserFS
System State: Multi-user, level 3
Base Pointers: 64-bit

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 32.3

Acer Altos R720 (Intel Xeon 5120)

SPECfp_rate_base2006 = 30.3

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
 Disk Subsystem: 1 x 73GB 10000PRM SAS HDD
 Other Hardware: None

Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2385	22.8	<u>2385</u>	<u>22.8</u>	2385	22.8	4	2370	22.9	2368	23.0	<u>2369</u>	<u>22.9</u>
416.gamess	4	<u>1490</u>	<u>52.5</u>	1494	52.4	1490	52.6	4	<u>1470</u>	<u>53.3</u>	1468	53.3	1471	53.2
433.milc	4	<u>2515</u>	<u>14.6</u>	2515	14.6	2515	14.6	4	2425	15.1	2426	15.1	<u>2425</u>	<u>15.1</u>
434.zeusmp	4	1057	34.4	1073	33.9	<u>1065</u>	<u>34.2</u>	4	1063	34.2	<u>1065</u>	<u>34.2</u>	1066	34.2
435.gromacs	4	623	45.9	633	45.1	<u>626</u>	<u>45.7</u>	4	617	46.3	618	46.2	<u>617</u>	<u>46.3</u>
436.cactusADM	4	1181	40.5	1147	41.7	<u>1178</u>	<u>40.6</u>	1	265	45.1	<u>265</u>	<u>45.2</u>	262	45.7
437.leslie3d	4	<u>2256</u>	<u>16.7</u>	2257	16.7	2255	16.7	4	<u>2224</u>	<u>16.9</u>	2224	16.9	2223	16.9
444.namd	4	812	39.5	815	39.4	<u>814</u>	<u>39.4</u>	4	<u>809</u>	<u>39.6</u>	821	39.1	809	39.7
447.dealII	4	818	55.9	815	56.1	<u>816</u>	<u>56.1</u>	4	763	60.0	<u>769</u>	<u>59.5</u>	771	59.4
450.soplex	4	1741	19.2	<u>1739</u>	<u>19.2</u>	1734	19.2	4	<u>1607</u>	<u>20.8</u>	1603	20.8	1610	20.7
453.povray	4	<u>363</u>	<u>58.6</u>	363	58.7	369	57.7	4	307	69.4	<u>311</u>	<u>68.5</u>	312	68.2
454.calculix	4	870	37.9	869	38.0	<u>869</u>	<u>38.0</u>	4	615	53.6	613	53.8	<u>614</u>	<u>53.7</u>
459.GemsFDTD	4	2925	14.5	2931	14.5	<u>2929</u>	<u>14.5</u>	4	2777	15.3	2781	15.3	<u>2778</u>	<u>15.3</u>
465.tonto	4	963	40.9	<u>965</u>	<u>40.8</u>	972	40.5	4	<u>940</u>	<u>41.9</u>	935	42.1	948	41.5
470.lbm	4	3261	16.9	<u>3261</u>	<u>16.9</u>	3261	16.9	4	2981	18.4	2981	18.4	<u>2981</u>	<u>18.4</u>
481.wrf	4	1400	31.9	<u>1402</u>	<u>31.9</u>	1405	31.8	4	<u>1399</u>	<u>31.9</u>	1396	32.0	1400	31.9
482.sphinx3	4	<u>2782</u>	<u>28.0</u>	2781	28.0	2783	28.0	4	<u>2568</u>	<u>30.4</u>	2567	30.4	2571	30.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

This result was measured on the Acer Altos R520.
 The Altos R720 and Altos R520 are electronically equivalent.

BIOS Settings

Hardware Prefetcher set to ON

Adjacent Cache Line Prefetch set to ON

Optimization for high-frequency FSB applications set to ON

All results used taskset to bind processes to cores.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 32.3

Acer Altos R720 (Intel Xeon 5120)

SPECfp_rate_base2006 = 30.3

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 32.3

Acer Altos R720 (Intel Xeon 5120)

SPECfp_rate_base2006 = 30.3

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icc  
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib  
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icpc  
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib  
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/ifort  
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib  
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
433.milc: -DSPEC_CPU_LP64  
434.zeusmp: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 32.3

Acer Altos R720 (Intel Xeon 5120)

SPECfp_rate_base2006 = 30.3

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 32.3

Acer Altos R720 (Intel Xeon 5120)

SPECfp_rate_base2006 = 30.3

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:51:30 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 11 December 2007.