



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

SPECint®\_rate2006 = 44.7

### IBM System x3250 M2 (Intel Xeon E3120)

SPECint\_rate\_base2006 = 38.1

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jun-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon E3120  
 CPU Characteristics: 1333MHz system bus  
 CPU MHz: 3166  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 6 MB I+D on chip per chip  
 L3 Cache: None  
 Other Cache: None  
 Memory: 8 GB (4 x 2 GB DDR2-6400E ECC)  
 Disk Subsystem: 1 x 160 GB SATA, 7200RPM  
 Other Hardware: None

### Software

Operating System: SuSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ Compiler 10.1 for Linux Build 20070913 Package ID: l\_cc\_p\_10.1.008  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run level 3 (Full multiuser with network)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: MicroQuill SmartHeap 8.1 Binutils 2.17.50.0.15



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = 44.7

IBM System x3250 M2 (Intel Xeon E3120)

SPECint\_rate\_base2006 = 38.1

CPU2006 license: 11

Test date: Jun-2008

Test sponsor: IBM Corporation

Hardware Availability: Sep-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	<b>472</b>	<b>41.4</b>	472	41.4	474	41.2	2	392	49.9	<b>392</b>	<b>49.9</b>	392	49.9
401.bzip2	2	589	32.8	<b>592</b>	<b>32.6</b>	599	32.2	2	553	34.9	557	34.6	<b>554</b>	<b>34.8</b>
403.gcc	2	424	38.0	420	38.3	<b>421</b>	<b>38.2</b>	2	<b>421</b>	<b>38.2</b>	422	38.1	420	38.4
429.mcf	2	<b>427</b>	<b>42.7</b>	426	42.8	428	42.6	2	437	41.8	<b>435</b>	<b>41.9</b>	434	42.0
445.gobmk	2	501	41.9	<b>501</b>	<b>41.9</b>	501	41.9	2	461	45.5	460	45.6	<b>460</b>	<b>45.6</b>
456.hammer	2	557	33.5	558	33.5	<b>557</b>	<b>33.5</b>	2	323	57.8	322	57.9	<b>322</b>	<b>57.9</b>
458.sjeng	2	641	37.8	637	38.0	<b>638</b>	<b>37.9</b>	2	570	42.4	<b>569</b>	<b>42.5</b>	569	42.5
462.libquantum	2	<b>1331</b>	<b>31.1</b>	1331	31.1	1346	30.8	1	322	64.4	<b>323</b>	<b>64.2</b>	324	64.0
464.h264ref	2	660	67.0	659	67.2	<b>660</b>	<b>67.1</b>	2	<b>631</b>	<b>70.1</b>	631	70.1	631	70.1
471.omnetpp	2	430	29.1	<b>430</b>	<b>29.1</b>	432	28.9	2	<b>402</b>	<b>31.1</b>	403	31.0	402	31.1
473.astar	2	<b>504</b>	<b>27.8</b>	504	27.9	507	27.7	2	461	30.5	462	30.4	<b>461</b>	<b>30.4</b>
483.xalancbmk	2	290	47.5	<b>290</b>	<b>47.5</b>	290	47.5	2	290	47.5	<b>290</b>	<b>47.5</b>	290	47.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hammer, for peak, are compiled in 64-bit mode  
Hardware Sector Prefetch Enabled and Adjacent Sector Prefetch Enabled  
OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to physical,0  
KMP\_STACKSIZE set to null  
taskset utility used to bind CPU(s) to processes

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = 44.7

IBM System x3250 M2 (Intel Xeon E3120)

SPECint\_rate\_base2006 = 38.1

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jun-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2007

## Base Optimization Flags

C benchmarks:

-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc  
-L/opt/intel/cce/10.1.008/lib  
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:

icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = 44.7

IBM System x3250 M2 (Intel Xeon E3120)

SPECint\_rate\_base2006 = 38.1

CPU2006 license: 11

Test date: Jun-2008

Test sponsor: IBM Corporation

Hardware Availability: Sep-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

## Peak Optimization Flags (Continued)

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
-no-prec-div -ansi-alias

456.hmmr: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch  
-opt-streaming-stores always -vec-guard-write  
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=block  
-Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
-Wl,-z,muldefs  
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revC.20090713.html>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECint\_rate2006 = 44.7

IBM System x3250 M2 (Intel Xeon E3120)

SPECint\_rate\_base2006 = 38.1

CPU2006 license: 11

Test date: Jun-2008

Test sponsor: IBM Corporation

Hardware Availability: Sep-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revC.20090713.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 19:11:21 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 2 September 2008.