SPEC CPU®2026 Integer Speed Result

Copyright 2026 Standard Performance Evaluation Corporation

Supermicro

Blade SBI-612BA-1NE34-LCC
(B14SBE-CPU-AP , Intel Xeon 6970E+)

SPECspeed®2026_int_base = 5.69

SPECspeed®2026_int_peak = 5.82

CPU2026 License: 001176
Test Sponsor: Supermicro
Tested by: Supermicro

Test Date: May-2026
Hardware Availability: Jun-2026
Software Availability: Apr-2026



Hardware

CPU Name:	Intel Xeon 6970E+
Max MHz:	3200
Nominal:	2300
Enabled:	192 cores, 1 chip
Orderable:	1 chip
Cache L1:	64 KB I + 32 KB D on chip per core
L2:	192 MB I+D on chip per chip, 4 MB shared / 4 cores
L3:	480 MB I+D on chip per chip
Other:	None
Memory:	1152 GB (12 x 96 GB 2Rx4 PC5-8000B-R)
Storage:	1 x 480 GB NVMe SSD
Cooling:	DLC
Other:	None

Software

OS:	Red Hat Enterprise Linux 9.7 Kernel 5.14.0-611.5.1.el9_7.x86_64
Compiler:	C/C++: Version 2026.0 of Intel oneAPI DPC++/C++ Compiler for Linux; Fortran: Version 2026.0 of Intel Fortran Compiler for Linux
Compiler Category:	Vendor
Firmware:	Version 1.5 released Apr-2026
File System:	xfs
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other:	jemalloc memory allocator V5.3.0
Power Management:	BIOS and OS set to prefer performance at the cost of additional power usage.

SPEC CPU®2026 Integer Speed Result

Copyright 2026 Standard Performance Evaluation Corporation

Supermicro

Blade SBI-612BA-1NE34-LCC
(B14SBE-CPU-AP , Intel Xeon 6970E+)

SPECspeed®2026_int_base = 5.69

SPECspeed®2026_int_peak = 5.82

CPU2026 License: 001176
Test Sponsor: Supermicro
Tested by: Supermicro

Test Date: May-2026
Hardware Availability: Jun-2026
Software Availability: Apr-2026

Results Table

Benchmark	Base							Peak						
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
801.xz_s	192	227	2.61	**227**	**2.60**			192	225	2.63	**227**	**2.60**		
807.ntest_s	192	**86.3**	**13.2**	86.1	13.2			192	**86.3**	**13.2**	86.1	13.2		
817.flac_s	192	443	3.92	**443**	**3.92**			192	443	3.92	**443**	**3.92**		
821.gcc_s	192	**119**	**17.4**	119	17.4			192	**109**	**19.0**	109	19.0		
823.llvm_s	192	82.1	17.2	**82.2**	**17.2**			192	83.5	16.9	**83.7**	**16.9**		
827.cppcheck_s	192	103	10.9	**103**	**10.8**			192	103	10.9	**103**	**10.8**		
829.abc_s	192	363	2.29	**369**	**2.25**			192	363	2.29	**369**	**2.25**		
834.vpr_s	192	**288**	**3.31**	287	3.32			192	**288**	**3.31**	287	3.32		
835.gem5_s	192	362	3.15	**364**	**3.13**			192	**355**	**3.21**	352	3.24		
838.diamond_s	192	108	9.28	**108**	**9.26**			192	104	9.62	**105**	**9.58**		
846.minizinc_s	192	**313**	**2.14**	285	2.35			192	**299**	**2.24**	288	2.33		
853.ns3_s	192	231	4.99	**231**	**4.98**			192	**205**	**5.63**	204	5.66		
854.graph500_s	192	**94.2**	**6.49**	93.6	6.53			192	**94.2**	**6.49**	93.6	6.53		

SPECspeed®2026_int_base = 5.69

SPECspeed®2026_int_peak = 5.82

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

Environment Variables Notes

```
Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH = "/home/cpu2026/lib"
MALLOC_CONF = "retain:true"
OMP_STACKSIZE = "192M"
```

General Notes

```
Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM
memory using CentOS Stream 9.
Transparent Huge Pages enabled by default
Prior to runcpu invocation
Filesystem page cache synced and cleared with:
sync; echo 3>       /proc/sys/vm/drop_caches

NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
is mitigated in the system as tested and documented.
```

(Continued on next page)

General Notes (Continued)

```
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
is mitigated in the system as tested and documented.
 jemalloc, a general purpose malloc implementation
 built with the CentOS Stream 9, and the system compiler gcc 11.5.0
 sources available from jemalloc.net or https://github.com/jemalloc/jemalloc/releases
```

Platform Notes

```
BIOS settings:
Workload Profile = HPC
KTI Prefetch = Enable
Stale AtoS = Disable
LLC Dead Line Alloc = Disable

 Sysinfo program /home/cpu2026/bin/sysinfo
 Rev: 779ab21020787073335a329f3a45e2cd
 running on  Mon May 25 20:41:46 2026

 SUT (System Under Test) info as seen by some common utilities.

 ----------------------------------------------------------------
 Table of contents
 ----------------------------------------------------------------
  1. uname -srvm
  2. w
  3. Username
  4. ulimit -a
  5. sysinfo process ancestry
  6. /proc/cpuinfo
  7. lscpu
  8. numactl --hardware
  9. /proc/meminfo
 10. who -r
 11. Systemd service manager version: systemd 252 (252-55.el9)
 12. Services, from systemctl list-unit-files
 13. Linux kernel boot-time arguments, from /proc/cmdline
 14. cpupower frequency-info
 15. tuned-adm active
 16. sysctl
 17. /sys/kernel/mm/transparent_hugepage
 18. /sys/kernel/mm/transparent_hugepage/khugepaged
 19. OS release
 20. Disk information
 21. /sys/devices/virtual/dmi/id
 22. dmidecode
 23. BIOS
```

(Continued on next page)

Platform Notes (Continued)

```
------------------------------------------------------------

------------------------------------------------------------
1. uname -srvm
  Linux 5.14.0-611.5.1.el9_7.x86_64 #1 SMP PREEMPT_DYNAMIC Fri Oct 17 14:16:35 EDT 2025 x86_64

------------------------------------------------------------
2. w
   20:41:46 up 10:33,  1 user,  load average: 28.11, 127.20, 163.32
  USER     TTY        LOGIN@   IDLE   JCPU   PCPU WHAT
  root     tty1      10:08   10:25m  1.35s  0.00s -bash

------------------------------------------------------------
3. Username
  From environment variable $USER:  root

------------------------------------------------------------
4. ulimit -a
  real-time non-blocking time  (microseconds, -R) unlimited
  core file size              (blocks, -c) 0
  data seg size               (kbytes, -d) unlimited
  scheduling priority                 (-e) 0
  file size                   (blocks, -f) unlimited
  pending signals                     (-i) 4640649
  max locked memory           (kbytes, -l) 64
  max memory size             (kbytes, -m) unlimited
  open files                          (-n) 1024
  pipe size                (512 bytes, -p) 8
  POSIX message queues         (bytes, -q) 819200
  real-time priority                  (-r) 0
  stack size                  (kbytes, -s) unlimited
  cpu time                   (seconds, -t) unlimited
  max user processes                  (-u) 4640649
  virtual memory              (kbytes, -v) unlimited
  file locks                          (-x) unlimited

------------------------------------------------------------
5. sysinfo process ancestry
 /usr/lib/systemd/systemd rhgb --switched-root --system --deserialize 31
 login -- root
 -bash
 -bash
 runcpu --nobuild --reportable --action validate --define default-platform-flags -c
   ic2026.0-clearwaterforest-cpu2026-1.0.1-speed-20260429.cfg --threads 192 --define cores=192 --tune
    base,peak -o all --define intspeedaffinity --define smt-on --define drop_caches intspeed
 runcpu --nobuild --reportable --action validate --define default-platform-flags --configfile
   ic2026.0-clearwaterforest-cpu2026-1.0.1-speed-20260429.cfg --threads 192 --define cores=192 --tune
```

(Continued on next page)

Platform Notes (Continued)

```
   base,peak --output_format all --define intspeedaffinity --define smt-on --define drop_caches --nopower
    --runmode speed --tune base:peak --size refspeed intspeed --nopreenv --note-preenv --logfile
    $SPEC/tmp/CPU2026.003/templogs/preenv.intspeed.003.0.log --lognum 003.0 --from_runcpu 2
  specperl $SPEC/bin/sysinfo
$SPEC = /home/cpu2026

------------------------------------------------------------
6. /proc/cpuinfo
    model name      : Intel(R) Xeon(R) 6970E+
    vendor_id       : GenuineIntel
    cpu family      : 6
    model           : 221
    stepping        : 1
    microcode       : 0x1000120
    bugs           : spectre_v1 spectre_v2 spec_store_bypass swapgs bhi spectre_v2_user
    cpu cores       : 192
    siblings        : 192
    1 physical ids (chips)
    192 processors (hardware threads)
    physical id 0: core ids 0-63,128-191,256-319
    physical id 0: apicids
   0,2,4,6,8,10,12,14,16,18,20,22,24,26,28,30,32,34,36,38,40,42,44,46,48,50,52,54,56,58,60,62,64,66,68,70,72
   ,74,76,78,80,82,84,86,88,90,92,94,96,98,100,102,104,106,108,110,112,114,116,118,120,122,124,126,256,258,2
   60,262,264,266,268,270,272,274,276,278,280,282,284,286,288,290,292,294,296,298,300,302,304,306,308,310,31
   2,314,316,318,320,322,324,326,328,330,332,334,336,338,340,342,344,346,348,350,352,354,356,358,360,362,364
   ,366,368,370,372,374,376,378,380,382,512,514,516,518,520,522,524,526,528,530,532,534,536,538,540,542,544,
   546,548,550,552,554,556,558,560,562,564,566,568,570,572,574,576,578,580,582,584,586,588,590,592,594,596,5
    98,600,602,604,606,608,610,612,614,616,618,620,622,624,626,628,630,632,634,636,638
  Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for
   virtualized systems.  Use the above data carefully.

------------------------------------------------------------
7. lscpu

From lscpu from util-linux 2.37.4:
  Architecture:                            x86_64
  CPU op-mode(s):                          32-bit, 64-bit
  Address sizes:                           52 bits physical, 48 bits virtual
  Byte Order:                              Little Endian
  CPU(s):                                  192
  On-line CPU(s) list:                     0-191
  Vendor ID:                               GenuineIntel
  BIOS Vendor ID:                          Intel(R) Corporation
  Model name:                              Intel(R) Xeon(R) 6970E+
  BIOS Model name:                         Intel(R) Xeon(R) 6970E+
  CPU family:                              6
  Model:                                   221
```

(Continued on next page)

Platform Notes (Continued)

```
  Thread(s) per core:                  1
  Core(s) per socket:                  192
  Socket(s):                           1
  Stepping:                            1
  BogoMIPS:                            4600.00
  Flags:                               fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
                                       pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
                                       pdpe1gb rdtscp lm constant_tsc art arch_perfmon bts rep_good nopl
                                       xtopology nonstop_tsc cpuid aperfmperf tsc_known_freq pni
                                       pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg fma
                                       cx16 xtpr pdcm pcid dca sse4_1 sse4_2 x2apic movbe popcnt
                                       tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm
                                       3dnowprefetch cpuid_fault epb cat_l3 cat_l2 cdp_l3 intel_ppin
                                       cdp_l2 ssbd mba ibrs ibpb stibp ibrs_enhanced tpr_shadow
                                       flexpriority ept vpid ept_ad fsgsbase tsc_adjust bmi1 avx2 smep
                                       bmi2 erms invpcid cqm rdt_a rdseed adx smap clflushopt clwb
                                       intel_pt sha_ni xsaveopt xsavec xgetbv1 xsaves cqm_llc
                                       cqm_occup_llc cqm_mbm_total cqm_mbm_local split_lock_detect
                                       user_shstk avx_vnni lam wbnoinvd dtherm ida arat pln pts vnmi umip
                                       pku ospke waitpkg gfni vaes vpclmulqdq tme rdpid bus_lock_detect
                                       cldemote movdiri movdir64b enqcmd fsrm md_clear serialize pconfig
                                       arch_lbr ibt flush_l1d arch_capabilities
  Virtualization:                      VT-x
  L1d cache:                           6 MiB (192 instances)
  L1i cache:                           12 MiB (192 instances)
  L2 cache:                            192 MiB (48 instances)
  L3 cache:                            480 MiB (1 instance)
  NUMA node(s):                        3
  NUMA node0 CPU(s):                   0-63
  NUMA node1 CPU(s):                   64-127
  NUMA node2 CPU(s):                   128-191
  Vulnerability Gather data sampling:      Not affected
  Vulnerability Indirect target selection: Not affected
  Vulnerability Itlb multihit:             Not affected
  Vulnerability L1tf:                      Not affected
  Vulnerability Mds:                       Not affected
  Vulnerability Meltdown:                  Not affected
  Vulnerability Mmio stale data:           Not affected
  Vulnerability Reg file data sampling:    Not affected
  Vulnerability Retbleed:                  Not affected
  Vulnerability Spec rstack overflow:      Not affected
  Vulnerability Spec store bypass:         Mitigation; Speculative Store Bypass disabled via prctl
  Vulnerability Spectre v1:                Mitigation; usercopy/swapgs barriers and __user pointer
                                           sanitization
  Vulnerability Spectre v2:                Mitigation; Enhanced / Automatic IBRS; IBPB conditional;
                                           PBRSB-eIBRS Not affected; BHI BHI_DIS_S
  Vulnerability Srbds:                     Not affected
```

(Continued on next page)

Platform Notes (Continued)

```
  Vulnerability Tsa:                    Not affected
  Vulnerability Tsx async abort:        Not affected

From lscpu --cache:
     NAME ONE-SIZE ALL-SIZE WAYS TYPE        LEVEL   SETS PHY-LINE COHERENCY-SIZE
     L1d       32K       6M    8 Data            1     64        1             64
     L1i       64K      12M    8 Instruction     1    128        1             64
     L2         4M     192M   16 Unified         2   4096        1             64
     L3       480M     480M   16 Unified         3 491520        1             64

------------------------------------------------------------
8. numactl --hardware
NOTE: a numactl 'node' might or might not correspond to a physical chip.
  available: 3 nodes (0-2)
  node 0 cpus: 0-63
  node 0 size: 386112 MB
  node 0 free: 383620 MB
  node 1 cpus: 64-127
  node 1 size: 387055 MB
  node 1 free: 381336 MB
  node 2 cpus: 128-191
  node 2 size: 387039 MB
  node 2 free: 378220 MB
  node distances:
  node     0    1    2
     0:   10   15   17
     1:   15   10   15
     2:   17   15   10

------------------------------------------------------------
9. /proc/meminfo
   MemTotal:       1188053240 kB

------------------------------------------------------------
10. who -r
  run-level 3 May 25 10:08

------------------------------------------------------------
11. Systemd service manager version: systemd 252 (252-55.el9)
  Default Target  Status
  multi-user      running

------------------------------------------------------------
12. Services, from systemctl list-unit-files
  STATE            UNIT FILES
  enabled          NetworkManager NetworkManager-dispatcher NetworkManager-wait-online atd auditd bluetooth
                   chronyd crond dbus-broker firewalld getty@ insights-client-boot irqbalance iscsi-onboot
```

(Continued on next page)

Platform Notes (Continued)

```
                 iscsi-starter kdump libstoragemgmt lvm2-monitor mcelog mdmonitor microcode multipathd
                nis-domainname nvmefc-boot-connections rhsmcertd rsyslog selinux-autorelabel-mark smartd
                sshd sssd systemd-boot-update systemd-network-generator systemd-pstore tas tuned udisks2
  enabled-runtime  systemd-remount-fs
  disabled        arp-ethers blk-availability chrony-wait chronyd-restricted cni-dhcp console-getty cpupower
                  debug-shell dnf-system-upgrade iprdump iprinit iprupdate iscsi-init iscsid iscsiuio kpatch
                   kvm_stat ledmon lvm-devices-import man-db-restart-cache-update netavark-dhcp-proxy
                    netavark-firewalld-reload nftables nvmf-autoconnect podman podman-auto-update
                   podman-clean-transient podman-kube@ podman-restart psacct rdisc rhcd rhsm rhsm-facts
                      rpmdb-rebuild selinux-check-proper-disable serial-getty@ sshd-keygen@
                      systemd-boot-check-no-failures systemd-sysext
  indirect        iscsi sssd-autofs sssd-kcm sssd-nss sssd-pac sssd-pam sssd-ssh sssd-sudo systemd-sysupdate
                      systemd-sysupdate-reboot

------------------------------------------------------------
13. Linux kernel boot-time arguments, from /proc/cmdline
  BOOT_IMAGE=(hd1,gpt2)/vmlinuz-5.14.0-611.5.1.el9_7.x86_64
  root=/dev/mapper/rhel_135--171--45-root
  ro
  crashkernel=1G-2G:192M,2G-64G:256M,64G-:512M
  resume=/dev/mapper/rhel_135--171--45-swap
  rd.lvm.lv=rhel_135-171-45/root
  rd.lvm.lv=rhel_135-171-45/swap
  rhgb
  quiet

------------------------------------------------------------
14. cpupower frequency-info
  analyzing CPU 144:
    Unable to determine current policy
    boost state support:
      Supported: yes
      Active: yes

------------------------------------------------------------
15. tuned-adm active
  Current active profile: throughput-performance

------------------------------------------------------------
16. sysctl
  kernel.numa_balancing               1
  kernel.randomize_va_space           2
  vm.compaction_proactiveness        20
  vm.dirty_background_bytes           0
  vm.dirty_background_ratio          10
  vm.dirty_bytes                      0
  vm.dirty_expire_centisecs        3000
```

(Continued on next page)

Platform Notes (Continued)

```
  vm.dirty_ratio                      40
  vm.dirty_writeback_centisecs       500
  vm.dirtytime_expire_seconds      43200
  vm.extfrag_threshold               500
  vm.min_unmapped_ratio                1
  vm.nr_hugepages                      0
  vm.nr_hugepages_mempolicy            0
  vm.nr_overcommit_hugepages           0
  vm.swappiness                       10
  vm.watermark_boost_factor        15000
  vm.watermark_scale_factor           10
  vm.zone_reclaim_mode                 0

------------------------------------------------------------
17. /sys/kernel/mm/transparent_hugepage
  defrag          always defer defer+madvise [madvise] never
  enabled         [always] madvise never
  hpage_pmd_size  2097152
  shmem_enabled   always within_size advise [never] deny force

------------------------------------------------------------
18. /sys/kernel/mm/transparent_hugepage/khugepaged
  alloc_sleep_millisecs   60000
  defrag                      1
  max_ptes_none             511
  max_ptes_shared           256
  max_ptes_swap              64
  pages_to_scan            4096
  scan_sleep_millisecs    10000

------------------------------------------------------------
19. OS release
  From /etc/*-release /etc/*-version
  os-release     Red Hat Enterprise Linux 9.7 (Plow)
  redhat-release Red Hat Enterprise Linux release 9.7 (Plow)
  system-release Red Hat Enterprise Linux release 9.7 (Plow)

------------------------------------------------------------
20. Disk information
SPEC is set to: /home/cpu2026
  Filesystem                      Type  Size  Used Avail Use% Mounted on
  /dev/mapper/rhel_135--171--45-home xfs   344G   37G  308G  11% /home

------------------------------------------------------------
21. /sys/devices/virtual/dmi/id
    Vendor:         PM_1768968004
    Product:        PPM_1768968004
```

(Continued on next page)

Platform Notes (Continued)

```
     Product Family: SMC B14
     Serial:         PS_1768968004

 ------------------------------------------------------------
 22. dmidecode
   Additional information from dmidecode 3.6 follows.  WARNING: Use caution when you interpret this section.
   The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
    "DMTF SMBIOS" standard.
   Memory:
     12x SK Hynix HMCGM4AMBRB970N 96 GB 2 rank 8000


 ------------------------------------------------------------
 23. BIOS
 (This section combines info from /sys/devices and dmidecode.)
    BIOS Vendor:       American Megatrends International, LLC.
    BIOS Version:      1.5
    BIOS Date:         04/22/2026
    BIOS Revision:     5.35
```

Compiler Version Notes

```
==============================================================================
C      | 854.graph500_s(base, peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C++    | 807.ntest_s(base, peak) 827.cppcheck_s(base, peak) 853.ns3_s(base,
       | peak)
------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------

==============================================================================
C++, C | 801.xz_s(base, peak) 817.flac_s(base, peak) 821.gcc_s(base, peak)
       | 823.llvm_s(base, peak) 829.abc_s(base, peak) 834.vpr_s(base, peak)
       | 835.gem5_s(base, peak) 838.diamond_s(base, peak)
       | 846.minizinc_s(base, peak)
------------------------------------------------------------------------------
```

(Continued on next page)

Compiler Version Notes (Continued)

```
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64,
  Version 2026.0.0 Build 20260331
Copyright (C) 1985-2026 Intel Corporation. All rights reserved.
------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
icx

C++ benchmarks:
icpx

Benchmarks using both C and C++:
icpx icx

Base Portability Flags

834.vpr_s: -fno-fast-math

Base Optimization Flags

C benchmarks:
-m64 -std=c18 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xclearwaterforest -O3 -ffp-model=fast -flto -mfpmath=sse
-funroll-loops -qopt-mem-layout-trans=4 -fno-strict-aliasing -fiopenmp
-DSPEC_OPENMP -L/usr/local/jemalloc-5.3.0/lib -ljemalloc

C++ benchmarks:
-m64 -std=c++17 -Wl,-z,muldefs -Wl,-plugin-opt=-inline-threshold=1500
-xclearwaterforest -O3 -ffp-model=fast -flto -mfpmath=sse
-funroll-loops -qopt-mem-layout-trans=4 -pthread -fiopenmp
-DSPEC_OPENMP -L/usr/local/jemalloc-5.3.0/lib -ljemalloc

Benchmarks using both C and C++:
-m64 -std=c++17 -std=c18 -Wl,-z,muldefs
-Wl,-plugin-opt=-inline-threshold=1500 -xclearwaterforest -O3
-ffp-model=fast -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -fno-strict-aliasing -fiopenmp -DSPEC_OPENMP
-pthread -L/usr/local/jemalloc-5.3.0/lib -ljemalloc

Peak Compiler Invocation

C benchmarks:
icx

C++ benchmarks:
icpx

Benchmarks using both C and C++:
icpx icx

Peak Portability Flags

834.vpr_s: -fno-fast-math

Peak Optimization Flags

C benchmarks:

854.graph500_s: basepeak = yes

C++ benchmarks:

807.ntest_s: basepeak = yes

827.cppcheck_s: basepeak = yes

853.ns3_s: -m64 -std=c++17 -Wl,-z,muldefs
-Wl,-plugin-opt=-inline-threshold=1500
-fprofile-generate(pass 1)
-fprofile-use=default.profdata(pass 2) -xCORE-AVX2(pass 1)
-ffp-model=fast -xclearwaterforest(pass 2) -flto
-qopt-mem-layout-trans=4 -O3 -mfpmath=sse -funroll-loops
-pthread -fiopenmp -DSPEC_OPENMP
-L/usr/local/jemalloc-5.3.0/lib -ljemalloc

Benchmarks using both C and C++:

801.xz_s: -m64 -std=c++17 -std=c18 -Wl,-z,muldefs
-Wl,-plugin-opt=-inline-threshold=1500
-fprofile-generate(pass 1)
-fprofile-use=default.profdata(pass 2) -xCORE-AVX2(pass 1)
-ffp-model=fast -xclearwaterforest(pass 2) -flto
-qopt-mem-layout-trans=4 -O3 -mfpmath=sse -funroll-loops

(Continued on next page)

Peak Optimization Flags (Continued)

801.xz_s (continued):
-fno-strict-aliasing -fiopenmp -DSPEC_OPENMP -pthread
-L/usr/local/jemalloc-5.3.0/lib -ljemalloc

817.flac_s: Same as 801.xz_s

821.gcc_s: -m64 -std=c++17 -std=c18 -Wl,-z,muldefs
-fprofile-generate(pass 1)
-fprofile-use=default.profdata(pass 2) -xCORE-AVX2(pass 1)
-ffp-model=fast -xclearwaterforest(pass 2) -flto
-qopt-mem-layout-trans=4 -O3 -mfpmath=sse -funroll-loops
-fno-strict-aliasing -fiopenmp -DSPEC_OPENMP -pthread
-L/usr/local/jemalloc-5.3.0/lib -ljemalloc

823.llvm_s: Same as 821.gcc_s

829.abc_s: basepeak = yes

834.vpr_s: basepeak = yes

835.gem5_s: Same as 801.xz_s

838.diamond_s: Same as 801.xz_s

846.minizinc_s: Same as 801.xz_s

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.html
http://www.spec.org/cpu2026/results/flags/Supermicro-Platform-Settings-V1.2-CWF-revC.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2026/results/flags/Intel-ic2026-official-linux64-v1.1.xml
http://www.spec.org/cpu2026/results/flags/Supermicro-Platform-Settings-V1.2-CWF-revC.xml

SPEC CPU and SPECspeed are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2026 v1.0.1 on 2026-05-25 08:41:45-0400.
Report generated on 2026-08-11 15:24:13 by CPU2026 PDF formatter (unknown).
Originally published on 2026-06-16.