



SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Hatch: Intel Server D50DNP1SB (Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 40.8

SPEChpc 2021_tny_peak = 43.4

hpc2021 License: 13


Test Sponsor: Intel

Tested by: Intel

Test Date: Apr-2025

Hardware Availability: Jan-2023

Software Availability: Mar-2025



Results Table

Benchmark	Base								Peak							
	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Model	Ranks	Thrds/Rnk	Seconds	Ratio	Seconds	Ratio
505.lbm_t	TGT	4	1	23.7	94.9	<u>23.5</u>	<u>95.9</u>	23.4	96.3	TGT	4	1	22.3	101	<u>22.3</u>	<u>101</u>
513.soma_t	TGT	4	1	<u>37.9</u>	<u>97.7</u>	37.8	97.8	38.0	97.3	TGT	4	1	<u>37.9</u>	<u>97.7</u>	37.8	97.8
518.tealeaf_t	TGT	4	1	<u>68.4</u>	<u>24.1</u>	68.5	24.1	67.9	24.3	TGT	4	1	63.6	25.9	<u>64.2</u>	<u>25.7</u>
519.clvleaf_t	TGT	4	1	46.6	35.4	47.1	35.0	<u>46.8</u>	<u>35.3</u>	TGT	4	1	<u>46.5</u>	<u>35.5</u>	46.8	35.3
521.miniswp_t	TGT	4	1	43.6	36.7	<u>43.8</u>	<u>36.5</u>	44.4	36.0	TGT	4	1	34.4	46.6	34.4	<u>46.5</u>
528.pot3d_t	TGT	4	1	<u>67.7</u>	<u>31.4</u>	67.3	31.6	67.8	31.3	TGT	4	1	64.9	32.8	<u>64.9</u>	<u>32.7</u>
532.sph_exa_t	TGT	4	1	118	16.6	<u>118</u>	<u>16.6</u>	118	16.5	TGT	4	1	110	17.8	<u>109</u>	<u>17.9</u>
534.hpgmgfv_t	TGT	4	1	<u>52.0</u>	<u>22.6</u>	51.9	22.6	52.6	22.3	TGT	4	1	49.9	23.6	<u>49.7</u>	<u>23.7</u>
535.weather_t	TGT	4	1	<u>34.9</u>	<u>92.4</u>	34.8	92.6	34.9	92.3	TGT	4	1	34.0	94.8	<u>34.1</u>	<u>94.7</u>

SPEChpc 2021_tny_base = 40.8

SPEChpc 2021_tny_peak = 43.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.



SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Hatch: Intel Server D50DNP1SB (Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 40.8

SPEChpc 2021_tny_peak = 43.4

hpc2021 License: 13

Test Sponsor: Intel

Tested by: Intel

Test Date: Apr-2025

Hardware Availability: Jan-2023

Software Availability: Mar-2025

Hardware Summary

Type of System: Homogenous Cluster
Compute Node: Intel Server D50DNP1SB (Xeon Platinum 8480+)
Interconnect: Mellanox HDR
Compute Nodes Used: 1
Total Chips: 2
Total Cores: 112
Total Threads: 224
Total Memory: 1 TB
Max. Peak Threads: 1

Software Summary

Compiler: Intel oneAPI Compiler 2025.1.0
MPI Library: Intel MPI Library 2021.15 for Linux OS
Other MPI Info: None
Other Software: None
Base Parallel Model: TGT
Base Ranks Run: 4
Base Threads Run: 1
Peak Parallel Models: TGT
Minimum Peak Ranks: 4
Maximum Peak Ranks: 4
Max. Peak Threads: 1
Min. Peak Threads: 1

Node Description: Intel Server D50DNP1SB (Xeon Platinum 8480+)

Hardware

Number of nodes: 1
Uses of the node: Compute
Vendor: Intel
Model: Intel Server D50DNP1SB (2 x Intel Xeon Platinum 8480+, 2.0GHz)
CPU Name: Intel Xeon Platinum 8480+
CPU(s) orderable: 1, 2 chips
Chips enabled: 2
Cores enabled: 112
Cores per chip: 56
Threads per core: 2
CPU Characteristics: Turbo Boost Technology up to 3.8 GHz
CPU MHz: 2000
Primary Cache: 32 KB I + 48 KB D on chip per core
Secondary Cache: 2 MB I+D on chip per core
L3 Cache: 105 MB I+D on chip per chip
Other Cache: None
Memory: 1 TB (16x64 GB DDR5 2Rx4 PC5-4800B-R)
Disk Subsystem: 1 x 1 1TB NVMe M.2 INTEL SSDPELKH010T8
Other Hardware: None
Accel Count: 2
Accel Model: Intel Data Center GPU Max 1550
Accel Vendor: Intel
Accel Type: GPU
Accel Connection: PCIe Gen5 x16
Accel ECC enabled: yes
Accel Description: Intel Data Center GPU Max 1550
Adapter: Mellanox ConnectX-6 HDR
Number of Adapters: 1
Slot Type: PCI-Express 4.0 x16
Data Rate: 200Gbit/s
Ports Used: 1

(Continued on next page)

Software

Accelerator Driver: 25.05.32567
Adapter: Mellanox ConnectX-6 HDR
Adapter Driver: --
Adapter Firmware: 20.38.1900
Operating System: SUSE Linux Enterprise Server 15 SP6
6.4.0-150600.23.42-default
Local File System: lustre
Shared File System: LUSTRE FS
System State: Run level 5
Other Software: None



SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Hatch: Intel Server D50DNP1SB (Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 40.8

SPEChpc 2021_tny_peak = 43.4

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2025
Hardware Availability: Jan-2023
Software Availability: Mar-2025

Node Description: Intel Server D50DNP1SB (Xeon Platinum 8480+)

Hardware (Continued)

Interconnect Type: Mellanox HDR

Interconnect Description: Mellanox HDR

Hardware

Vendor: Mellanox
Model: Mellanox HDR
Switch Model: Mellanox Technologies MT28908 Family InfiniBand Switch
Number of Switches: 12
Number of Ports: 40
Data Rate: 200 Gbit/s
Firmware: 20.38.1900
Topology: Fat-tree
Primary Use: MPI Traffic, LustreFS traffic

Software

: --

Submit Notes

The config file option 'submit' was used.

General Notes

Environment variables set by runhpc before the start of the run:
LIBOMPTARGET_LEVEL_ZERO_USE_IMMEDIATE_COMMAND_LIST = "all"
I_MPI_FABRICS=shm:ofi
I_MPI_OFFLOAD=1
I_MPI_OFFLOAD_CELL=tile
I_MPI_OFFLOAD_TOPOLIB=level_zero
I_MPI_OFFLOAD_CELL_LIST=0,1,2,3,4,5,6,7
For the following tests src.alt was used in PEAK:
518 519 521 528 532 534 535

Platform Notes

Device Vendor	Intel
Device Version	OpenCL 3.0 NEO
Driver Version	25.05.32567
Base clock	900MHZ
Max clock frequency	1600MHZ
Tiles	2
Slices per Tile	1
Max compute units per Tile	512

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Hatch: Intel Server D50DNP1SB (Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 40.8

SPEChpc 2021_tny_peak = 43.4

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2025
Hardware Availability: Jan-2023
Software Availability: Mar-2025

Platform Notes (Continued)

Sub-slices per slice	64
EUs per sub-slice	8
Threads per EU	8
Max work item dimensions	3
Max work item sizes	1024x1024x1024
Max work group size	1024
Preferred work group size multiple	32
Max sub-groups per work group	64
Sub-group sizes	16, 32
L1 Cache per EU	65536
L2 cache size	427819008
Global memory size	137438953472
Address bits	64, Little-Endian

Compiler Version Notes

=====

CXXC 532.sph_exa_t(base, peak)

Intel(R) oneAPI DPC++/C++ Compiler 2025.1.0 (2025.1.0.20250317)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir:
/lfs/lfs17/mknyazev/intel/2025.1/oneapi/compiler/2025.1/bin/compiler
Configuration file:
/lfs/lfs17/mknyazev/intel/2025.1/oneapi/compiler/2025.1/bin/compiler/./icpx.cfg

=====

CC 505.lbm_t(base, peak) 513.soma_t(base, peak) 518.tealeaf_t(base, peak)
521.miniswp_t(base, peak) 534.hpgmgfv_t(base, peak)

Intel(R) oneAPI DPC++/C++ Compiler 2025.1.0 (2025.1.0.20250317)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir:
/lfs/lfs17/mknyazev/intel/2025.1/oneapi/compiler/2025.1/bin/compiler
Configuration file:
/lfs/lfs17/mknyazev/intel/2025.1/oneapi/compiler/2025.1/bin/compiler/./icx.cfg

=====

FC 519.clvleaf_t(base, peak) 535.weather_t(base, peak)

ifx (IFX) 2025.1.0 20250317
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Hatch: Intel Server D50DNP1SB (Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 40.8

SPEChpc 2021_tny_peak = 43.4

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2025
Hardware Availability: Jan-2023
Software Availability: Mar-2025

Compiler Version Notes (Continued)

=====

```
FC 528.pot3d_t(base, peak)
```

```
ifx: command line warning #10157: ignoring option '-W'; argument is of wrong
type
ifx (IFX) 2025.1.0 20250317
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.
```

Base Compiler Invocation

C benchmarks:
mpiicc -cc=icx

C++ benchmarks:
mpiicpc -cxx=icpx

Fortran benchmarks:
mpiifort -fc=ifx

Base Portability Flags

```
505.lbm_t: -DUSE_MPI
513.soma_t: -DUSE_MPI -DSPEC_NO_VAR_ARRAY_REDUCE
518.tealeaf_t: -DUSE_MPI
519.clvleaf_t: -DUSE_MPI
528.pot3d_t: -DUSE_MPI
535.weather_t: -DUSE_MPI
```

Base Optimization Flags

C benchmarks:

```
-O3 -xCORE-AVX512 -flto -mprefer-vector-width=512 -ffast-math
-fiopenmp -fopenmp-targets=spir64_gen
-ftarget-register-alloc-mode=pvc:auto
-Xopenmp-target-backend '-device pvc -revision_id 0x2f' -DSPEC_COLLAPSE
-DSPEC_ACCEL_AWARE_MPI -fopenmp-optimistic-collapse
```

(Continued on next page)



SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Hatch: Intel Server D50DNP1SB (Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 40.8

SPEChpc 2021_tny_peak = 43.4

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2025
Hardware Availability: Jan-2023
Software Availability: Mar-2025

Base Optimization Flags (Continued)

C++ benchmarks:

-O3 -xCORE-AVX512 -flto -mprefer-vector-width=512 -ffast-math
-fiopenmp -fopenmp-targets=spir64_gen
-ftarget-register-alloc-mode=pvc:auto
-Xopenmp-target-backend '-device pvc -revision_id 0x2f' -DSPEC_COLLAPSE
-DSPEC_ACCEL_AWARE_MPI

Fortran benchmarks:

-DSPEC_COLLAPSE -O3 -xCORE-AVX512 -DSPEC_ACCEL_AWARE_MPI -flto
-mprefer-vector-width=512 -ffast-math -fiopenmp
-fopenmp-targets=spir64_gen -ftarget-register-alloc-mode=pvc:auto
-Xopenmp-target-backend '-device pvc -revision_id 0x2f'
-fopenmp-target-loopopt

Base Other Flags

Fortran benchmarks:

528.pot3d_t: -Wno-incompatible-function-pointer-types

Peak Compiler Invocation

C benchmarks:

mpiicc -cc=icx

C++ benchmarks:

mpiicpc -cxx=icpx

Fortran benchmarks:

mpiifort -fc=ifx

Peak Portability Flags

505.lbm_t: -DUSE_MPI
513.soma_t: -DUSE_MPI -DSPEC_NO_VAR_ARRAY_REDUCE
518.tealeaf_t: -DUSE_MPI
519.clvleaf_t: -DUSE_MPI
528.pot3d_t: -DUSE_MPI
535.weather_t: -DUSE_MPI



SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Hatch: Intel Server D50DNP1SB (Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 40.8

SPEChpc 2021_tny_peak = 43.4

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2025
Hardware Availability: Jan-2023
Software Availability: Mar-2025

Peak Optimization Flags

C benchmarks:

```
505.lbm_t: -O3 -xCORE-AVX512 -flto -mprefer-vector-width=512
-ffast-math -fiopenmp -fopenmp-targets=spir64_gen
-ftarget-register-alloc-mode=pvc:large
-Xopenmp-target-backend '-device pvc -revision_id 0x2f'
-DSPEC_COLLAPSE -DSPEC_ACCEL_AWARE_MPI
-fopenmp-optimistic-collapse
```

513.soma_t: basepeak = yes

```
518.tealeaf_t: -O3 -xCORE-AVX512 -flto -mprefer-vector-width=512
-ffast-math -fiopenmp -fopenmp-targets=spir64_gen
-ftarget-register-alloc-mode=pvc:auto
-Xopenmp-target-backend '-device pvc -revision_id 0x2f'
-DSPEC_COLLAPSE -DSPEC_ACCEL_AWARE_MPI
-fopenmp-optimistic-collapse
```

521.miniswp_t: Same as 518.tealeaf_t

534.hpgmgfv_t: Same as 518.tealeaf_t

C++ benchmarks:

```
-O3 -xCORE-AVX512 -flto -mprefer-vector-width=512 -ffast-math
-fiopenmp -fopenmp-targets=spir64_gen
-ftarget-register-alloc-mode=pvc:auto
-Xopenmp-target-backend '-device pvc -revision_id 0x2f' -DSPEC_COLLAPSE
-DSPEC_ACCEL_AWARE_MPI
```

Fortran benchmarks:

```
-DSPEC_COLLAPSE -O3 -xCORE-AVX512 -DSPEC_ACCEL_AWARE_MPI -flto
-mprefer-vector-width=512 -ffast-math -fiopenmp
-fopenmp-targets=spir64_gen -ftarget-register-alloc-mode=pvc:auto
-Xopenmp-target-backend '-device pvc -revision_id 0x2f'
-fopenmp-target-loopopt
```

Peak Other Flags

Fortran benchmarks:

528.pot3d_t: -Wno-incompatible-function-pointer-types



SPEChpc™ 2021 Tiny Result

Copyright 2021-2025 Standard Performance Evaluation Corporation

Intel

Hatch: Intel Server D50DNP1SB (Xeon Platinum 8480+)

SPEChpc 2021_tny_base = 40.8

SPEChpc 2021_tny_peak = 43.4

hpc2021 License: 13
Test Sponsor: Intel
Tested by: Intel

Test Date: Apr-2025
Hardware Availability: Jan-2023
Software Availability: Mar-2025

The flags file that was used to format this result can be browsed at
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2025-05-22.00.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/hpc2021/flags/Intel_compiler_flags.2025-05-22.00.xml

SPEChpc is a trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEChpc2021 v1.1.9 on 2025-04-14 06:48:01-0400.
Report generated on 2025-05-22 11:01:12 by hpc2021 PDF formatter v1.0.3.
Originally published on 2025-05-21.