



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
RS/6000 44P-270 (2 CPU, 8MB L2)

SPECfp_rate2000 = 7.98

SPECfp_rate_base2000 = 6.99

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Sep-2000 | Hardware Avail: Oct-2000 | Software Avail: Oct-2000

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	529	7.02	2	307	12.1
171.swim	2	1289	5.58	2	980	7.34
172.mgrid	2	680	6.14	2	688	6.07
173.applu	2	788	6.18	2	785	6.21
177.mesa	2	509	6.38	2	513	6.33
178.galgel	2	755	8.92	2	753	8.93
179.art	2	273	22.1	2	273	22.1
183.quake	2	309	9.75	2	227	13.3
187.facerec	2	878	5.02	2	528	8.34
188.amp	2	789	6.47	2	685	7.46
189.lucas	2	817	5.68	2	814	5.70
191.fma3d	2	750	6.50	2	741	6.57
200.sixtrack	2	593	4.30	2	592	4.31
301.apsi	2	852	7.08	2	795	7.58

Hardware

CPU: IBM Power3-II
CPU MHz: 375
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 2,4
Parallel: No
Primary Cache: 32KBI+64KBD (on chip)
Secondary Cache: 8MB (I+D) (off chip)
L3 Cache: None
Other Cache: None
Memory: 4GB
Disk Subsystem: 1x9.1GB IBM Ultra-2 SCSI, 10000RPM
Other Hardware: None

Software

Operating System: AIX 4.3.3 + beta of APAR IY12051
Compiler: Fortran 77 and 90: IBM xl Fortran 6.1 invoked as 'xlF90'
C: IBM VAC 5.0 invoked as 'xlC'
File System: AIX/JFS
System State: Multi-user

Notes/Tuning Information

Portability Flags

-qfixed used in: wupwise, swim, mgrid, applu, galgel, sixtrack, apsi
-qsuffix=f=f90 used in: galgel, facerec, lucas, fma3d

NOTE: The flag combination 'qpfd1/qpfd2' indicates a 2 step compilation process, the exact process is as follows:

```
fdo_pre0 = rm -rf ${PDFDIR}; mkdir -p ${PDFDIR}
PASS1_FLAGS    =-qpfd1 {optimization flags}
PASS1_LDFLAGS  ={libraries} -L{pdf library location} -lpdf
PASS2_FLAGS    =-qpfd2 {optimization flags}
PASS2_LDFLAGS  =-{libraries}
```

Base Optimization Flags:

```
Fortran: -qpfd1/pdf2 -O3 -qarch=pwr3 -lmass
C: -O5 -lmass
```

Peak Optimization Flags:

```
168.wupwise: -qpfd1/pdf2 -O4 -qipa=level=2 -lmass
171.swim: -qpfd1/pdf2 -O4 -qipa=level=2 -qhot -lmass
172.mgrid:-O3 -qarch=pwr3 -qhot
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
RS/6000 44P-270 (2 CPU, 8MB L2)

SPECfp_rate2000 = 7.98
SPECfp_rate_base2000 = 6.99

SPEC license #: 11 | Tested by: IBM, Austin, TX | Test date: Sep-2000 | Hardware Avail: Oct-2000 | Software Avail: Oct-2000

Notes/Tuning Information (Continued)

```
173.applu: -qpdf1/pdf2 -O3 -qarch=pwr3 -lmass
177.mesa: -O5 -lmass
178.galgel: -O4 -qipa=level=2 -qhot -lmass
179.art: -O5 -lmass
183.quake: -O5 -lmass -lhm
187.facerec: -O3 -qarch=pwr3 -qhot -lmass
188.amp: -O3 -qarch=pwr3 -bnso -bI:/lib/syscalls.exp
189.lucas: -qpdf1/pdf2 -O3 -qarch=pwr3 -lmass
191.fma3d: -O4 -qipa=level=2 -qhot -lmass
200.sixtrack: -O3 -qarch=pwr3
301.apsi: -O4 -qipa=level=2 -qhot -lmass -bnso -bI:/lib/syscalls.exp
```