



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

## Advanced Micro Devices

Gigabyte GA-7DX Motherboard, AMD Athlon (TM) XP 1500+

SPECfp2000 = 536

SPECfp\_base2000 = 494

SPEC license #: 49 Tested by: AMD Austin TX Test date: Sep-2001 Hardware Avail: Oct-2001 Software Avail: Sep-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	223	717	223	716	
171.swim	3100	391	793	391	793	
172.mgrid	1800	375	481	374	481	
173.applu	2100	460	456	455	462	
177.mesa	1400	198	708	191	735	
178.galgel	2900	638	455	361	802	
179.art	2600	706	368	668	389	
183.quake	1300	301	431	246	528	
187.facerec	1900	337	563	335	566	
188.amp	2200	598	368	557	395	
189.lucas	2000	374	534	372	538	
191.fma3d	2100	385	545	385	545	
200.sixtrack	1100	326	338	316	348	
301.apsi	2600	647	402	559	465	

### Hardware

CPU: AMD Athlon (TM) XP 1500+  
 CPU MHz: 1333  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
 CPU(s) orderable: 1  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD on chip  
 Secondary Cache: 256KB(I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 2x128MB PC2100 DDR SDRAM CL2 Micron  
 Disk Subsystem: IBM DPTA-372020  
 Other Hardware: None

### Software

Operating System: Windows 2000 SP2  
 Compiler: Compaq Visual Fortran 6.6  
 Intel C/C++ 5.0.1 build 010525Z and  
 Intel Fortran 5.0.1 build 010525Z  
 Microsoft Visual Studio 6.0 SP5 (libraries)  
 MicroQuill Smartheap Library 5.0  
 File System: FAT32  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
icl and ifl are the Intel C/C++ and Fortran compilers
f90 is the Compaq Fortran compiler
shlw32M.lib is the SmartHeap library V5.0 from MicroQuill www.microquill.com
Portability:
178.galgel: -FI -Fe$@ -link -stack:32000000
Baseline: C icl -QxK -Qipo +FDO shlw32M.lib
Baseline: Fortran ifl -O3 -QxK -Qipo +FDO
Peak tuning:
168.wupwise: ifl -O3 -QxK -Qwp_ipo +FDO
171.swim: ifl -O3 -QxK -Qwp_ipo +FDO
172.mgrid: ifl -O3 -QxK -Qwp_ipo +FDO
173.applu: ifl -O3 -QxK -Qwp_ipo -Qscalar_rep- -Qauto +FDO
177.mesa: icl -O3 -QxK -Qwp_ipo -Oa -Qunroll10 +FDO shlw32M.lib
178.galgel: f90 -Optimize:5 -fast
179.art: icl -O3 -QxK -QaxW -Qwp_ipo -Oa +FDO shlw32M.lib
183.quake: icl -O3 -QxK -Qwp_ipo -Qrcd -Oa +FDO shlw32M.lib
```



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Gigabyte GA-7DX Motherboard, AMD Athlon (TM) XP 1500+

SPECfp2000 = 536

SPECfp\_base2000 = 494

SPEC license #: 49 | Tested by: AMD Austin TX | Test date: Sep-2001 | Hardware Avail: Oct-2001 | Software Avail: Sep-2001

## Notes/Tuning Information (Continued)

```
187.facerec: f90 -Optimize:5 -fast
188.ammf: icl -O3 -QxK -Qwp_ipo -Oa +FDO
189.lucas: ifl -O3 -QxK -Qwp_ipo +FDO shlw32M.lib
191.fma3d: ifl -O3 -QxK -Qwp_ipo +FDO
200.sixtrack: ifl -QxK -QaxW -Qwp_ipo -Qprefetch +FDO
301.apsi: f90 -Optimize:5 -fast
```

Library ordering for 189.lucas (to include SmartHeap correctly with default libs):

```
LIBS=libIEPCF90.lib libintrins.lib libF90.lib
libqwind.lib libm.lib shlw32M.lib LIBC.lib libirc.lib OLDNAMES.lib
ONESTEP is used for all base and peak runs
```

The tested system can be assembled using an ATX case such as the Antec KS-282, a 300W power supply such as the Sparkle FSP300-60GT, and a PCI or AGP video card. The System bus runs at 266MHz