



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 300 8X 500MHz R14k

SPECint_rate2000 = **34.0**
SPECint_rate_base2000 = **32.7**

SPEC license #: 4 Tested by: SGI Test date: Oct-2001 Hardware Avail: Oct-2001 Software Avail: Aug-2001

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	519	25.0	8	504	25.8
175.vpr	8	368	35.3	8	365	35.6
176.gcc	8	311	32.8	8	313	32.6
181.mcf	8	624	26.8	8	624	26.8
186.crafty	8	267	34.7	8	249	37.2
197.parser	8	579	28.9	8	553	30.2
252.eon	8	300	40.2	8	281	42.9
253.perlbnk	8	608	27.5	8	601	27.8
254.gap	8	436	23.4	8	429	23.8
255.vortex	8	360	49.0	8	315	56.0
256.bzip2	8	446	31.2	8	412	33.8
300.twolf	8	571	48.8	8	571	48.8

Hardware

CPU: R14000
CPU MHz: 500
FPU: Integrated
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
CPU(s) orderable: 2-8
Parallel: No
Primary Cache: 32KBI + 32KBD on chip
Secondary Cache: 2MB(I+D) off chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 GB
Disk Subsystem: 1 x 18 GB FC, 2 x 18 GB FC (striped)
Other Hardware: None

Software

Operating System: IRIX 6.5.13m
Compiler: MIPSpro 7.3.1.2m C, C++
SCSL 1.3 Math Library
File System: xfs
System State: Single-user

Notes/Tuning Information

Baseline optimization flags (C and C++ use same flags):

PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)
PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

Portability Flags:

176.gcc: -Dalloca=__builtin_alloca -DMIPS -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSGI
252.eon: -lm
253.perlbnk: -DSPEC_CPU2000_SGI -DI_FCNTL
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_IOCTL_PROTO
-DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
300.twolf: -DHAVE_SIGNED_CHAR

Peak optimization flags:

note: all occurrences of (FEEDBACK) below means compiled with a two-step process:

PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)
164.gzip: -Ofast=ip27 -IPA:space=500:plimit=500 -lmalloc (FEEDBACK)
175.vpr: -Ofast=ip27 -IPA:space=300:plimit=10000:callee_limit=5000:linear=on
. -LNO:prefetch Ahead=2 -INLINE:aggressive=on
. -OPT:Olimit=0:alias=disjoint:alias=restrict -CG:ld_latency=10 -lmalloc (FEEDBACK)
181.mcf: basepeak=yes



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 300 8X 500MHz R14k

SPECint_rate2000 = 34.0
SPECint_rate_base2000 = 32.7

SPEC license #: 4 | Tested by: SGI | Test date: Oct-2001 | Hardware Avail: Oct-2001 | Software Avail: Aug-2001

Notes/Tuning Information (Continued)

```

176.gcc: -Ofast=ip27 -CG:ld_latency=4 (FEEDBACK)
186.crafty: -Ofast=ip27 -LNO:prefetch=0 -OPT:goto=off -CG:ld_latency=4 -lmalloc (FEEDBACK)
197.parser: -Ofast=ip27 -IPA:min_hot=14 (FEEDBACK)
252.eon: -Ofast=ip27 -LNO:prefetch=0 -LANG:exceptions=off -CG:ld_latency=4 -lmalloc -lm
      (FEEDBACK)
253.perlbnk: -Ofast=ip27 -IPA:use_intrinsic -Wl,-x (FEEDBACK)
254.gap: -Ofast=ip27 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4
      -OPT:alias=restrict:alias=disjoint -IPA:min_hot=7 -CG:ld_latency=8 -lmalloc (FEEDBACK)
255.vortex: -Ofast=ip27 -IPA:use_intrinsic
      -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4 -LNO:opt=0 -CG:ld_latency=5
      -IPA:min_hot=14 -TENV:X=4 -IPA:space=500:plimit=3600 -OPT:goto=off (FEEDBACK)
256.bzip2: -Ofast=ip27 -IPA:min_hot=5:space=500:plimit=2900 -INLINE:aggressive=on (FEEDBACK)
300.twolf: basepeak=yes

```

The following O/S parameters were set:

```

setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
system -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
system -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
system -i ; r12k_bdiag = 0x4000000 ;
limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```

rm -rf /tmp/SPEC2000 ; mkdir /tmp/SPEC2000 ; cd /tmp/SPEC2000 ; mkdir FBDIR_base ; mkdir FBDIR_peak
The first disk mentioned in the Disk Subsystem is the system disk. A striped
XFS filesystem was created using the rest of the disks and the benchmark was
run on this.

```