



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEPOWER850 (1350MHz)

SPECfp\_rate2000 = 194

SPECfp\_rate\_base2000 = 143

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Jun-2003 | Hardware Avail: Aug-2003 | Software Avail: May-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	16	312	95.1	16	160	185
171.swim	16	535	108	16	141	409
172.mgrid	16	378	88.3	16	345	96.9
173.applu	16	340	115	16	208	188
177.mesa	16	282	92.2	16	234	111
178.galgel	16	152	355	16	111	484
179.art	16	26.4	1830	16	26.3	1833
183.quake	16	133	182	16	133	182
187.facerec	16	189	186	16	174	203
188.amp	16	330	124	16	297	137
189.lucas	16	373	99.4	16	373	99.4
191.fma3d	16	388	100	16	331	118
200.sixtrack	16	598	34.1	16	269	75.8
301.apsi	16	278	174	16	277	174

### Hardware

CPU: SPARC64 V  
CPU MHz: 1350  
FPU: Integrated  
CPU(s) enabled: 16 cores, 16 chips, 1 core/chip  
CPU(s) orderable: 1 to 16 (increments of 1)  
Parallel: None  
Primary Cache: 128KBI+128KBD on chip  
Secondary Cache: 2MB(I+D) on chip  
L3 Cache: None  
Other Cache: None  
Memory: 65536MB  
Disk Subsystem: 1 x 36.4GB SCSI (10000rpm)  
Other Hardware: None

### Software

Operating System: Solaris8 2/02 with current patches (see notes)  
Compiler: Fujitsu Parallelnavi 2.1 with patch 912528-02  
Sun ONE Studio 8  
Sun Performance Library 8  
File System: ufs  
System State: multi user

## Notes/Tuning Information

FDO: (for Parallelnavi 2.1)  
fdo\_pre0=rm -rf `pwd`/\*.f.d  
PASS1=-Kpg PASS2=-Kpu

FDO: (for Sun ONE Studio 8 )  
fdo\_pre0=rm -rf ./feedback.profile ./SunWS\_cache  
PASS1=-xprofile=collect:./feedback  
PASS2=-xprofile=use:./feedback

Baseline:  
(using Fortran compiler of Sun ONE Studio 8 )  
-fast -xtarget=ultra3 -lprism32 FDO  
  
(using C compiler of Sun ONE Studio 8 )  
-fast -xtarget=ultra3 -xipo=2 ONESTEP=yes FDO

Peak:



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEPOWER850 (1350MHz)

SPECfp\_rate2000 = 194

SPECfp\_rate\_base2000 = 143

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Jun-2003 | Hardware Avail: Aug-2003 | Software Avail: May-2003

## Notes/Tuning Information (Continued)

(using FORTRAN90 compiler of Parallelnavi 2.1)

```

168.wupwise: -fs -Kfast_GP2=2,largepage -O5 -x dir=./
             -Kpreex,prefetch_infer,alignl=64,preschedule_length=17 -fs FDO
172.mgrid:  -fs -Kfast_GP2=2,largepage,GREG_SYSTEM
             -Kpreex,prefetch_line=6,commonpad=144,alignc=64 -fs FDO
191.fma3d:  -fs -Kfast_GP2=2,largepage,GREG_SYSTEM -x dir=./ -x55
             -Kpreex,prefetch_infer,prefetch=4 -fs -Am FDO
200.sixtrack: -fs -Kfast_GP2=2,largepage,GREG_SYSTEM -O5
             -Kunroll=2,preex,prefetch_line=8,frecipro,novfunc,preschedule_length=27 -fs FDO

```

(using FORTRAN90 compiler of Sun ONE Studio 8 )

```

171.swim: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:2048/64/4
          -xpad=common:1660 -xprefetch=latx:2.6
          -Qoption iropt -Atile:skewp:b10,-Ainline:cs=700 -lprism32
173.applu: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:2048/64/4
          -xchip=ultra3 -xipo=2 -xprefetch=latx:0.6 FDO ONESTEP=yes
178.galgel: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:2048/64/4
          -xipo=2 -xprefetch=latx:0.4 -Qoption iropt -Addint:sf=9
          -lprism32 -xlic_lib=sunperf RM_SOURCES=lapak.f90 FDO ONESTEP=yes
187.facerec: -xO5 -xchip=ultra3 -xcache=128/64/2:2048/64/4 -xarch=v8plus
          -xprefetch=yes -xprefetch_level=1 -xprefetch=latx:2.2 -xvector=no
          -xdepend -fttrap=%none -fns -fsimple=2 -lprism32 FDO ONESTEP=yes
189.lucas: basepeak=yes
301.apsi: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:2048/64/4
          -xchip=ultra3 -xipo=2 -xprefetch=latx:2.0 -Qoption iropt -Mt450
          -lprism32 FDO ONESTEP=yes

```

(using C compiler of Sun ONE Studio 8 )

```

177.mesa: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:2048/64/4
          -xchip=ultra2 -xipo=2 -xrestrict -xalias_level=strong
          -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qms_pipe+unoovf FDO ONESTEP=yes
179.art: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:2048/64/4
          -xchip=ultra3 -xipo=2 -xalias_level=std FDO ONESTEP=yes
183.quake: basepeak=yes
188.ammp: -fast -xarch=v8plusb -xchip=ultra3cu -xcache=128/64/2:2048/64/4
          -xchip=ultra3 -xipo=2 -xalias_level=std -xdepend -xprefetch=latx:2.6
          -xrestrict -lprism32 FDO ONESTEP=yes

```

Portability:

178.galgel: -e -fixed (for Sun ONE Studio 8 )

Note:

System Tunables: (for /etc/system)

```

set consistent_coloring=1,
set shmsys:shminfo_shmmax=8589934592,set shmsys:shminfo_shmmni=256,
set shmsys:shminfo_shmseg=400,set shmsys:shminfo_shmmmin=1
set tune_t_fsflushr = 86400
set autoup = 86400

```

System Tunables: (for /etc/opt/FJSVpnm/lpg.conf)

TSS=4096M, SHMSEGSIZE=256M

Shell Environments:

```

LD_LIBRARY_PATH="/opt3/SUNWspro/prod/lib/v8plusb"
PRISM_HEAP=268435456
PRISM_MODE=2

```

Feedback directed optimization was used except 171.swim(peak).

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Limited  
PRIMEPOWER850 (1350MHz)

SPECfp\_rate2000 = 194  
SPECfp\_rate\_base2000 = 143

SPEC license #: 19 | Tested by: Fujitsu Limited | Test date: Jun-2003 | Hardware Avail: Aug-2003 | Software Avail: May-2003

## Notes/Tuning Information (Continued)

Processes were bound to CPUs using "submit=pbind".  
Stack size set to unlimited via "ulimit -s unlimited".  
Sun ONE Studio 8 , posted at URL <http://www.sun.com/software/sundev/suncc/>  
was used for this submission.  
All patches for Solaris8 posted at  
[http://access1.sun.com/patch.public/cgi-bin/show\\_list.cgi/wrk/Sun\\_ONE\\_Studio\\_7\\_SPARC\\_SunOS\\_5.8](http://access1.sun.com/patch.public/cgi-bin/show_list.cgi/wrk/Sun_ONE_Studio_7_SPARC_SunOS_5.8)  
as of date 2003/04/21 were applied: 108434-12, 108435-12, 111697-04, 111721-03.