



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECfp_rate2000 = 37.2
SPECfp_rate_base2000 = 33.9

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Jul-2004 Hardware Avail: Jul-2004 Software Avail: Jul-2004

| Benchmark | Base Copies | Base Runtime | Base Ratio | Copies | Runtime | Ratio |
|--------------|-------------|--------------|------------|--------|---------|-------|
| 168.wupwise | 2 | 99.6 | 37.3 | 2 | 78.7 | 47.1 |
| 171.swim | 2 | 156 | 46.2 | 2 | 148 | 48.7 |
| 172.mgrid | 2 | 160 | 26.0 | 2 | 138 | 30.3 |
| 173.applu | 2 | 165 | 29.5 | 2 | 141 | 34.5 |
| 177.mesa | 2 | 77.0 | 42.2 | 2 | 70.9 | 45.8 |
| 178.galgel | 2 | 112 | 60.3 | 2 | 103 | 65.5 |
| 179.art | 2 | 262 | 23.0 | 2 | 168 | 35.8 |
| 183.quake | 2 | 98.6 | 30.6 | 2 | 92.7 | 32.5 |
| 187.facerec | 2 | 86.4 | 51.0 | 2 | 86.4 | 51.0 |
| 188.amp | 2 | 162 | 31.4 | 2 | 159 | 32.1 |
| 189.lucas | 2 | 135 | 34.5 | 2 | 134 | 34.7 |
| 191.fma3d | 2 | 143 | 34.0 | 2 | 143 | 34.0 |
| 200.sixtrack | 2 | 149 | 17.1 | 2 | 149 | 17.1 |
| 301.apsi | 2 | 176 | 34.3 | 2 | 174 | 34.7 |

Hardware

CPU: AMD Opteron (TM) 850
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1,2,4
Parallel: No
Primary Cache: 64KBI + 64KBD on chip
Secondary Cache: 1024KB (I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1GB, PC2700 CL2.5 DDR SDRAM ECC Registered
Disk Subsystem: SCSI, 73GB, 10K RPM
Other Hardware: None

Software

Operating System: SuSE Linux 8.0 SLES 64 bit (SP3)
Compiler: PathScale EKO Compiler Suite, Release 1.1
SuSE optional gcc 3.3 (from SLES8 SP3)
PGI Fortran 5.2 (build 5.2-0E)
AMD Core Math Library (Version 2.0) for AMD64
File System: Linux/ext3
System State: Multi-user, Run level 3

Notes/Tuning Information

A two-pass compilation method is used where indicated:

+PSFDO indicates PathScale feedback

PASS1: -fb_create fbdata

PASS2: -fb_opt fbdata

+ACML is the AMD Core Math Library V2.0

Compilers:

C: pathcc (PathScale C) unless otherwise noted

Fortran: pathf90 (PathScale f90) unless otherwise noted

If other compilers are used, they are indicated as:

gcc: Gnu C

pgf90: PGI Fortran

Floating Point base tuning:

Fortran: pgf90 -fastsse -Mipa=fast -Msmart

C: pathcc -Ofast -WOPT:mem_opnds=on +PSFDO

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V40z

SPECfp_rate2000 = 37.2

SPECfp_rate_base2000 = 33.9

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Jul-2004 Hardware Avail: Jul-2004 Software Avail: Jul-2004

Notes/Tuning Information (Continued)

Floating Point peak tuning:

```

168.wupwise: pgf90 -fastsse -Mipa=fast,inline -Msmart
171.swim: -Ofast -OPT:ro=3 -LNO:fusion=2:prefetch=2
172.mgrid: -O3 -OPT:Ofast
           -LNO:fusion=2:blocking=off:ou_max=5:sclrze=off:prefetch=2
           -OPT:unroll_times=8:unroll_size=256:ro=3
           -CG:gcm=off:cflow=off
173.applu: -O3 -ipa
           -LNO:fusion=2:interchange=OFF:blocking=OFF:ou_prod_max=10
           :ou_max=5:prefetch=2 -OPT:IEEE_arith=1:ro=3:unroll_size=0
           -TENV:X=4 -WOPT:mem_opnds=on:retype_expr=on:val=0 -CG:local_fwd_sched=on
177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +PSFDO
178.galgel: pgf90 -fastsse -Mipa=fast -mp +ACML
           RM_SOURCES=lapak.f90 ONESTEP
179.art: -O3 -OPT:Ofast -fno-math-errno -m32 +PSFDO
183.earthquake: gcc -DSPEC_CPU2000_LP64 -O3 -funroll-all-loops -ffast-math
           -finline-limit=2000 ONESTEP
187.facerec: basepeak=true
188.ammp: -O3 -OPT:alias=disjoint:unroll_times=8:Ofast:ro=3
           -fno-math-errno -TENV:X=4 +PSFDO
189.lucas: pgf90 -fastsse -Mipa=fast,inline -Msmart
191.fma3d: basepeak=true
200.sixtrack: basepeak=true
301.apsi: -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0:blocking=off
           -IPA:linear=on:plimit=525

```

Portability:

178.galgel: -Mfixed

Notes:

BIOS build 2.1.0.9E, default setting was used.
Only two CPUs were present in the system, other CPUs were physically removed.