



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI

SGI Altix 3700 Bx2 (1600MHz 9M L3, Itanium 2)

SPECint_rate2000 = --

SPECint_rate_base2000 = 133

SPEC license #: 4 | Tested by: SGI | Test date: Oct-2004 | Hardware Avail: Nov-2004 | Software Avail: Nov-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	8	132	98.5			
175.vpr	8	117	111			
176.gcc	8	69.3	147			
181.mcf	8	68.9	242			
186.crafty	8	78.0	119			
197.parser	8	173	96.7			
252.eon	8	65.5	184			
253.perlbnk	8	134	124			
254.gap	8	117	87.1			
255.vortex	8	85.5	206			
256.bzip2	8	121	115			
300.twolf	8	198	140			

Hardware

CPU: Intel Itanium 2
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
CPU(s) orderable: 16-256
Parallel: No
Primary Cache: 16KBI + 16KBD on chip, per core
Secondary Cache: 256KB (I+D) on chip, per core
L3 Cache: 9.0MB (I+D) on chip, per core
Other Cache: N/A
Memory: 32 GB (1GB PC2700 DIMMS)
Disk Subsystem: 16 x 73 GB FibreChannel (Seagate Cheetah 15k rpm)
Other Hardware: None

Software

Operating System: SGI ProPack(TM) v3.0 Service Pack 1
Compiler: Intel(R) C++ Compiler for Linux 8.1 (Build 20041021)
MicroQuill SmartHeap Library 7.01 (www.microquill.com)
File System: xfs
System State: Single-user

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -fast -auto_ilp32 +FDO
C++ programs: -fast -ansi_alias +FDO
Extra Libraries: libsmartheap64.a

Portability Flags:

176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca
186.crafty: -DLINUX_i386
252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST -DFMAX_IS_DOUBLE
253.perlbnk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
-DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
-DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
255.vortex: -DSPEC_CPU2000_LP64 srcalt=closed_files

Extra CPUs were disabled at firmware.
Processes were bound to CPUs using dplace.