



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP Integrity rx2620-2 (1.6GHz/6MB Itanium 2)

SPECint_rate2000 = 35.5
SPECint_rate_base2000 = 35.5

SPEC license #: 3 Tested by: HP Richardson Test date: Dec-2004 Hardware Avail: Dec-2004 Software Avail: Jan-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	2	131	24.8	2	131	24.8
175.vpr	2	111	29.3	2	111	29.3
176.gcc	2	61.0	41.9	2	61.0	41.9
181.mcf	2	73.3	57.0	2	73.3	57.0
186.crafty	2	75.9	30.6	2	75.9	30.6
197.parser	2	159	26.3	2	159	26.3
252.eon	2	65.5	46.0	2	65.5	46.0
253.perlbnk	2	124	33.6	2	124	33.6
254.gap	2	94.4	27.0	2	94.4	27.0
255.vortex	2	81.8	53.9	2	81.8	53.9
256.bzip2	2	102	34.2	2	102	34.2
300.twolf	2	185	37.7	2	185	37.7

Hardware

CPU: Intel Itanium 2 (1.6GHz/6MB, 400MHz FSB)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip
CPU(s) orderable: 1,2
Parallel: no
Primary Cache: 16KBI + 16KBD on chip, per core
Secondary Cache: 256KB (I+D) on chip, per core
L3 Cache: 6.0MB (I+D) on chip, per core
Other Cache: N/A
Memory: 24GB (12x2GB DIMMs)
Disk Subsystem: 1x146GB 15K SCSI
Other Hardware: N/A

Software

Operating System: HPUX11i-TCOE B.11.23.0409
Compiler: HP C/ANSI C Compiler C.06.00
HP aC++ Compiler C.06.00
File System: vxfs
System State: Multi-user

Notes/Tuning Information

Portability Flags

```
176.gcc : -DHOST_WORDS_BIG_ENDIAN
186.crafty : -DHP
252.eon : -DFMAX_IS_DOUBLE
253.perlbnk : -DSPEC_CPU2000_HP
254.gap : -DSPEC_CPU2000_HP -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO
        -DSYS_HAS_TIME_PROTO -DSYS_HAS_CALLOC_PROTO
```

Base Flags

```
all : +Oprofile=collect:all/+Oprofile=use
C : +Ofaster -exec +Otype_safety=ansi
C++ : +Ofaster +Otype_safety=ansi
```

Peak Flags

same as base (basepeak=true set globally)

Kernel Tunables:

```
dbc_max_pct=20
dbc_min_pct=20
maxdsiz=3221225472
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP Integrity rx2620-2 (1.6GHz/6MB Itanium 2)

SPECint_rate2000 = 35.5
SPECint_rate_base2000 = 35.5

SPEC license #: 3 | Tested by: HP Richardson | Test date: Dec-2004 | Hardware Avail: Dec-2004 | Software Avail: Jan-2005

Notes/Tuning Information (Continued)

```
maxssiz=401604608
maxdsiz_64bit=4396972761584
maxssiz_64bit=1073741824
vps_pagesize=4096
vps_ceiling=16384
```

Notes:

The system under test had the HP-UX 11i v2 (version 11.23.0409, September, 2004) Technical Computing Operating Environment and AR1204 compilers installed, along with the following patches:

```
PHSS_31849 linker + fdp cumulative patch
PHSS_31850 assembler patch
PHSS_31851 Integrity Unwind Library
PHSS_31852 aC++ Runtime (IA: A.05.60, PA A.03.60)
PHSS_31853 Math Library Cumulative Patch
PHSS_31854 milli cumulative patch
```

EFI command "cpuconfig" used prior to booting to deconfigure other processors if necessary