



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices  
TYAN S2865 K8E Tomcat, AMD Opteron (TM) 150

SPECfp2000 = 1955  
SPECfp\_base2000 = 1817

SPEC license #: 49 Tested by: AMD, Austin, TX Test date: Jul-2005 Hardware Avail: Aug-2005 Software Avail: Aug-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	59.9	2673	55.4	2885	
171.swim	3100	149	2083	146	2123	
172.mgrid	1800	114	1585	105	1718	
173.applu	2100	104	2014	96.9	2167	
177.mesa	1400	74.7	1873	70.5	1985	
178.galgel	2900	99.4	2919	91.0	3188	
179.art	2600	102	2560	74.7	3481	
183.earth	1300	80.0	1626	72.9	1783	
187.facerec	1900	85.6	2218	81.3	2337	
188.amp	2200	156	1413	144	1532	
189.lucas	2000	107	1877	107	1877	
191.fma3d	2100	137	1532	136	1545	
200.sixtrack	1100	142	776	134	818	
301.apsi	2600	172	1509	166	1569	

**Hardware**

CPU: AMD Opteron (TM) 150 (939-pin)  
CPU MHz: 2400  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 1  
Parallel: No  
Primary Cache: 64KBI + 64KBD on chip  
Secondary Cache: 1024KB (I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 4x512 MB, DDR400 CL2.0  
Disk Subsystem: IDE, Western Digital WD2000JB, 7200 rpm  
Other Hardware: None

**Software**

Operating System: SuSE Linux Enterprise Server 9 (SP2) for AMD64  
Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.1  
File System: Linux/ext3  
System State: Multi-user, run level 3

## Notes/Tuning Information

Tested by AMD

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML means -L/opt/acml2.5.1/pathscale64/lib -lacml,
           which causes linking with AMD Core Math Library V2.5.1
```

Baseline optimization

```
C programs: -Ofast -WOPT:mem_opnds=on +FDO
Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on +FDO
Portability Flags:
178.galgel: -fixedform
```

Peak Tuning:

```
168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
             -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3
             -IPA:linear=on:plimit=50000:callee_limit=5000
             -INLINE:aggressive=on
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Advanced Micro Devices  
TYAN S2865 K8E Tomcat, AMD Opteron (TM) 150

SPECfp2000 = 1955  
SPECfp\_base2000 = 1817

SPEC license #: 49 | Tested by: AMD, Austin, TX | Test date: Jul-2005 | Hardware Avail: Aug-2005 | Software Avail: Aug-2005

## Notes/Tuning Information (Continued)

```

171.swim:      -Ofast -LNO:fusion=2 -m3dnow
172.mgrid:    -O3 -LNO:fusion=2:blocking=off
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:ro=3
              -CG:gcm=off:cflow=off -m3dnow
173.applu:    -Ofast -CG:local_fwd_sched=on
              -LNO:fusion=2:fission=2:full_unroll_size=10000:prefetch=3
              -OPT:ro=3 -TENV:X=3
177.mesa:     -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +FDO
178.galgel:   -Ofast -OPT:fast_complex=on +ACML
179.art:      -O3 -OPT:ro=2:div_split=on:alias=typed -fno-math-errno -m32
183.earthquake: -Ofast -CG:load_exe=2 -OPT:treeheight=on -WOPT:mem_opnds=on
              -m32 +FDO
187.facerec:  -Ofast -OPT:IEEE_NaN_Inf=off:ro=3 -LNO:fusion=2
              -IPA:plimit=1500 +FDO
188.ammp:     -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
              -fno-math-errno -TENV:X=4 +FDO
189.lucas:    basepeak = true
191.fma3d:    -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
              -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack:= -O3 -OPT:Ofast:Olimit=6000 -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:     -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0
The tested system can be assembled using a standard ATX footprint, an Antec True 550
Watt EPS12V power supply, and a PCI or PCIe graphics card.
All memory slots were populated with Corsair CMX512-3200XL.
Memory timings manually set in BIOS: CAS=2, TRCD=2, TRAS=5, TRP=2
BIOS version 1.01

```