



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 236 (2.8 GHz Xeon, 2MB L2 Cache)

SPECfp_rate2000 = 29.5

SPECfp_rate_base2000 = 28.8

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jul-2005 | Hardware Avail: Sep-2005 | Software Avail: Oct-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	79.8	46.5	2	79.8	46.5
171.swim	2	272	26.5	2	272	26.5
172.mgrid	2	186	22.5	2	186	22.5
173.applu	2	220	22.2	2	213	22.9
177.mesa	2	114	28.4	2	114	28.5
178.galgel	2	111	60.6	2	111	60.6
179.art	2	92.2	65.4	2	92.2	65.4
183.quake	2	111	27.3	2	81.9	36.8
187.facerec	2	133	33.1	2	133	33.1
188.amp	2	216	23.7	2	216	23.7
189.lucas	2	181	25.7	2	181	25.7
191.fma3d	2	210	23.2	2	210	23.2
200.sixtrack	2	196	13.0	2	196	13.0
301.apsi	2	255	23.7	2	255	23.7

Hardware

CPU: Intel Xeon 2.8 (800 MHz system bus)
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
 Secondary Cache: 2048KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 x 2048 MB ECC PC2-3200 Single Rank
 Disk Subsystem: 73GB SCSI 10K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
 Compiler: Intel C/C++ Compiler 9.0 (20050624Z) for 32-bit applications
 Intel Fortran Compiler 9.0 (20050624Z) for 32-bit applications
 Microsoft Visual Studio .NET 13.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.30
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
 +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY

178.galgel: -FI /F3200000
 191.fma3d: srcalt=windowsdp

BASE TUNING

C/F77/F90: -fast -Qansi_alias +FDO

PEAK TUNING

168.wupwise: basepeak=yes
 171.swim: -fast -f77rtl +FDO
 172.mgrid: basepeak=yes
 173.applu: -fast -Qscalar_rep- -Qauto -f77rtl +FDO
 177.mesa: -fast +FDO
 178.galgel: basepeak=yes
 179.art: basepeak=yes
 183.quake: -fast -Oa -Qrcd +FDO shlw32M.lib



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 236 (2.8 GHz Xeon, 2MB L2 Cache)

SPECfp_rate2000 = 29.5

SPECfp_rate_base2000 = 28.8

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jul-2005 | Hardware Avail: Sep-2005 | Software Avail: Oct-2004

Notes/Tuning Information (Continued)

```
187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO
188.amp: basepeak=yes
189.lucas: -fast
191.fma3d: basepeak=yes
200.sixtrack: -Qipo +FDO
301.apsi: basepeak=yes
```