



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R710 (Dual-Core Intel Xeon 2.8 GHz, 2x2MB L2, 800MHz system bus)

SPECfp_rate2000 = 29.4

SPECfp_rate_base2000 = 29.3

SPEC license #: 97 Tested by: Acer Incorporated Test date: Dec-2005 Hardware Avail: Dec-2005 Software Avail: Jul-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	80.6	46.0	2	80.7	46.0
171.swim	2	274	26.2	2	273	26.3
172.mgrid	2	177	23.6	2	176	23.7
173.applu	2	220	22.2	2	220	22.2
177.mesa	2	114	28.4	2	114	28.4
178.galgel	2	111	60.9	2	111	60.8
179.art	2	85.8	70.3	2	85.8	70.3
183.quake	2	81.7	36.9	2	81.5	37.0
187.facerec	2	130	33.9	2	130	33.9
188.amp	2	235	21.7	2	229	22.3
189.lucas	2	185	25.1	2	185	25.1
191.fma3d	2	215	22.7	2	215	22.7
200.sixtrack	2	199	12.8	2	201	12.7
301.apsi	2	263	22.9	2	266	22.7

Hardware

CPU: Dual-Core Intel Xeon (2.8 GHz, 2x2MB L2, 800MHz system bus)
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip(Hyper-Threading Technology Disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip, per core
Secondary Cache: 2048KB(I+D) on chip, per core
L3 Cache: N/A
Other Cache: N/A
Memory: 6 x 1024MB ECC DDR2-400 SDRAM
Disk Subsystem: 1 x 146GB 10000RPM U320 SCSI HDD
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler: Intel C++ 9.0 Build 20050430Z for IA32 and Fortran Compiler 9.0 Build 20050722Z for IA32
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)
shlw32M.lib is SmartHeap Library Version 7.4 from http://www.microquill.com/
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for all Fortran Programs : -fast -Qansi_alias +FDO
Base tuning for all C Programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
192.fma3d: Approved windowsdp src.alt used
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast -Qansi_alias +FDO
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: -fast -Qansi_alias +FDO
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd -Qprof_gen shlw32M.lib
187.facerec: basepeak=yes
188.amp: -Oa -QxP
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R710 (Dual-Core Intel Xeon 2.8 GHz, 2x2MB L2, 800MHz system bus)

SPECfp_rate2000 = 29.4

SPECfp_rate_base2000 = 29.3

SPEC license #: 97 | Tested by: Acer Incorporated | Test date: Dec-2005 | Hardware Avail: Dec-2005 | Software Avail: Jul-2005

Notes/Tuning Information (Continued)

189.lucas: -fast -Qprefetch- +FDO

191.fma3d: basepeak=yes

200.sixtrack: -Qipo -QxP +FDO

301.apsi: -fast +FDO

Enable hardware prefetching and adjacent cache line prefetch BIOS setting

Product description located at <http://www.acer.com>