



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1950 (Intel Xeon processor 5110, 1.60GHz)

SPECfp_rate2000 = 60.9

SPECfp_rate_base2000 = 60.9

SPEC license #: 55 Tested by: Dell, Round Rock, TX Test date: Jun-2006 Hardware Avail: Jul-2006 Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	84.7	87.6	4	84.7	87.6
171.swim	4	298	48.2	4	298	48.2
172.mgrid	4	210	39.8	4	210	39.8
173.applu	4	211	46.2	4	211	46.2
177.mesa	4	83.7	77.6	4	83.7	77.6
178.galgel	4	90.7	148	4	90.7	148
179.art	4	63.6	190	4	63.6	190
183.quake	4	131	46.0	4	131	46.0
187.facerec	4	109	80.6	4	109	80.6
188.amp	4	200	51.1	4	200	51.1
189.lucas	4	178	52.2	4	178	52.2
191.fma3d	4	213	45.8	4	213	45.8
200.sixtrack	4	181	28.1	4	181	28.1
301.apsi	4	267	45.2	4	267	45.2

Hardware

CPU: Intel Xeon processor 5110 (1066MHz system bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8 x 1GB 667MHz ECC CL5 DDR2 FB-DIMM
Disk Subsystem: 1 x 80GB SATA 7200 RPM
Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux 4 Advanced Server Update 3 EM64T
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T Builds 20060120 and 20051201
File System: ext3
System State: Runlevel 3

Notes/Tuning Information

GENERAL

ONESTEP=yes for all benchmarks

+FDO implies feedback-directed optimization PASS1: -prof_gen PASS2: -prof_use

PORTABILITY FLAGS

-DSPEC_CPU2000_LP64 applied to all benchmarks

178.galgel: -FI for fixed-format Fortran

BASE TUNING

Baseline optimizations for C and Fortran: -fast +FDO

PEAK TUNING

basepeak=yes set for all benchmarks

BIOS SETTINGS

Snoop Filter enabled in BIOS