



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL360 G5 (3.0GHz, Intel Xeon processor 5160)

SPECfp_rate2000 = 46.8
SPECfp_rate_base2000 = 46.1

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jun-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	54.7	67.9	2	54.7	67.9
171.swim	2	206	34.9	2	206	34.9
172.mgrid	2	134	31.2	2	134	31.3
173.applu	2	151	32.2	2	151	32.2
177.mesa	2	50.5	64.4	2	51.3	63.3
178.galgel	2	54.8	123	2	54.8	123
179.art	2	52.1	116	2	52.1	116
183.quake	2	64.8	46.6	2	64.8	46.5
187.facerec	2	83.3	52.9	2	83.4	52.9
188.amp	2	147	34.8	2	117	43.7
189.lucas	2	144	32.3	2	142	32.6
191.fma3d	2	141	34.5	2	141	34.5
200.sixtrack	2	93.5	27.3	2	93.5	27.3
301.apsi	2	176	34.2	2	176	34.2

Hardware

CPU: Intel Xeon processor 5160 (3.0GHz, 4MB L2 shared, 1333MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KBI + 32KBD (on chip) per core
Secondary Cache: 4096KB(I+D) (on chip) shared
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1024MB PC2-5300F
Disk Subsystem: 1x36GB 10K SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Intel Fortran Compiler for 32-bit applications, (Version 9.1 Build 20060323Z)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0

File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
Portability flags:
 178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -fast -Qansi_alias +FDO
171.swim: -fast +FDO ONESTEP=yes
172.mgrid: -fast -Qansi_alias +FDO
173.applu: basepeak=1
177.mesa: -fast +FDO ONESTEP=yes
178.galgel: basepeak=1
179.art: basepeak=1
183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlw32M.lib
187.facerec: -fast -Qunroll1 -Qscalar_rep- +FDO ONESTEP=yes
188.amp: -fast -Qansi_alias +FDO
189.lucas: -fast
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL360 G5 (3.0GHz, Intel Xeon processor 5160)

SPECfp_rate2000 = 46.8

SPECfp_rate_base2000 = 46.1

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jun-2006 | Hardware Avail: Jun-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
191.fma3d:    basepeak=1
200.sixtrack: -fast                +FDO
301.apsi:     basepeak=1
BIOS Configuration Notes
Power Regulator set to Static High Performance Mode
```