



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP Integrity Superdome (1.6GHz/24MB Dual Core Itanium 2)

SPECint_rate2000 = 2367

SPECint_rate_base2000 = 2367

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Jul-2006 Hardware Avail: Sep-2006 Software Avail: Sep-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	128	132	1570	128	132	1570
175.vpr	128	102	2044	128	102	2044
176.gcc	128	61.8	2644	128	61.8	2644
181.mcf	128	54.0	4952	128	54.0	4952
186.crafty	128	72.2	2057	128	72.2	2057
197.parser	128	161	1659	128	161	1659
252.eon	128	59.6	3236	128	59.6	3236
253.perlbnk	128	120	2232	128	120	2232
254.gap	128	112	1462	128	112	1462
255.vortex	128	73.9	3816	128	73.9	3816
256.bzip2	128	102	2181	128	102	2181
300.twolf	128	181	2456	128	181	2456

Hardware

CPU: Dual Core Intel(R) Itanium(R) 2 (1.6GHz/24MB, 533MHz FSB)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 128 cores, 64 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 2-128
Parallel: no
Primary Cache: 16KBI + 16KBD on chip, per core
Secondary Cache: 1024KBI + 256KBD on chip, per core
L3 Cache: 12.0MB (I+D) on chip, per core
Other Cache: N/A
Memory: 512GB (512x1GB DIMMs)
Disk Subsystem: 8x36GB 15K SCSI (striped)
Other Hardware: N/A

Software

Operating System: HPUX11i-TCOE B.11.23.0606
Compiler: HP C/ANSI C Compiler C.11.23.12
HP aC++ Compiler C.11.23.12
File System: vxfs
System State: Multi-user

Notes/Tuning Information

Portability Flags

```
176.gcc : -DHOST_WORDS_BIG_ENDIAN
186.crafty : -DHP
253.perlbnk : -DSPEC_CPU2000_HP
254.gap : -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
```

Base Flags

```
all : +Oprofile=collect:all/+Oprofile=use
C : +Ofaster +Otype_safety=ansi
C++ : +Ofaster +Otype_safety=ansi
```

Peak Flags:

same as base (basepeak=true set globally)

Kernel Tunables:

```
dbc_max_pct=10
dbc_min_pct=10
maxdsiz=3221225472
maxssiz=401604608
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
HP Integrity Superdome (1.6GHz/24MB Dual Core Itanium 2)

SPECint_rate2000 = 2367
SPECint_rate_base2000 = 2367

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Jul-2006 | Hardware Avail: Sep-2006 | Software Avail: Sep-2006

Notes/Tuning Information (Continued)

maxdsiz_64bit=4396972765184
maxssiz_64bit=1073741824
vps_chatr_ceiling=4194304

Notes:

The system had the June 2006 HP-UX 11i v2 Technical Computing Operating Environment (TCOE) installed, along with the AR0606 compilers, and the following patches:

PHSS_34858 linker + fdp cumulative patch
PHSS_34853 Math Library Cumulative Patch
PHSS_34854 Integrity Unwind Library
PHSS_34855 HP C Compiler (A.06.12)
PHSS_34856 aC++ Compiler (A.06.12)
PHSS_34857 u2comp/be/plugin library patch
PHSS_34395 FORTRAN I/O Library [libIO77]
PHSS_34397 FORTRAN Intrinsics [libF90 B.11.23.16]
PHSS_34399 HP FORTRAN90
PHSS_34441 aC++ Runtime (IA: A.06.10)
PHKL_34020 Perfmon enhancements and Itanium-2 9000 HWE

System was configured as a single partition with 16 cells and 4 processors (8 cores) per cell. Memory was configured as 50% local and 50% interleaved.

HP-UX mpsched utility was used to assign processes to cells.

filesystem used for spec runs mounted tmplog