



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System p5 505 (2100 MHz, 1 CPU)

SPECint2000 = 1704  
SPECint\_base2000 = 1617

SPEC license #: 11 | Tested by: IBM Austin | Test date: Jun-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	147	950	144	970	
175.vpr	1400	98.7	1418	98.7	1418	
176.gcc	1100	64.4	1709	64.4	1709	
181.mcf	1800	51.6	3486	50.0	3597	
186.crafty	1000	76.7	1305	62.8	1593	
197.parser	1800	124	1457	122	1480	
252.eon	1300	74.1	1755	72.0	1805	
253.perlbnk	1800	169	1066	153	1173	
254.gap	1100	75.3	1460	73.9	1488	
255.vortex	1900	71.0	2675	62.5	3039	
256.bzip2	1500	95.8	1565	91.2	1645	
300.twolf	3000	164	1830	157	1910	

### Hardware

CPU: POWER5+  
 CPU MHz: 2100  
 FPU: Integrated  
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (SMT off)  
 CPU(s) orderable: 2 core  
 Parallel: No  
 Primary Cache: 64 KB I + 32 KB D on chip per core  
 Secondary Cache: 1920 KB I+D on chip per chip  
 L3 Cache: 36 MB I+D off chip per chip, 1 chip per SUT  
 Other Cache: None  
 Memory: 16 GB (8x2 GB)  
 Disk Subsystem: 1x73GB SCSI, 15K RPM  
 Other Hardware: None

### Software

Operating System: AIX 5L V5.3  
 Compiler: XL C/C++ Enterprise Edition Version 8.0 for AIX  
 XL Fortran Enterprise Edition Version 10.1 for AIX  
 Other Software: ESSL 4.2.0.4  
 File System: AIX/JFS2  
 System State: Multi-user

## Notes/Tuning Information

### Portability Flags:

```
176.gcc: -ma -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DAIX
253.perlbnk: -DSPEC_CPU2000_AIX
254.gap: -DSYS_IS_BSD -DSYS_STRING_H
          -DSYS_HAS_MALLOC_PROTO -DSYS_HAS_CALLOC_PROTO
300.twolf: -DHAVE_SIGNED_CHAR
```

### Base Optimization Flags:

```
C: -qpdf1/pdf2
   -O5 -blpdata -D_ILS_MACROS
C++: -qpdf1/pdf2
      -O4 -qalign=natural
```

### Peak Optimization Flags

```
164.gzip: -qpdf1/pdf2
          -O4 -qfdpr -blpdata
          fdpr -q -O3
175.vpr: basepeak=1
176.gcc: basepeak=1
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System p5 505 (2100 MHz, 1 CPU)

SPECint2000 = 1704  
SPECint\_base2000 = 1617

SPEC license #: 11 | Tested by: IBM Austin | Test date: Jun-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

## Notes/Tuning Information (Continued)

```

181.mcf:      -qpdf1/pdf2
              -O5 -blpdata -qalign=natural -qhot=arraypad -qfdpr -Q -qmaxmem=-1
              fdpr -q -O3
186.crafty:   -qpdf1/pdf2
              -O4 -qalign=natural -q64 -lhm -blpdata
197.parser:   -qpdf1/pdf2
              -O4 -qfdpr -D_ILS_MACROS -blpdata
              fdpr -q -O3
252.eon:      -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural
253.perlbnk:  -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata -lhm
254.gap:      -qpdf1/pdf2
              -O4 -qarch=pwr4 -qtune=pwr4 -qalign=natural -blpdata
255.vortex:   -qpdf1/pdf2
              -O4 -qfdpr -lhm -blpdata
              fdpr -q -O3
256.bzip2:    -qpdf1/pdf2
              -O5 -qfdpr -blpdata
              fdpr -q -O3
300.twolf:    -O5 -qfdpr -blpdata
              fdpr -q -O3

```

The installed OS level is AIX 5L for POWER Version 5.3 with the 5300-05 Recommended Technology Level. The installed C/C++ compiler is XL C/C++ Enterprise Edition Version 8.0 for AIX. The installed Fortran copiler is XL Fortran Enterprise Edition Version 10.1 with the May 2006 AIX PTF.

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

SUT: Acronym for "System Under Test"

PTF: IBM identifier for "Program Fix Level"

```

Extended C:   IBM XL C for AIX invoked as cc
ANSI C89:     IBM XL C for AIX invoked as xlc
C++:         IBM XL C for AIX invoked as xlc

```

ulimits set to unlimited.

Large page mode and memory affinity were set as follows:

```

vmo -r -o lpgg_regions=128 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
bosboot -aD
shutdown -rF
export MEMORY_AFFINITY=MCM

```

The following config-file entry was used to assign each benchmark process to a core:

```
submit = bindprocessor \${$} \${SPECUSERNUM}; $command
```

The "bindprocessor" AIX command binds a process to a CPU core.

One core was deconfigured and SMT disabled using the AIX commands

```

smtctl -m off -w boot
bosboot -aD
shutdown -rF
drmgr -r -c cpu

```

This result was measured on an IBM System p5 510. IBM System p5 505 and IBM System



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System p5 505 (2100 MHz, 1 CPU)

SPECint2000 = 1704

SPECint\_base2000 = 1617

SPEC license #: 11 | Tested by: IBM Austin | Test date: Jun-2006 | Hardware Avail: Aug-2006 | Software Avail: Aug-2006

## Notes/Tuning Information (Continued)

p5 510 (2-core version) are electronically equivalent.