



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**IBM Corporation**  
IBM System X 3755 (AMD Opteron (TM) 8218)

SPECfp\_rate2000 = 162  
SPECfp\_rate\_base2000 = 151

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	68.9	216	8	63.1	235
171.swim	8	186	155	8	184	156
172.mgrid	8	129	130	8	125	134
173.applu	8	123	159	8	113	173
177.mesa	8	69.3	187	8	65.1	199
178.galgel	8	105	256	8	105	256
179.art	8	138	174	8	96.0	251
183.quake	8	119	101	8	107	113
187.facerec	8	91.7	192	8	89.7	197
188.amp	8	154	133	8	148	138
189.lucas	8	129	144	8	117	158
191.fma3d	8	148	132	8	150	130
200.sixtrack	8	128	79.6	8	122	83.9
301.apsi	8	167	145	8	158	153

**Hardware**

CPU: AMD Opteron 8218  
 CPU MHz: 2600  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip  
 CPU(s) orderable: 1,2,3,4  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB (I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 16x2GB, PC2-5300  
 Disk Subsystem: SAS, 73GB 15K RPM  
 Other Hardware: None

**Software**

Operating System: SuSE Linux 9.0 SP3 SLES 64 bit Kernel 2.6.5-7.244-smp  
 Compiler: PathScale EKO Compiler Suite, Release 2.4  
 PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
 File System: Linux/reiserfs  
 System State: Multi-user, run level 3

## Notes/Tuning Information

+FDO: PASS1= -fb\_create fbdata PASS2= -fb\_opt fbdata

### Baseline optimization

C programs: -Ofast -WOPT:mem\_opnds=on +FDO  
 Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast\_complex=on +FDO  
 Portability Flags:  
 178.galgel: -fixedform

### Peak Tuning:

168.wupwise: -Ofast -IPA:linear=on -LNO:prefetch Ahead=5:prefetch=3  
 -OPT:unroll\_times\_max=8:unroll\_size=128:IEEE\_NaN\_Inf=off:ro=3  
 171.swim: -Ofast -CG:local\_fwd\_sched=on -LNO:fusion=2 -m3dnow  
 172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE\_arith=3:unroll\_size=200  
 -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2  
 -WOPT:mem\_opnds=on:aggstr=0  
 173.applu: -Ofast -CG:local\_fwd\_sched=on -OPT:ro=3 -TENV:X=3  
 -LNO:fusion=2:fission=2:full\_unroll\_size=10000 +FDO



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System X 3755 (AMD Opteron (TM) 8218)

SPECfp\_rate2000 = 162  
SPECfp\_rate\_base2000 = 151

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2006 | Hardware Avail: Aug-2006 | Software Avail: Mar-2006

## Notes/Tuning Information (Continued)

```

177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on -WOPT:mem_opnds=on +FDO
178.galgel:    -Ofast -OPT:fast_complex=on +FDO
179.art:       -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.quake:    -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec:  -Ofast -IPA:plimit=1500 -LNO:fusion=2
              -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 +FDO
188.amp:      -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
              -GRA:optimize_boundary=on -fno-math-errno -TENV:X=4 +FDO
189.lucas:    -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d:    -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
              -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:early_intrinsics=on
              -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:     -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```