



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Rackable Systems
C1000-L03-25W30 (Intel Xeon 5160)

SPECint_rate2000 = 113
SPECint_rate_base2000 = 113

SPEC license #: 64 Tested by: Rackable Systems Test date: Jul-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	82.8	78.5	4	82.8	78.5
175.vpr	4	79.8	81.4	4	79.8	81.4
176.gcc	4	42.8	119	4	42.8	119
181.mcf	4	106	78.7	4	106	78.7
186.crafty	4	28.9	161	4	28.9	161
197.parser	4	98.9	84.4	4	98.9	84.4
252.eon	4	32.4	186	4	32.4	186
253.perlbnk	4	56.5	148	4	56.5	148
254.gap	4	57.3	89.0	4	57.3	89.0
255.vortex	4	50.9	173	4	50.9	173
256.bzip2	4	82.4	84.4	4	82.4	84.4
300.twolf	4	97.4	143	4	97.4	143

Hardware

CPU: Intel(R) Xeon(R) CPU 5160 @ 3.0GHz
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chip(s)
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4096KB(I+D) on chip, per chip, shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4 x 1024MB ECC FB-DIMM DDR2-667MHz
 Disk Subsystem: 1 x 250GB SATA HDD
 Other Hardware: --

Software

Operating System: Red Hat Enterprise Linux 4 ES Update 3 EM64T
 Compiler: Intel C++ 9.1.038 and Fortran Compiler 9.1.032 for EM64T
 File System: ext3
 System State: Runlevel 3

Notes/Tuning Information

-DSPEC_CPU2000_LP64 applied to all benchmarks
 186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL -DSPEC_CPU2000_GLIBC22
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
 -DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
 178.galgel: -FI for fixed-format Fortran
 Portability for integer benchmarks
 Optimization flags
 ONESTEP=yes for all benchmarks
 +FDO implies feedback-directed optimization PASS1: -prof_gen PAS2: -prof_use
 Baseline optimizations for C: -fast -auto_ilp32 +FDO
 Baseline optimizations for C++: -fast -auto_ilp32 +FDO
 basepeak=yes set for all benchmarks
 Portability for fp benchmarks
 Optimization flags
 ONESTEP=yes for all benchmarks
 +FDO implies feedback-directed optimization PASS1: -prof_gen PAS2: -prof_use
 Baseline optimizations for C and Fortran: -fast +FDO
 basepeak=yes set for all benchmarks



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Rackable Systems
C1000-L03-25W30 (Intel Xeon 5160)

SPECint_rate2000 = 113

SPECint_rate_base2000 = 113

SPEC license #: 64 Tested by: Rackable Systems Test date: Jul-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

Notes/Tuning Information (Continued)

Taskset utility used to bind process to CPU(s)