



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Rackable Systems
C1000-L03-25W26 (Intel Xeon 5150)

SPECfp_rate2000 = 76.2
SPECfp_rate_base2000 = 76.2

SPEC license #: 64 Tested by: Rackable Systems Test date: Jul-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

				Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
250	200	150	100	168.wupwise	4	68.4	109	4	68.4	109
				171.swim	4	268	53.7	4	268	53.7
				172.mgrid	4	175	47.7	4	175	47.7
				173.applu	4	189	51.7	4	189	51.7
				177.mesa	4	53.3	122	4	53.3	122
				178.galgel	4	65.1	207	4	65.1	207
				179.art	4	55.7	217	4	55.7	217
				183.equake	4	131	46.1	4	131	46.1
				187.facerec	4	90.2	97.7	4	90.2	97.7
				188.amp	4	130	78.4	4	130	78.4
				189.lucas	4	182	51.1	4	182	51.1
				191.fma3d	4	167	58.3	4	167	58.3
				200.sixtrack	4	110	46.4	4	110	46.4
				301.apsi	4	205	58.7	4	205	58.7

Hardware

CPU: Intel(R) Xeon(R) CPU 5150 @ 2.66GHz
CPU MHz: 2660
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2 chip(s)
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 1024MB ECC FB-DIMM DDR2-667MHz
Disk Subsystem: 1 x 250GB SATA HDD
Other Hardware: --

Software

Operating System: Red Hat Enterprise Linux 4 ES Update 2 EM64T
Compiler: Intel C++ 9.1.038 and Fortran Compiler 9.1.032 for EM64T
File System: ext3
System State: Runlevel 3

Notes/Tuning Information

-DSPEC_CPU2000_LP64 applied to all benchmarks
186.crafty: -DLINUX_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL -DSPEC_CPU2000_GLIBC22
254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
-DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO
178.galgel: -FI for fixed-format Fortran
Portability for integer benchmarks
Optimization flags
ONESTEP=yes for all benchmarks
+FDO implies feedback-directed optimization PAS1: -prof_gen PAS2: -prof_use
Baseline optimizations for C: -fast -auto_ilp32 +FDO
Baseline optimizations for C++: -fast -auto_ilp32 +FDO
basepeak=yes set for all benchmarks
Portability for fp benchmarks
Optimization flags
ONESTEP=yes for all benchmarks



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Rackable Systems
C1000-L03-25W26 (Intel Xeon 5150)

SPECfp_rate2000 = 76.2

SPECfp_rate_base2000 = 76.2

SPEC license #: 64 Tested by: Rackable Systems Test date: Jul-2006 Hardware Avail: Aug-2006 Software Avail: Jun-2006

Notes/Tuning Information (Continued)

+FDO implies feedback-directed optimization PASS1: -prof_gen PAS2: -prof_use
Baseline optimizations for C and Fortran: -fast +FDO
basepeak=yes set for all benchmarks
Taskset utility used to bind process to CPU(s)