



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY TX600 S3, Intel Xeon processor 7120M, 3.0 GHz

SPECint\_rate2000 = 64.3

SPECint\_rate\_base2000 = 64.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Sep-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	8	219	59.2	8	219	59.2
175.vpr	8	332	39.2	8	332	39.2
176.gcc	8	119	85.5	8	119	85.5
181.mcf	8	411	40.6	8	411	40.6
186.crafty	8	181	51.2	8	181	51.2
197.parser	8	264	63.3	8	264	63.3
252.eon	8	118	102	8	118	102
253.perlbnk	8	221	75.7	8	221	75.7
254.gap	8	144	70.9	8	144	70.9
255.vortex	8	176	100	8	176	100
256.bzip2	8	266	52.3	8	266	52.3
300.twolf	8	417	66.8	8	417	66.8

### Hardware

CPU: Intel Xeon processor 7120M (3.0 GHz, 2x1MB L2, 4MB L3, 800 MHz system bus)  
CPU MHz: 3000  
FPU: Integrated  
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1,2,4 chips  
Parallel: No  
Primary Cache: 12k micro-ops(I) + 16KB(D) on chip, per core  
Secondary Cache: 1024KB(I+D) on chip, per core  
L3 Cache: 4MB on chip, per chip  
Other Cache: N/A  
Memory: 16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3)  
Disk Subsystem: Fujitsu MAS3367NC (SCSI, 15krpm, 36GB)  
Other Hardware: none

### Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)  
Compiler: Intel C++ Compiler 9.1  
Build 20060323Z (for 32-bit applications),  
Microsoft Visual Studio .Net 2003  
7.1.3088 (for libraries),  
SmartHeap Library Version 8.0  
from <http://www.microquill.com>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### Portability flags

176.gcc: -Dalloca=\_alloca /F10000000  
186.crafty: -DNT\_i386  
253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### Base tuning flags

for C programs: -fast +FDO shlw32m.lib  
for C++ programs: -fast -Qcxx\_features +FDO shlw32m.lib

### Peak tuning flags

same as baseline (basepeak=true set globally)

The system bus runs at 800 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY TX600 S3, Intel Xeon processor 7120M, 3.0 GHz

SPECint\_rate2000 = 64.3

SPECint\_rate\_base2000 = 64.3

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Sep-2006 | Hardware Avail: Aug-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>