



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL320 G5 (2.66 GHz, Intel Xeon processor 3070)

SPECfp2000 = **3044**
SPECfp_base2000 = **2763**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Sep-2006 Hardware Avail: Sep-2006 Software Avail: May-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	37.5	4263	37.5	4263
171.swim	3100	109	2851	102	3034
172.mgrid	1800	100	1797	76.4	2356
173.applu	2100	99.5	2111	73.5	2855
177.mesa	1400	49.5	2828	45.8	3055
178.galgel	2900	46.6	6221	46.6	6221
179.art	2600	24.6	10590	24.6	10590
183.quake	1300	50.3	2587	40.1	3242
187.facerec	1900	60.5	3142	42.6	4463
188.amp	2200	113	1946	113	1946
189.lucas	2000	73.7	2715	72.5	2760
191.fma3d	2100	101	2081	101	2081
200.sixtrack	1100	108	1019	108	1019
301.apsi	2600	135	1933	128	2031

Hardware

CPU: Intel Xeon processor 3070 (2.66 GHz, 4 MB L2 shared, 1066 MHz bus)
CPU MHz: 2660
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8 GB (4x2 GB PC2-5300E)
Disk Subsystem: 1x250 GB SATA
Other Hardware:

Software

Operating System: RedHat Enterprise Linux 4.0 Advanced Server for AMD64/EM64T, Update 3 Kernel 2.6.9-34.EL
Compiler: Intel C++ Compiler for EM64T-based applications, (Version 9.1 Build 20060323)
Intel Fortran Compiler for EM64T-based applications, (Version 9.1 Build 20060323)
PathScale EKOPATH(TM) Compiler Suite, Release 2.4
File System: ext2
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -prof_gen PASS2=-prof_use (Intel Compiler)
+FDO: PASS1= -fb_create fbdata PASS2=-fb_opt fbdata (PathScale Compiler)
ifort is the Intel Fortran compiler, icc is the Intel C++ compiler; and
pathf95 is PathScale Fortran compiler, pathcc is the PathScale C compiler.
Base tuning for C programs: icc -fast -auto_ilp32 +FDO
Base tuning for FORTRAN programs: ifort -fast +FDO
Portability:
-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI
Peak tuning:
168.wupwise: basepeak=1
171.swim: pathf95 -Ofast -LNO:fusion=2:simd=0 -WOPT:val=0 -march=em64t
172.mgrid: pathf95 -Ofast -CG:load_exe=0 -LNO:blocking=off:prefetch_ahead=5
-OPT:ro=3:unroll_size=256 -WOPT:mem_opnds=on -march=em64t
173.applu: pathf95 -O3 -ipa -CG:load_exe=0
-LNO:fission=1:fusion=2:blocking=off:full_unroll_size=9000
-OPT:IEEE_a=3:ro=3 -TENV:X=3 -march=em64t
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL320 G5 (2.66 GHz, Intel Xeon processor 3070)

SPECfp2000 = 3044
SPECfp_base2000 = 2763

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Sep-2006 | Hardware Avail: Sep-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
177.mesa: pathcc -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
          -GRA:optimize_boundary=on -march=em64t +FDO
178.galgel: basepeak=1
179.art: basepeak=1
183.quake: icc -fast +FDO ONESTEP=yes -rcd -auto-ilp32
187.facerec: pathf95 -Ofast -IPA:plimit=1500 -LNO:fusion=2
            -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 -march=em64t +FDO
188.ammmp: basepeak=1
189.lucas: ifort -fast ONESTEP=yes
191.fma3d: basepeak=1
200.sixtrack: basepeak=1
301.apsi: pathf95 -Ofast -CG:load_exe=0 -LNO:opt=0:prefetch=1 -march=em64t
```

BIOS Configuration Notes
Power Regulator set to Static High

Other Configuration Notes
Single processor kernel used