



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Hewlett-Packard Company**  
ProLiant BL25p G2 (AMD Opteron (TM) 2218)

SPECint\_rate2000 = **81.6**  
SPECint\_rate\_base2000 = **72.9**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Sep-2006 Hardware Avail: Nov-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	88.5	73.4	4	88.5	73.4
175.vpr	4	113	57.4	4	109	59.7
176.gcc	4	62.2	82.1	4	61.9	82.5
181.mcf	4	288	29.0	4	174	48.0
186.crafty	4	44.4	105	4	44.3	105
197.parser	4	150	55.8	4	119	70.3
252.eon	4	47.2	128	4	41.9	144
253.perlbnk	4	104	80.1	4	92.6	90.2
254.gap	4	67.8	75.3	4	67.3	75.9
255.vortex	4	75.2	117	4	70.9	124
256.bzip2	4	104	66.9	4	104	66.9
300.twolf	4	217	64.0	4	168	83.0

### Hardware

CPU: AMD Opteron (TM) 2218  
 CPU MHz: 2600  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Parallel: No  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 1 MB I+D on chip per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 16 GB (8x2 GB PC2-5300 CL5)  
 Disk Subsystem: 1x36.4 GB 10 K SAS  
 Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP 3  
 SuSE kernel 2.6.5-7.244-smp  
 Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
 File System: Linux/ext2  
 System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
Base tuning for C programs: -Ofast +FDO
Base tuning for C++ programs: -Ofast +FDO
Portability flags:
 186.crafty: -DLINUX_i386
 252.eon: -DHAS_ERRLIST -DSPEC_CPU2000_LP64
 253.perlbnk: -DSPEC_CPU2000_LINUX_I386 -DSPEC_CPU2000_NEED_BOOL
              -DSPEC_CPU2000_LP64
 254.gap: -DSYS_IS_USG -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO
           -DSYS_HAS_CALLOC_PROTO -DSPEC_CPU2000_LP64
 255.vortex: -DSPEC_CPU2000_LP64
Peak tuning:
 164.gzip: -O3 -ipa -WOPT:val=0 -OPT:unroll_size=0 +FDO
 175.vpr: -O3 -ipa -m32 +FDO
 176.gcc: -O3 -IPA:plimit=10000 -LNO:opt=0 -OPT:goto=off +FDO
 181.mcf: -O3 -ipa -IPA:field_reorder=on -m32 +FDO
 186.crafty: -Ofast -CG:local_fwd_sched=on -LNO:opt=0 -WOPT:val=0 +FDO
 197.parser: -O3 -ipa -m32 -IPA:ctype=on +FDO
 252.eon: -Ofast -CG:gcm=off:p2align_freq=1:prefetch=off -IPA:plimit=4000
           -OPT:treeheight=on -TENV:X=4:frame_pointer=off -fno-exceptions
```



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant BL25p G2 (AMD Opteron (TM) 2218)

SPECint\_rate2000 = 81.6  
SPECint\_rate\_base2000 = 72.9

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Sep-2006 | Hardware Avail: Nov-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

```
-LNO:fu=10:full_unroll_outer=on -GRA:optimize_boundary=on +FDO
253.perlbnk: -O2 -ipa -OPT:Ofast:transform_to_memlib=off
              -fno-math-errno -IPA:plimit=10000 +FDO
254.gap:      -Ofast -IPA:min_hotness=5 -OPT:alias=disjoint -CG:movnti=1 +FDO
255.vortex:   -Ofast -OPT:goto=off +FDO
256.bzip2:    basepeak=true
300.twolf:    -O2 -CG:gcm=off:p2align_freq=100000
              -OPT:Ofast:unroll_times_max=8:unroll_size=256:alias=disjoint
              -WOPT:mem_opnds=on -m32 +FDO
```

### BIOS Configuration Notes

Node Interleaving Disabled

### Other Configuration Notes

Taskset utility used to bind process to CPU(s)