




CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL25p G2 (AMD Opteron (TM) 2218)

SPECfp_rate2000 = 45.1
SPECfp_rate_base2000 = 41.9

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Sep-2006 Hardware Avail: Nov-2006 Software Avail: May-2006



Hardware

CPU: AMD Opteron (TM) 2218
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 GB (4x2 GB PC2-5300 CL5)
 Disk Subsystem: 1x36.4 GB 10 K SAS
 Other Hardware:

Software

Operating System: SuSE Linux Enterprise Server 9 (x86_64) SP 3
 SuSE kernel 2.6.5-7.244-smp
 Compiler: PathScale EKOPATH(TM) Compiler Suite, Release 2.4
 AMD Core Math Library 3.6.0
 File System: Linux/ext2
 System State: Multi-user run level 3

Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on +FDO
Portability flags:
  178.galgel: -fixedform
Peak tuning:
  168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
              -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3
              -IPA:linear=on:plimit=50000:callee_limit=5000 -INLINE:aggressive=on
  171.swim: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 -m3dnow
  172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_a=3:unroll_size=200
              -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2 -WOPT:mem_opnds=on:aggstr=0
  173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
              -LNO:fusion=2:fission=2:full_unroll_size=10000 +FDO
  177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
              -WOPT:mem_opnds=on +FDO
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL25p G2 (AMD Opteron (TM) 2218)

SPECfp_rate2000 = 45.1
SPECfp_rate_base2000 = 41.9

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Sep-2006 Hardware Avail: Nov-2006 Software Avail: May-2006

Notes/Tuning Information (Continued)

```

178.galgel: -Ofast -OPT:fast_complex-on RM_SOURCES=lapak.f90 +ACML +FDO
179.art: -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.equake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec: -Ofast -LNO:fusion=2 -OPT:fast_complex=on:IEEE_NaN_Inf=off:unroll_size=0 +FDO
188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
          -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
          -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000:early_intrinsics=on -fno-math-errno
          -CG:load_exe=1 +FDO
301.apsi: -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

BIOS Configuration Notes
Node Interleaving is Disabled

Other Configuration Notes
Taskset utility used to bind process to CPU(s)