



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itaotec

Servidor Itaotec LX211 (Intel Xeon 5160 processor)

SPECfp_rate2000 = 69.4

SPECfp_rate_base2000 = 69.4

SPEC license #: 9001 | Tested by: Itaotec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	79.3	93.7	4	79.3	93.7
171.swim	4	351	40.9	4	351	40.9
172.mgrid	4	215	38.9	4	215	38.9
173.applu	4	264	36.9	4	264	36.9
177.mesa	4	55.4	117	4	55.4	117
178.galgel	4	65.8	205	4	65.8	205
179.art	4	67.5	179	4	67.5	179
183.equake	4	98.5	61.2	4	98.5	61.2
187.facerec	4	104	84.6	4	104	84.6
188.amp	4	147	69.2	4	147	69.2
189.lucas	4	228	40.7	4	228	40.7
191.fma3d	4	191	50.9	4	191	50.9
200.sixtrack	4	94.0	54.3	4	94.0	54.3
301.apsi	4	190	63.6	4	190	63.6

Hardware

CPU: Intel Xeon 5160 processor (3.00 GHz, 4MB L2 shared, 1333 MHz system bus)
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4096KB(I+D) on chip, per chip, shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 6x2GB DDR2-RAM PC2-5300F (CAS 5-5-5)ECC
 Disk Subsystem: 1 x 120GB Serial ATA 7200 RPM
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
 Compiler: Intel C++ Compiler 9.1
 Build 20060519Z (for 32-bit applications),
 Intel Fortran Compiler 9.1
 Build 20060519Z (for 32-bit applications),
 Microsoft Visual Studio 2005 (for libraries,
 MicroQuill SmartHeap for SMP Library 8.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

178.galgel: -FI /F32000000

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO

for C programs: -fast +FDO shlSMPMt.lib

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>